



Poles	A	B
2	4.25 (.167)	.049 (1.25)
3	5.50 (.217)	.098 (2.50)
4	6.75 (.266)	.148 (3.75)
5	8.00 (.315)	.197 (5.00)
6	9.25 (.364)	.246 (6.25)
7	10.50 (.413)	.295 (7.50)
8	11.75 (.463)	.344 (8.75)
9	13.00 (.512)	.394 (10.00)
10	14.25 (.561)	.443 (11.25)
11	15.50 (.610)	.492 (12.50)
12	16.75 (.659)	.541 (13.75)
13	18.00 (.709)	.591 (15.00)
14	19.25 (.758)	.640 (16.25)
15	20.50 (.807)	

**SPECIFICATIONS**  
Voltage rating: 250 volts  
Current rating: 1 amp  
Contact material: Brass tin plated  
Contact resistance: 10 milliohm max.  
Insulation material: Nylon 66, UL94V-0  
Insulation resistance: 100 megohms min.  
Withstanding: 250 VAC/minute  
Temperature range: -25°C to +85°C  
Poles: 2-15

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
440 Lincoln Blvd., Middlesex, New Jersey 08846  
Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-1147-XX**

Description: Disconnectable connector, 1.25mm (.049") pitch