

# SN54HC32, SN74HC32 QUADRUPLE 2-INPUT POSITIVE-OR GATES

D2884. DECEMBER 1982—REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

## description


These devices contain four independent 2-input OR gates. They perform the Boolean functions  $Y = A + B$  or  $Y = \overline{A} \cdot \overline{B}$  in positive logic.

The SN54HC32 is characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74HC32 is characterized for operation from  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

FUNCTION TABLE  
(each gate)

INPUTS		OUTPUT
A	B	Y
H	X	H
X	H	H
L	L	L

## logic symbol†




†This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.


Pin numbers shown are for D, J, and N packages.

SN54HC32 . . . J PACKAGE  
SN74HC32 . . . D OR N PACKAGE

(TOP VIEW)



SN54HC32 . . . FK PACKAGE  
(TOP VIEW)



NC—No internal connection

## logic diagram (positive logic)



2

HCMOS Devices

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1982, Texas Instruments Incorporated

**TEXAS**  
**INSTRUMENTS**

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265

# SN54HC32, SN74HC32 QUADRUPLE 2-INPUT POSITIVE-OR GATES

**absolute maximum ratings over operating free-air temperature range<sup>†</sup>**

Supply voltage, V <sub>CC</sub> . . . . .	-0.5 V to 7 V
Input clamp current, I <sub>IK</sub> (V <sub>I</sub> < 0 or V <sub>I</sub> > V <sub>CC</sub> ) . . . . .	±20 mA
Output clamp current, I <sub>OK</sub> (V <sub>O</sub> < 0 or V <sub>O</sub> > V <sub>CC</sub> ) . . . . .	±20 mA
Continuous output current, I <sub>O</sub> (V <sub>O</sub> = 0 to V <sub>CC</sub> ) . . . . .	±25 mA
Continuous current through V <sub>CC</sub> or GND pins . . . . .	±50 mA
Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package . . . . .	300°C
Lead temperature 1.6 mm (1/16 in) from case for 10 s: D or N package . . . . .	260°C
Storage temperature range . . . . .	-65°C to 150°C

**2**

<sup>†</sup>Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

## HCMOS Devices

### recommended operating conditions

		SN54HC32			SN74HC32			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V <sub>CC</sub>	Supply voltage	2	5	6	2	5	6	V
V <sub>IH</sub>	High-level input voltage	V <sub>CC</sub> = 2 V V <sub>CC</sub> = 4.5 V V <sub>CC</sub> = 6 V	1.5 3.15 4.2		1.5 3.15 4.2			V
V <sub>IL</sub>	Low-level input voltage	V <sub>CC</sub> = 2 V V <sub>CC</sub> = 4.5 V V <sub>CC</sub> = 6 V	0 0 0	0.3 0.9 1.2	0 0 0	0.3 0.9 1.2		V
V <sub>I</sub>	Input voltage		0	V <sub>CC</sub>	0	V <sub>CC</sub>	V <sub>CC</sub>	V
V <sub>O</sub>	Output voltage		0	V <sub>CC</sub>	0	V <sub>CC</sub>	V <sub>CC</sub>	V
t <sub>t</sub>	Input transition (rise and fall) times	V <sub>CC</sub> = 2 V V <sub>CC</sub> = 4.5 V V <sub>CC</sub> = 6 V	0 0 0	1000 500 400	0 0 0	1000 500 400		ns
T <sub>A</sub>	Operating free-air temperature		-55	125	-40	85	85	°C

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	V <sub>CC</sub>	T <sub>A</sub> = 25°C			SN54HC32	SN74HC32	UNIT
			MIN	TYP	MAX			
V <sub>OH</sub>	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> . I <sub>OH</sub> = -20 μA	2 V	1.9	1.998	1.9	1.9	1.9	V
		4.5 V	4.4	4.499	4.4	4.4	4.4	
	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> . I <sub>OH</sub> = -4 mA	6 V	5.9	5.999	5.9	5.9	5.9	
		4.5 V	3.98	4.30	3.7	3.84		
V <sub>OL</sub>	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> . I <sub>OL</sub> = 20 μA	6 V	5.48	5.80	5.2	5.34		V
		2 V	0.002	0.1	0.1	0.1	0.1	
	V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> . I <sub>OL</sub> = 4 mA	4.5 V	0.001	0.1	0.1	0.1	0.1	
		6 V	0.001	0.1	0.1	0.1	0.1	
I <sub>I</sub>	V <sub>I</sub> = V <sub>CC</sub> or 0	4.5 V	0.17	0.26	0.4	0.4	0.33	
		6 V	0.15	0.26	0.4	0.4	0.33	
I <sub>CC</sub>	V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0	6 V		2	40	20	20	μA
C <sub>i</sub>		2 to 6 V	3	10	10	10	10	pF

**SN54HC32, SN74HC32**  
**QUADRUPLE 2-INPUT POSITIVE-OR GATES**

**switching characteristics over recommended operating free-air temperature range (unless otherwise noted),  $C_L = 50 \text{ pF}$  (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V <sub>CC</sub>	$T_A = 25^\circ\text{C}$			SN54HC32		SN74HC32		UNIT
				MIN	typ	MAX	MIN	MAX	MIN	MAX	
$t_{pd}$	A or B	Y	2 V	50	100		150		125		ns
			4.5 V	10	20		30		25		
			6 V	8	17		25		21		
$t_t$		Y	2 V	38	75		110		95		ns
			4.5 V	8	15		22		19		
			6 V	6	13		19		16		

$C_{pd}$	Power dissipation capacitance per gate	No load, $T_A = 25^\circ\text{C}$	20 pF typ
----------	--	-----------------------------------	-----------

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2

HCMOS Devices

TEXAS  
INSTRUMENTS

POST OFFICE BOX 655012 • DALLAS, TEXAS 75265