



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

60 MODII HDR DRRA SHRD .100CL

AMPMODU | AMPMODU Headers

2-103166-8

TE Internal Number: 2-103166-8

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **60**

Header Type **Shrouded**

Product Drawings

[HDR ASSY, MOD II, SHROUDED, 4 SIDES, DBL ROW, .100X.100 RIGHT ANGLE, W/ .025 SQ POSTS](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

	Strain Relief	Without
	Board Standoff	With
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	60
	Number of Rows	2
	Keyed	No
	Selectively Loaded	No
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	750 Vrms
<hr/>		
Body Features	Header Type	Shrouded
	Post Size	.64 mm [.025 in]
<hr/>		
Contact Features	Contact Protection	With
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Mating Area Plating Material	Gold
	Contact Protection Type	Shrouded
Contact Current Rating (A)	3	
<hr/>		
Termination Features	Termination Post Length	3.43 mm [.135 in]
	Termination End Plating Thickness (µin)	100 – 200
	Termination End Plating Material	Tin
	Termination Method to PC Board	Through Hole
<hr/>		
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Mating Connector Lock Type	Detent Windows
	Panel Mount Retention	Without
	Mating Alignment	With
	Mating Connector Lock	With

Mating Alignment Type

Polarization

Housing Features

Centerline

2.54 mm [.1 in]

Housing Color

Black

Housing Material

Thermoplastic

Housing Style

4-Sided

Dimensions

Shrouded End Dimension

1.68 mm [.066 in]

PCB Thickness (Recommended)

1.397 mm [.055 in]

Mating Post Length

8.08 mm [.318 in]

Usage Conditions

Operating Temperature Range (°C)

-65 – 105

High Temperature Housing

No

Operation/Application

High Speed Serial Data Connector

No

Industry Standards

UL Flammability Rating

UL 94V-0

Approved Standards

CSA LR7189, UL E28476

Packaging Features

Packaging Quantity

24

Packaging Method

Tray

Product Compliance

[Statement of Compliance](#)
PDF[VIEW ALL PRODUCT COMPLIANCE](#)