



**SPECIFICATIONS**

CURRENT RATING:1AMP  
 INSULATOR RESISTANCE:5000MΩMIN  
 DIELECTRIC WITHSTANDING:AC 500V  
 OPERATING TEMPERATURE:-40°C-+105°C  
 CONTACT MATERIAL:PHOSPHOR BRONZE OR BRONZE  
 INSULATOR MATERIAL:POLYESTER UL94V-0  
 NYLON-6T  
 FINISH:GOLD FLASH

**ORDER INFORMATION:**

2142-1 X ?? -S -D1 -L1  
 Pin Length:L1: A:2.8mm/B:2.0mm  
 L2: A:6.0mm/B:3.0mm  
 Height: D1:1.40mm  
 D2:1.70mm  
 D3:2.50mm  
 S:Straight  
 No of Contacts 2~50  
 Single Row



**易昕企業有限公司**  
 LEAMAX ENTERPRISE CO., LTD.

PROJ		SCALE : F DO NOT SCALE DWG	MOLD NO	2142A1	
APP			MODEL	FILE NO	REV.
CHK	CCJ	90.11.29		P/H P: 1.27mm 180' single row	X1
DGN	AMY	90.11.29	UNIT	SHT 1 OF 1	SIZE
DRW	SHIEH	90.11.29	MM		A4