



# 74VHC175 Quad D Flip-Flop

## General Description

The VHC175 is an advanced high-speed CMOS device fabricated with silicon gate CMOS technology. It achieves the high-speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation.

The VHC175 is a high-speed quad D flip-flop. The device is useful for general flip-flop requirements where clock and clear inputs are common. The information on the D inputs is stored during the LOW-to-HIGH clock transition. Both true and complemented outputs of each flip-flop are provided. A Master Reset input resets all flip-flops, independent of the Clock or D inputs, when LOW.


An input protection circuit insures that 0V to 7V can be applied to the input pins without regard to the supply voltage. This device can be used to interface 5V to 3V systems and two supply systems such as battery backup. This circuit prevents device destruction due to mismatched supply and input voltages.

## Features

- High speed
- Low power dissipation:  $I_{CC} = 4 \mu A$  (max) at  $T_A = 25^\circ C$
- High noise immunity:  $V_{NIH} = V_{NIL} = 28\% V_{CC}$  (min)
- All inputs are equipped with a power down protection function
- Balanced propagation delays:  $t_{PLH} \approx t_{PHL}$
- Wide operating voltage range:  $V_{CC}$  (opr) = 2V ~ 5.5V
- Low noise:  $V_{OLP} = 0.8V$  (max)
- Pin and function compatible with 74HC175
- Edge-triggered D-type inputs
- Buffered positive edge-triggered clock
- Asynchronous common reset
- True and complement output


**Ordering Code:** See Section 5

## Logic Symbols




Pin Names	Description
D <sub>0</sub> -D <sub>3</sub>	Data Inputs
CP	Clock Pulse Input
MR	Master Reset Input
Q <sub>0</sub> -Q <sub>3</sub>	True Outputs
Q̄ <sub>0</sub> -Q̄ <sub>3</sub>	Complement Outputs

## Connection Diagram



### Pin Assignment for SSOP and SOIC



## Functional Description


The VHC175 consists of four edge-triggered D flip-flops with individual D inputs and Q and  $\bar{Q}$  outputs. The Clock and Master Reset are common. The four flip-flops will store the state of their individual D inputs on the LOW-to-HIGH clock (CP) transition, causing individual Q and  $\bar{Q}$  outputs to follow. A LOW input on the Master Reset ( $\overline{MR}$ ) will force all Q outputs LOW and  $\bar{Q}$  outputs HIGH independent of Clock or Data inputs. The VHC175 is useful for general logic applications where a common Master Reset and Clock are acceptable.

## Truth Table

Inputs	Outputs	
@ $t_n, \overline{MR} = H$	@ $t_{n+1}$	
$D_n$	$Q_n$	$\bar{Q}_n$
L	L	H
H	H	L

H = HIGH Voltage Level  
 L = LOW Voltage Level  
 $t_n$  = Bit Time before Clock Pulse  
 $t_{n+1}$  = Bit Time after Clock Pulse

## Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

## Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage ( $V_{CC}$ )	-0.5V to +7.0V
DC Input Voltage ( $V_{IN}$ )	-0.5V to +7.0V
DC Output Voltage ( $V_{OUT}$ )	-0.5V to $V_{CC} + 0.5V$
Input Diode Current ( $I_{IK}$ )	-20 mA
Output Diode Current ( $I_{OK}$ )	$\pm 20$ mA
DC Output Current ( $I_{OUT}$ )	$\pm 25$ mA
DC $V_{CC}$ /GND Current ( $I_{CC}$ )	$\pm 50$ mA
Storage Temperature ( $T_{STG}$ )	-65°C to +150°C
Lead Temperature ( $T_L$ ) (Soldering, 10 seconds)	300°C

Note 1: Absolute Maximum Ratings are values beyond which the device may be damaged or have its useful life impaired. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation outside databook specifications.

## Recommended Operating Conditions

Supply Voltage ( $V_{CC}$ )	2.0V to +5.5V
Input Voltage ( $V_{IN}$ )	0V to +5.5V
Output Voltage ( $V_{OUT}$ )	0V to $V_{CC}$
Operating Temperature ( $T_{OPP}$ )	-40°C to +85°C
Input Rise and Fall Time ( $t_r, t_f$ )	
$V_{CC} = 3.3V \pm 0.3V$	0 ~ 100 ns/V
$V_{CC} = 5.0V \pm 0.5V$	0 ~ 20 ns/V

## DC Characteristics for 'VHC Family Devices

Symbol	Parameter	$V_{CC}$ (V)	74VHC				Units	Conditions	
			$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$			
			Min	Typ	Max	Min			Max
$V_{IH}$	High Level Input Voltage	2.0 3.0-5.5	1.50 0.7 $V_{CC}$			1.50 0.7 $V_{CC}$	V		
$V_{IL}$	Low Level Input Voltage	2.0 3.0-5.5		0.50 0.3 $V_{CC}$		0.50 0.3 $V_{CC}$	V		
$V_{OH}$	High Level Output Voltage	2.0 3.0 4.5	1.9 2.9 4.4	2.0 3.0 4.5		1.9 2.9 4.4	V	$V_{IN} = V_{IH}$ or $V_{IL}$	$I_{OH} = -50 \mu\text{A}$
		3.0 4.5	2.58 3.94			2.48 3.80	V		$I_{OH} = -4 \text{ mA}$ $I_{OH} = -8 \text{ mA}$
$V_{OL}$	Low Level Output Voltage	2.0 3.0 4.5		0.0 0.0 0.0	0.1 0.1 0.1	0.1 0.1 0.1	V	$V_{IN} = V_{IH}$ or $V_{IL}$	$I_{OL} = 50 \mu\text{A}$
		3.0 4.5			0.36 0.36	0.44 0.44	V		$I_{OL} = 4 \text{ mA}$ $I_{OL} = 8 \text{ mA}$
$I_{IN}$	Input Leakage Current	0-5.5			$\pm 0.1$	$\pm 1.0$	$\mu\text{A}$	$V_{IN} = 5.5V$ or GND	
$I_{CC}$	Quiescent Supply Current	5.5			4.0	40.0	$\mu\text{A}$	$V_{IN} = V_{CC}$ or GND	

## DC Characteristics for 'VHC Family Devices: See Section 2 for Waveforms (Continued)

Symbol	Parameter	V <sub>CC</sub> (V)	74VHC			Units	Conditions	Fig. No.
			T <sub>A</sub> = 25°C		T <sub>A</sub> = -40°C to +85°C			
			Typ	Limits	Limits			
V <sub>OLP</sub> *	Quiet Output Maximum Dynamic V <sub>OL</sub>	5.0	0.4	0.8		V	C <sub>L</sub> = 50 pF	2-11, 12
V <sub>OLV</sub> *	Quiet Output Minimum Dynamic V <sub>OL</sub>	5.0	-0.4	-0.8		V	C <sub>L</sub> = 50 pF	2-11, 12
V <sub>IHD</sub> *	Minimum High Level Dynamic Input Voltage	5.0		3.5		V	C <sub>L</sub> = 50 pF	2-11, 12
V <sub>ILD</sub> *	Maximum Low Level Dynamic Input Voltage	5.0		1.5		V	C <sub>L</sub> = 50 pF	2-11, 12

\*Parameter guaranteed by design.

## AC Electrical Characteristics for 'VHC: See Section 2 for Waveforms

Symbol	Parameter	V <sub>CC</sub> (V)	74VHC			74VHC		Units	Conditions	Fig. No.
			T <sub>A</sub> = 25°C			T <sub>A</sub> = -40°C to +85°C				
			Min	Typ	Max	Min	Max			
f <sub>MAX</sub>	Maximum Clock Frequency	3.3 ± 0.3	90	140		75		MHz	C <sub>L</sub> = 15 pF	
			50	75		45			C <sub>L</sub> = 50 pF	
		5.0 ± 0.5	150	210		125		MHz	C <sub>L</sub> = 15 pF	
			85	115		75			C <sub>L</sub> = 50 pF	
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay Time (CP to Q <sub>n</sub> or $\bar{Q}_n$ )	3.3 ± 0.3	7.5	11.5		1.0	13.5	ns	C <sub>L</sub> = 15 pF	2-5, 6
			10.0	15.0		1.0	17.0		C <sub>L</sub> = 50 pF	2-5, 6
		5.0 ± 0.5	4.8	7.3		1.0	8.5	ns	C <sub>L</sub> = 15 pF	2-5, 6
			6.3	9.3		1.0	10.5		C <sub>L</sub> = 50 pF	2-5, 6
t <sub>PLH</sub> , t <sub>PHL</sub>	Propagation Delay Time (MR to Q <sub>n</sub> or $\bar{Q}_n$ )	3.3 ± 0.3	6.3	10.1		1.0	12.0	ns	C <sub>L</sub> = 15 pF	2-5, 6
			8.8	13.6		1.0	15.5		C <sub>L</sub> = 50 pF	2-5, 6
		5.0 ± 0.5	4.3	6.4		1.0	7.5	ns	C <sub>L</sub> = 15 pF	2-5, 6
			5.8	8.4		1.0	9.5		C <sub>L</sub> = 50 pF	2-5, 6
t <sub>OSLH</sub> , t <sub>OSHL</sub>	Output to Output Skew	3.3 ± 0.3		1.5		1.5		C <sub>L</sub> = 50 pF (Note 1)		
		5.0 ± 0.5		1.0		1.0		C <sub>L</sub> = 50 pF (Note 1)		
C <sub>IN</sub>	Input Capacitance		4	10		10	pF	V <sub>CC</sub> = Open		
C <sub>PD</sub>	Power Dissipation Capacitance		44				pF	(Note 2)		

**Note 1:** Parameter guaranteed by design.  $t_{OSLH} = |t_{PLH,max} - t_{PLH,min}|$ ;  $t_{OSHL} = |t_{PHL,max} - t_{PHL,min}|$ .

**Note 2:** C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained from the equation:  $I_{CC}(opr.) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}/4$  (per F/F), and the total C<sub>PD</sub> when n pcs of the Flip Flop operate can be calculated by the following equation:  $C_{PD}(total) = 30 + 14 \cdot n$

## AC Operating Requirements for VHC: See Section 2 for Waveforms

Symbol	Parameter	*V <sub>CC</sub> (V)	74VHC		74VHC		Units	Conditions	Fig. No.
			T <sub>A</sub> = 25°C		T <sub>A</sub> = -40°C to +85°C				
			Typ	Guaranteed Minimum					
t <sub>W(L)</sub> t <sub>W(H)</sub>	Minimum Pulse Width (CP)	3.3 5.0		5.0 5.0	5.0 5.0		ns		2-6
t <sub>W(L)</sub>	Minimum Pulse Width ( $\overline{MR}$ )	3.3 5.0		5.0 5.0	5.0 5.0		ns		2-6
t <sub>S</sub>	Minimum Setup Time (Dn to CP)	3.3 5.0		5.0 4.0	5.0 4.0		ns		2-9
t <sub>H</sub>	Minimum Hold Time (Dn to CP)	3.3 5.0		1.0 1.0	1.0 1.0		ns		2-9
t <sub>rem</sub>	Minimum Removal Time ( $\overline{MR}$ )	3.3 5.0		5.0 5.0	5.0 5.0		ns		2-6, 9

\*V<sub>CC</sub> is 3.3 ± 0.3V or 5.0 ± 0.5V