


N-CHANNEL JFETs



SOT-23/TO-236AB

ELECTRICAL CHARACTERISTICS at $T_A = 25^\circ\text{C}$

Device Type	$V_{(B)GSS}$		I_{GSS}		$V_{GS(off)}$		I_{DSS}			g_{fs}		C_{iss}^1		C_{rss}^1		r_{DS} Max.	Pinning 1, 2, 3			
					Limits	Conditions														
	Min. @ I_G (V)	Max. @ V_{DS} (μA)	Min. (nA)	Max. (V)	Min. (V)	Max. (I_D) (nA)	Min. (mA)	Max. @ V_{DS} (mA)	Min. (V)	Max. @ V_{DS} (mS)	Max. @ V_{DS} (pF)	Max. @ V_{DS} (V)	Max. (Ω)							
TMPPF3819	-25	-1.0	-2.0	-15	—	-8.0	15	2.0	2.0	20	15	2.0	6.5	15	8.0	15	4.0	15	—	DSG
TMPPF3821	-50	-1.0	-1.0	-30	—	-4.0	10	1.0	0.5	2.5	15	1.5	4.5	15	6.0	15	2.0	15	—	DSG
TMPPF3822	-50	-1.0	-1.0	-30	—	-6.0	10	1.0	2.0	10	15	3.0	6.5	15	6.0	15	2.0	15	—	DSG
TMPPF3823	-30	-1.0	-1.0	-20	—	-8.0	10	1.0	4.0	20	15	3.5	6.5	15	6.0	15	2.0	15	—	DSG
TMPPF3824	-50	-1.0	-1.0	-30	—	-8.0	15	0.5	4.0	20	15	3.5	6.5	15	6.0	15	2.0	15	250	DSG
TMPPF4091	-40	-1.0	-1.0	-20	-5.0	-10	20	1.0	30	—	20	—	—	—	16	20	5.0	-20 ³	30	DSG
TMPPF4092	-40	-1.0	-1.0	-20	-2.0	-7.0	20	1.0	15	—	20	—	—	—	16	20	5.0	-20 ³	50	DSG
TMPPF4093	-40	-1.0	-1.0	-20	-1.0	-5.0	20	1.0	8.0	—	20	—	—	—	16	20	5.0	-20 ³	80	DSG
TMPPF4117	-40	-1.0	-0.01	-20	-0.6	-1.8	10	1.0	0.03	0.09	10	0.07	0.21	10	3.0	10	1.5	10	—	DSG
TMPPF4118	-40	-1.0	-0.01	-20	-1.0	-3.0	10	1.0	0.08	0.24	10	0.08	0.25	10	3.0	10	1.5	10	—	DSG
TMPPF4119	-40	-1.0	-0.01	-20	-2.0	-6.0	10	1.0	0.2	0.6	10	0.10	0.33	10	3.0	10	1.5	10	—	DSG
TMPPF4220	-30	-1.0	-1.0	-15	—	-4.0	15	1.0	0.5	3.0	15	1.0	4.0	15	6.0	15	2.0	15	—	DSG
TMPPF4221	-30	-1.0	-1.0	-15	—	-6.0	15	1.0	2.0	6.0	15	2.0	5.0	15	6.0	15	2.0	15	—	DSG
TMPPF4222	-30	-1.0	-1.0	-15	—	-8.0	15	1.0	5.0	15	15	2.5	6.0	15	6.0	15	2.0	15	—	DSG
TMPPF4223	-30	-1.0	-1.0	-20	—	-8.0	15	1.0	3.0	18	15	3.0	7.0	15	6.0	15	2.0	15	—	DSG
TMPPF4224	-30	-1.0	-1.0	-20	—	-8.0	15	1.0	2.0	20	15	2.0	7.5	15	6.0	15	2.0	15	—	DSG
TMPPF4391	-40	-1.0	-1.0	-20	-4.0	-10	20	1.0	5.0	150	20	—	—	—	16	20	5.0	-12 ³	30	DSG
TMPPF4392	-40	-1.0	-1.0	-20	-2.0	-5.0	20	1.0	25	100	20	—	—	—	16	20	5.0	-7 ³	60	DSG
TMPPF4393	-40	-1.0	-1.0	-20	-0.5	-3.0	20	1.0	5.0	30	20	—	—	—	16	20	5.0	-5 ³	100	DSG
TMPPF4416	-30	-1.0	-1.0	-20	—	-6.0	15	1.0	5.0	15	15	4.5	7.5	15	4.5	15	1.2	15	—	DSG
TMPPF4416A	-35	-1.0	-1.0	-20	-2.5	-6.0	15	1.0	5.0	15	15	4.5	7.5	15	4.5	15	1.2	15	—	DSG
TMPPF4856	-40	-1.0	-1.0	-20	-4.0	-10	15	1.0	50	—	15	—	—	—	18	-10 ³	8.0	-10 ³	25	DSG
TMPPF4857	-40	-1.0	-1.0	-20	-2.0	-6.0	15	1.0	20	100	15	—	—	—	18	-10 ³	8.0	-10 ³	40	DSG
TMPPF4858	-40	-1.0	-1.0	-20	-0.8	-4.0	15	1.0	8.0	80	15	—	—	—	18	-10 ³	8.0	-10 ³	60	DSG
TMPPF4859	-30	-1.0	-1.0	-15	-4.0	-10	15	1.0	50	—	15	—	—	—	18	-10 ³	8.0	-10 ³	25	DSG
TMPPF4860	-30	-1.0	-1.0	-15	-2.0	-6.0	15	1.0	20	100	15	—	—	—	18	-10 ³	8.0	-10 ³	40	DSG
TMPPF4861	-30	-1.0	-1.0	-15	-0.8	-4.0	15	1.0	8.0	80	15	—	—	—	18	-10 ³	8.0	-10 ³	60	DSG
TMPPF5163	-25	-1.0	-1.0	-15	0.4	8.0	15	1.0 ²	1.0	40	15	2.0	9.0	15	12	15	3.0	15	—	DSG
TMPPF5245	-30	-1.0	-1.0	-20	-1.0	-6.0	15	1.0	5.0	15	15	4.0	—	15	4.5	15	1.5	15	—	DSG
TMPPF5246	-30	-1.0	-1.0	-20	-0.5	-4.0	15	1.0	1.5	7.0	15	2.5	—	15	4.5	15	1.5	15	—	DSG
TMPPF5247	-30	-1.0	-1.0	-20	-1.5	-8.0	15	1.0	8.0	24	15	4.0	—	15	4.5	15	1.5	15	—	DSG
TMPPF5248	-30	-1.0	-5.0	-20	-1.0	-8.0	15	1.0	4.0	20	15	3.0	—	15	6.0	15	2.0	15	—	DSG
TMPPF5358	-40	-1.0	-1.0	-20	-0.5	-3.0	15	100	1.0	1.0	15	1.0	3.0	15	6.0	15	2.0	15	—	DSG
TMPPF5359	-40	-1.0	-1.0	-20	-0.8	-4.0	15	100	0.6	1.6	15	1.2	3.6	15	6.0	15	2.0	15	—	DSG
TMPPF5360	-40	-1.0	-1.0	-20	-0.8	-4.0	15	100	1.5	3.0	15	1.4	4.2	15	6.0	15	2.0	15	—	DSG

- NOTES: 1) $V_{GS} = 0\text{ V}$.
 2) I_D in μA .
 3) $V_{DS} = 0\text{ V}$, V_{GS} in volts.
 4) $I_D = 10\ \mu\text{A}$.
 5) $I_D = 5.0\ \mu\text{A}$.
 6) $I_D = 1.0\ \text{mA}$.
 7) $I_D = 500\ \mu\text{A}$.
 8) $I_D = 200\ \mu\text{A}$.

Continued next page...

N-CHANNEL JFETs

SOT-23/TO-236AB

ELECTRICAL CHARACTERISTICS continued

Device Type	V _{BRYGSS}		I _{GSS}		V _{GS(on)}				I _{DSS}			g _{fs}			C _{ISS} ¹		C _{RSS} ¹		r _{DS} Max.	Pinning 1, 2, 3
					Limits		Conditions													
	Min.	@ I _G	Max.	@ V _{DS}	Min.	Max.	V _{DS}	I _D	Min.	Max.	@ V _{DS}	Min.	Max.	@ V _{DS}	Max.	@ V _{DS}	Max.	@ V _{DS}	(Ω)	
TMPF5361	-40	-1.0	-1.0	-20	-1.0	-6.0	15	100	2.5	5.0	15	1.5	4.5	15	6.0	15	2.0	15	—	DSG
TMPF5362	-40	-1.0	-1.0	-20	-2.0	-7.0	15	100	4.0	8.0	15	2.0	5.5	15	6.0	15	2.0	15	—	DSG
TMPF5363	-40	-1.0	-1.0	-20	-2.5	-8.0	15	100	7.0	14	15	2.5	6.0	15	6.0	15	2.0	15	—	DSG
TMPF5364	-40	-1.0	-1.0	-20	-2.5	-8.0	15	100	9.0	18	15	2.7	6.5	15	6.0	15	2.0	15	—	DSG
TMPF5457	-25	-10	-1.0	-15	-0.5	-6.0	15	10	1.0	5.0	15	1.0	5.0	15	7.0	15	3.0	15	—	DSG
TMPF5458	-25	-10	-1.0	-15	-1.0	-7.0	15	10	2.0	9.0	15	1.5	5.5	15	7.0	15	3.0	15	—	DSG
TMPF5459	-25	-10	-1.0	-15	-2.0	-8.0	15	10	4.0	16	15	2.0	6.0	15	7.0	15	3.0	15	—	DSG
TMPF5484	-25	-10	-1.0	-20	-0.3	-3.0	15	10	1.0	5.0	15	3.0	6.0	15	5.0	15	1.0	15	—	DSG
TMPF5485	-25	-1.0	-1.0	-20	-0.5	-4.0	15	10	4.0	10	15	3.5	7.0	15	5.0	15	1.0	15	—	DSG
TMPF5486	-25	-1.0	-1.0	-20	-2.0	-6.0	15	10	8.0	20	15	4.0	8.0	15	5.0	15	1.2	15	—	DSG
TMPF5638	-30	-10	-1.0	-15	—	-12	15	10	50	—	20	—	—	—	10	-12 ³	4.0	-12 ³	30	DSG
TMPF5639	-30	-10	-1.0	-15	—	-8.0	15	1.0	25	—	20	—	—	—	10	-12 ³	4.0	-12 ³	60	DSG
TMPF5640	-30	-10	-1.0	-15	—	-6.0	15	10	5.0	—	20	—	—	—	10	-12 ³	4.0	-12 ³	100	DSG
TMPF5653	-30	-10	-1.0	-15	—	-12	15	10	4.0	—	20	—	—	—	10	-12 ³	3.5	-12 ³	50	DSG
TMPF5654	-25	-10	-1.0	-15	—	-8.0	15	10	15	—	20	—	—	—	10	-8.0 ³	3.5	-8.0 ³	100	DSG
TMPF5668	-25	-10	-1.0	-15	-0.2	-4.0	15	10	1.0	5.0	15	1.0	—	15	7.0	15	3.0	15	—	DSG
TMPF5669	-25	-10	-1.0	-15	-1.0	-6.0	15	10	4.0	10	15	1.6	—	15	7.0	15	3.0	15	—	DSG
TMPF5670	-25	-10	-1.0	-15	-2.0	-8.0	15	10	8.0	20	15	2.0	—	15	7.0	15	3.0	15	—	DSG
TMPF5949	-30	-1.0	-1.0	-15	-3.0	-7.0	15	100	12	18	15	3.0	—	15	6.0	15	2.0	15	—	DSG
TMPF5950	-30	-1.0	-1.0	-15	-2.5	-6.0	15	100	10	15	15	3.0	—	15	6.0	15	2.0	15	—	DSG
TMPF5951	-30	-1.0	-1.0	-15	-2.0	-5.0	15	100	7.0	13	15	3.0	—	15	6.0	15	2.0	15	—	DSG
TMPF5952	-30	-1.0	-1.0	-15	-1.3	-3.5	15	100	4.0	8.0	15	1.0	—	15	6.0	15	2.0	15	—	DSG
TMPF5953	-30	-1.0	-1.0	-15	-0.8	-3.0	15	100	2.5	5.0	15	1.0	—	15	6.0	15	2.0	15	—	DSG
TMPFBC264A	-30	-1.0	-1.0	-20	-0.5	—	15	10	2.0	4.5	15	2.5	—	15	4.0	15	1.2	15	—	DSG
TMPFBC264B	-30	-1.0	-1.0	-20	-0.5	—	15	10	3.5	6.5	15	3.0	—	15	4.0	15	1.2	15	—	DSG
TMPFBF264C	-30	-1.0	-1.0	-20	-0.5	—	15	10	5.0	8.0	15	3.5	—	15	4.0	15	1.2	15	—	DSG
TMPFBF264D	-30	-1.0	-1.0	-20	-0.5	—	15	10	7.0	12	15	4.0	—	15	4.0	15	1.2	15	—	DSG
TMPFBF244A	-30	-1.0	-5.0	-20	-0.5	-8.0	15	10	2.0	6.5	15	3.0	6.5	15	—	—	—	—	—	DSG
TMPFBF244B	-30	-1.0	-5.0	-20	-0.5	-8.0	15	10	6.0	15	15	3.0	6.5	15	—	—	—	—	—	DSG
TMPFBF244C	-30	-1.0	-5.0	-20	-0.5	-8.0	15	10	12	25	15	3.0	6.5	15	—	—	—	—	—	DSG
TMPFBF246A	-25	-1.0	-5.0	-15	-0.6	-14.5	15	10	30	80	15	—	—	—	—	—	—	—	65	DSG
TMPFBF246B	-25	-1.0	-5.0	-15	-0.6	-14.5	15	10	60	140	15	—	—	—	—	—	—	—	50	DSG
TMPFBF246C	-25	-1.0	-5.0	-15	-0.6	-14.5	15	10	110	250	15	—	—	—	—	—	—	—	35	DSG
TMPFBF256A	-30	-1.0	-5.0	-20	-0.5	-7.5	15	10	3.0	7.0	15	4.5	—	15	4.5	15	1.2	15	—	DSG
TMPFBF256B	-30	-1.0	-5.0	-20	-0.5	-7.5	15	10	6.0	13	15	4.5	—	15	4.5	15	1.2	15	—	DSG
TMPFBF256C	-30	-1.0	-5.0	-20	-0.5	-7.5	15	10	11	18	15	4.5	—	15	4.5	15	1.2	15	—	DSG
TMPFJ1111	-35	-1.0	-1.0	-15	-3.0	-10	5.0	1.0	20	—	15	—	—	—	16	15	5	-10 ³	30	DSG
TMPFJ1112	-35	-1.0	-1.0	-15	-1.0	-5.0	5.0	1.0	5.0	—	15	—	—	—	16	15	5	-10 ³	50	DSG
TMPFJ112A	-40	-1.0	-0.2	-1.0	-2.0	-7.0	5.0	1.0	15	—	15	—	—	—	16	15	5	-10 ³	50	DSG
TMPFJ113	-35	-1.0	-1.0	-15	—	-3.0	5.0	1.0	2.0	—	15	—	—	—	16	15	5	-10 ³	100	DSG

- NOTES: 1) V_{GS} = 0 V.
 2) I_D in μA.
 3) V_{DS} = 0 V, V_{GS} in volts.
 4) I_D = 10 μA.
 5) I_D = 5.0 μA.
 6) I_D = 1.0 mA.
 7) I_D = 500 μA.
 8) I_D = 200 μA.

Continued next page...

N-CHANNEL JFETs

SOT-23/TO-236AB

ELECTRICAL CHARACTERISTICS continued

Device Type	V _{(BR)GSS}		I _{GSS}		V _{GS(off)}				I _{DSS}			g _{fs}		C _{ISS} ¹		C _{RSS} ¹		r _{DS} Max.	Pinning 1, 2, 3	
					Limits		Conditions													
	Min.	@ I _G	Max.	@ V _{DS}	Min.	Max.	V _{DS}	I _D	Min.	Max.	@ V _{DS}	Min.	Max.	@ V _{DS}	Max.	@ V _{DS}	Max.			@ V _{DS}
(V)	(μA)	(nA)	(V)	(V)	(V)	(V)	(nA)	(mA)	(mA)	(V)	(mS)	(mS)	(V)	(pF)	(V)	(pF)	(V)	(Ω)		
TMPFJ113A	-40	-1.0	-0.2	-1.0	-1.0	-5.0	5.0	1.0	8.0	—	15	—	—	16	15	5	-10 ³	80	DSG	
TMPFJ201	-40	-1.0	-1.0	-2.0	-0.3	-1.5	20	10	0.2	1.0	20	0.5	—	20	4.0	20	1.0	20	—	DSG
TMPFJ202	-40	-1.0	-1.0	-2.0	-0.8	-4.0	20	10	0.9	4.5	20	1.0	—	20	4.0	20	1.0	20	—	DSG
TMPFJ203	-40	-1.0	-1.0	-2.0	-2.0	-1.0	20	10	4.0	20	20	1.5	—	20	6.0	20	1.2	20	—	DSG
TMPFJ230	-40	-1.0	-1.0	-3.0	-0.5	-3.0	20	1 ²	0.7	3.0	20	1.0	3.5	20	—	—	—	—	—	DSG
TMPFJ231	-40	-1.0	-1.0	-3.0	-1.5	-5.0	20	1 ²	2.0	6.0	20	1.5	4.0	20	—	—	—	—	—	DSG
TMPFJ232	-40	-1.0	-1.0	-3.0	-3.0	-6.0	20	1 ²	5.0	10	20	2.5	5.0	20	—	—	—	—	—	DSG
TMPFJ304	-30	-1.0	-1.0	2.0	-2.0	-6.0	15	1.0	5.0	15	15	4.5	7.5	15	—	—	—	—	—	DSG
TMPFJ305	-30	-1.0	-1.0	-2.0	-0.5	-3.0	15	1.0	1.0	8.0	15	3.0	—	15	—	—	—	—	—	DSG
TMPFJ308	-25	-1.0	-1.0	-15	-1.0	-6.5	10	1.0	12	60	10	8.0	—	10 ⁴	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFJ309	-25	-1.0	-1.0	-15	-1.0	-4.0	10	1.0	12	30	10	10	—	10 ⁴	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFJ310	-25	-1.0	-1.0	-15	-2.0	-6.5	10	1.0	24	60	10	8.0	—	10 ⁴	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFU308	-25	-1.0	-1.0	-15	-1.0	-6.0	10	1.0	12	60	10	—	—	—	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFU309	-25	-1.0	-1.0	-15	-1.0	-4.0	10	1.0	12	30	10	—	—	—	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFU310	-25	-1.0	-1.0	-15	-2.5	-6.0	10	1.0	24	60	10	—	—	—	7.5	-10 ³	3.5	-10 ³	—	DSG
TMPFU1897	-40	-1.0	-1.0	-2.0	-5.0	-1.0	20	1.0	30	—	20	—	—	—	16	20	3.5	20	30	DSG
TMPFU1898	-40	-1.0	-1.0	-2.0	-2.0	-7.0	20	1.0	15	—	20	—	—	—	16	20	3.5	20	50	DSG
TMPFU1899	-40	-1.0	-1.0	-2.0	-1.0	-5.0	20	1.0	8.0	—	20	—	—	—	16	20	3.5	20	80	DSG

- NOTES: 1) V_{GS} = 0 V.
 2) I_D in μA.
 3) V_{DS} = 0 V, V_{GS} in volts.
 4) I_D = 10 μA
 5) I_D = 5.0 μA
 6) I_D = 1.0 mA
 7) I_D = 500 μA
 8) I_D = 200 μA