


## NTC Thermistors

**Thermistor for temperature compensation and measurement, e.g. in transistor circuits**

Temperature range - 55 °C ... + 125 °C

Rated temperature + 25 °C



Type	$R_{25}$ $\Omega$	Ordering code	Min. qty.	Max. qty.	Price each in DM		
					Min. qty. +	250 +	500 +
$R_B$ tolerance $\pm 5\%$							
K164/ 68 /5%	68	B57164-K680-J	100	2000	-.63	-.55	-.50
K164/100 /5%	100	B57164-K101-J	100	2000	-.63	-.55	-.50
K164/150 /5%	150	B57164-K151-J	100	2000	-.63	-.55	-.50
K164/220 /5%	220	B57164-K221-J	100	2000	-.63	-.55	-.50
K164/330 /5%	330	B57164-K331-J	100	2000	-.63	-.55	-.50
K164/470 /5%	470	B57164-K471-J	100	2000	-.63	-.55	-.50
K164/ 1 k/5%	1 k	B57164-K102-J	100	2000	-.63	-.55	-.50
K164/ 2,2 k/5%	2,2 k	B57164-K222-J	100	2000	-.63	-.55	-.50
K164/ 3,3 k/5%	3,3 k	B57164-K332-J	100	2000	-.63	-.55	-.50
K164/ 4,7 k/5%	4,7 k	B57164-K472-J	100	2000	-.63	-.55	-.50
K164/ 6,8 k/5%	6,8 k	B57164-K682-J	100	2000	-.63	-.55	-.50
K164/ 10 k/5%	10 k	B57164-K103-J	100	2000	-.63	-.55	-.50
K164/ 15 k/5%	15 k	B57164-K153-J	100	2000	-.63	-.55	-.50
K164/ 22 k/5%	22 k	B57164-K223-J	100	2000	-.63	-.55	-.50
K164/ 33 k/5%	33 k	B57164-K333-J	100	2000	-.63	-.55	-.50
K164/ 47 k/5%	47 k	B57164-K473-J	100	2000	-.63	-.55	-.50
K164/ 68 k/5%	68 k	B57164-K683-J	100	2000	-.63	-.55	-.50
K164/100 k/5%	100 k	B57164-K104-J	100	2000	-.63	-.55	-.50
K164/470 k/5%	470 k	B57164-K474-J	100	2000	-.63	-.55	-.50

NTC thermistors of type K164 and C621 are also available as lab assortment; for details refer to page 330.