


Major Ratings and Characteristics

| Characteristics | 200CNQ... | Units |
|--|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform | 200 | A |
| V_{RRM} range | 35 to 45 | V |
| I_{FSM} @tp = 5 μ s sine | 26,000 | A |
| V_F @100Apk, $T_J = 125^\circ\text{C}$ (per leg) | 0.49 | V |
| T_J range | -55 to 150 | $^\circ\text{C}$ |

Description/Features

The 200CNQ center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 150 $^\circ\text{C}$ junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 150 $^\circ\text{C}$ T_J operation
- Center tap module
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



200CNQ... Series

Bulletin PD-2.257 rev. D 07/01

International
ISOR Rectifier

Voltage Ratings

| Part number | 200CNQ035 | 200CNQ040 | 200CNQ045 |
|---|-----------|-----------|-----------|
| V_R Max. DC Reverse Voltage (V) | 35 | 40 | 45 |
| V_{RWM} Max. Working Peak Reverse Voltage (V) | | | |

Absolute Maximum Ratings

| Parameters | 200CNQ | Units | Conditions |
|---|--------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current (Per Leg) * See Fig. 5 (Per Device) | 100 | A | 50% duty cycle @ $T_C = 114^\circ\text{C}$, rectangular wave form |
| | 200 | | |
| I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7 | 26,000 | A | 5 μs Sine or 3 μs Rect. pulse 10ms Sine or 6ms Rect. pulse |
| | 1550 | | |
| E_{AS} Non-Repetitive Avalanche Energy (Per Leg) | 135 | mJ | $T_J = 25^\circ\text{C}$, $I_{AS} = 20$ Amps, $L = 0.67$ mH |
| I_{AR} Repetitive Avalanche Current (Per Leg) | 20 | A | Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical |

Electrical Specifications

| Parameters | 200CNQ | Units | Conditions |
|--|--------|------------------|---|
| V_{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1) | 0.54 | V | @ 100A |
| | 0.68 | V | @ 200A |
| | 0.49 | V | @ 100A |
| | 0.64 | V | @ 200A |
| I_{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1) | 10 | mA | $T_J = 25^\circ\text{C}$ |
| | 500 | mA | $T_J = 125^\circ\text{C}$ |
| $V_{F(TO)}$ Threshold Voltage | 0.32 | V | $T_J = T_J$ max. |
| r_t Forward Slope Resistance | 0.81 | m Ω | |
| C_T Max. Junction Capacitance (Per Leg) | 5200 | pF | $V_R = 5V_{DC}$, (test signal range 100Khz to 1Mhz) 25°C |
| L_S Typical Series Inductance (Per Leg) | 7.0 | nH | From top of terminal hole to mounting plane |
| dv/dt Max. Voltage Rate of Change (Rated V_R) | 10000 | V/ μs | |

Thermal-Mechanical Specifications

(1) Pulse Width < 300 μs , Duty Cycle <2%

| Parameters | 200CNQ | Units | Conditions |
|---|------------|--------------------|--------------------------------------|
| T_J Max. Junction Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| T_{stg} Max. Storage Temperature Range | -55 to 150 | $^\circ\text{C}$ | |
| R_{thJC} Max. Thermal Resistance Junction to Case (Per Leg) | 0.40 | $^\circ\text{C/W}$ | DC operation * See Fig. 4 |
| R_{thJC} Max. Thermal Resistance Junction to Case (Per Package) | 0.20 | $^\circ\text{C/W}$ | DC operation |
| R_{thCS} Typical Thermal Resistance, Case to Heatsink | 0.10 | $^\circ\text{C/W}$ | Mounting surface, smooth and greased |
| wt Approximate Weight | 79(2.80) | g(oz.) | |
| T Mounting Torque | Min. | 24(20) | Kg-cm (lbf-in) |
| | Max. | 35(30) | |
| | Typ. | 13.5(12) | |
| | Max. | 46(40) | |
| Case Style | TO-244AB | | Modified JEDEC |




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics (Per Leg)




Fig. 5- Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6- Forward Power Loss Characteristics (Per Leg)




Fig. 7- Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8- Unclamped Inductive Test Circuit

(2) Formula used: $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$;

Pd = Forward Power Loss = $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);

Pd_{REV} = Inverse Power Loss = $V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = 80\%$ rated V_R

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
07/01



Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.