

Voltage regulator diodes

BZV55 series

FEATURES


- Total power dissipation: max. 500 mW
- Three tolerance series: $\pm 2\%$, $\pm 3\%$ and $\pm 5\%$
- Working voltage range: nom. 2.4 to 75 V (E24 range)
- Non-repetitive peak reverse power dissipation: max. 40 W.

APPLICATIONS

- Low-power voltage stabilizers or voltage references.

DESCRIPTION

Low-power voltage regulator diodes in small hermetically sealed glass SOD80C SMD packages. The diodes are available in the normalized E24 $\pm 2\%$ (BZV55-B), $\pm 3\%$ (BZV55-F) and $\pm 5\%$ (BZV55-C) tolerance range. The series consists of 37 types with nominal working voltages from 2.4 to 75 V.



LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
I_F	continuous forward current		–	250	mA
I_{ZSM}	non-repetitive peak reverse current	$t_p = 100 \mu s$; square wave; $T_j = 25^\circ C$ prior to surge		see Tables 1 and 2	
P_{tot}	total power dissipation	$T_{amb} \leq 50^\circ C$; note 1	–	400	mW
		tie-point $\leq 50^\circ C$; note 1	–	500	mW
P_{ZSM}	non-repetitive peak reverse power dissipation	$t_p = 100 \mu s$; square wave; $T_j = 25^\circ C$ prior to surge; see Fig.3	–	40	W
T_{stg}	storage temperature		–65	+200	$^\circ C$
T_j	junction temperature		–65	+200	$^\circ C$

Note

1. Device mounted on a ceramic substrate of $10 \times 10 \times 0.6$ mm.

Voltage regulator diodes

BZV55 series

ELECTRICAL CHARACTERISTICS

Total BZV55-B, F and C series

 $T_j = 25\text{ }^\circ\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MAX.	UNIT
V_F	forward voltage	$I_F = 10\text{ mA}$; see Fig.4	0.9	V
I_R	reverse current			
	BZV55-B/F/C2V4	$V_R = 1\text{ V}$	50	μA
	BZV55-B/F/C2V7	$V_R = 1\text{ V}$	20	μA
	BZV55-B/F/C3V0	$V_R = 1\text{ V}$	10	μA
	BZV55-B/F/C3V3	$V_R = 1\text{ V}$	5	μA
	BZV55-B/F/C3V6	$V_R = 1\text{ V}$	5	μA
	BZV55-B/F/C3V9	$V_R = 1\text{ V}$	3	μA
	BZV55-B/F/C4V3	$V_R = 1\text{ V}$	3	μA
	BZV55-B/F/C4V7	$V_R = 2\text{ V}$	3	μA
	BZV55-B/F/C5V1	$V_R = 2\text{ V}$	2	μA
	BZV55-B/F/C5V6	$V_R = 2\text{ V}$	1	μA
	BZV55-B/F/C6V2	$V_R = 4\text{ V}$	3	μA
	BZV55-B/F/C6V8	$V_R = 4\text{ V}$	2	μA
	BZV55-B/F/C7V5	$V_R = 5\text{ V}$	1	μA
	BZV55-B/F/C8V2	$V_R = 5\text{ V}$	700	nA
	BZV55-B/F/C9V1	$V_R = 6\text{ V}$	500	nA
	BZV55-B/F/C10	$V_R = 7\text{ V}$	200	nA
	BZV55-B/F/C11	$V_R = 8\text{ V}$	100	nA
	BZV55-B/F/C12	$V_R = 8\text{ V}$	100	nA
	BZV55-B/F/C13	$V_R = 8\text{ V}$	100	nA
BZV55-B/F/C15 to 75	$V_R = 0.7V_{Znom}$	50	nA	

Voltage regulator diodes

BZV55 series

Table 1 Per type BZV55-B/F/C2V4 to B/F/C24
 $T_j = 25^\circ\text{C}$; unless otherwise specified.

BZV55-B or F or C XXX	WORKING VOLTAGE V_z (V) at $I_{z\text{test}} = 5\text{ mA}$						DIFFERENTIAL RESISTANCE r_{diff} (Ω)				TEMP. COEFF. S_z (mV/K) at $I_{z\text{test}} = 5\text{ mA}$ (see Figs 5 and 6)			DIODE CAP. C_d (pF) at $f = 1\text{ MHz}$; $V_R = 0\text{ V}$		NON-REPETITIVE PEAK REVERSE CURRENT $I_{z\text{SM}}$ (A) at $t_p = 100\text{ }\mu\text{s}$; $T_{\text{amb}} = 25^\circ\text{C}$	
	Tol. $\pm 2\%$ (B)		Tol. $\pm 3\%$ (F)		Tol. $\pm 5\%$ (C)		at $I_{z\text{test}} = 1\text{ mA}$		at $I_{z\text{test}} = 5\text{ mA}$		MIN.		TYP.		MAX.		
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	TYP.	MAX.	TYP.	MAX.	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
	2V4	2.35	2.45	2.33	2.47	2.2	2.6	275	600	70	100	-3.5	-1.6	0	450	6.0	
2V7	2.65	2.75	2.62	2.78	2.5	2.9	300	600	75	100	-3.5	-2.0	0	450	6.0		
3V0	2.94	3.06	2.91	3.09	2.8	3.2	325	600	80	95	-3.5	-2.1	0	450	6.0		
3V3	3.23	3.37	3.20	3.40	3.1	3.5	350	600	85	95	-3.5	-2.4	0	450	6.0		
3V6	3.53	3.67	3.49	3.71	3.4	3.8	375	600	85	90	-3.5	-2.4	0	450	6.0		
3V9	3.82	3.98	3.78	4.02	3.7	4.1	400	600	85	90	-3.5	-2.5	0	450	6.0		
4V3	4.21	4.39	4.17	4.43	4.0	4.6	410	600	80	90	-3.5	-2.5	0	450	6.0		
4V7	4.61	4.79	4.56	4.84	4.4	5.0	425	500	50	80	-3.5	-1.4	0.2	300	6.0		
5V1	5.00	5.20	4.95	5.25	4.8	5.4	400	480	40	60	-2.7	-0.8	1.2	300	6.0		
5V6	5.49	5.71	5.43	5.77	5.2	6.0	80	400	15	40	-2.0	1.2	2.5	300	6.0		
6V2	6.08	6.32	6.01	6.39	5.8	6.6	40	150	6	10	0.4	2.3	3.7	200	6.0		
6V8	6.66	6.94	6.60	7.00	6.4	7.2	30	80	6	15	1.2	3.0	4.5	200	6.0		
7V5	7.35	7.65	7.28	7.72	7.0	7.9	30	80	6	15	2.5	4.0	5.3	150	4.0		
8V2	8.04	8.36	7.95	8.45	7.7	8.7	40	80	6	15	3.2	4.6	6.2	150	4.0		
9V1	8.92	9.28	8.83	9.37	8.5	9.6	40	100	6	15	3.8	5.5	7.0	150	3.0		
10	9.80	10.20	9.70	10.30	9.4	10.6	50	150	8	20	4.5	6.4	8.0	90	3.0		
11	10.80	11.20	10.67	11.33	10.4	11.6	50	150	10	20	5.4	7.4	9.0	85	2.5		
12	11.80	12.20	11.64	12.36	11.4	12.7	50	150	10	25	6.0	8.4	10.0	85	2.5		
13	12.70	13.30	12.61	13.39	12.4	14.1	50	170	10	30	7.0	9.4	11.0	80	2.5		
15	14.70	15.30	14.55	15.45	13.8	15.6	50	200	10	30	9.2	11.4	13.0	75	2.0		
16	15.70	16.30	15.50	16.50	15.3	17.1	50	200	10	40	10.4	12.4	14.0	75	1.5		
18	17.60	18.40	17.50	18.50	16.8	19.1	50	225	10	45	12.4	14.4	16.0	70	1.5		
20	19.60	20.40	19.40	20.60	18.8	21.2	60	225	15	55	14.4	16.4	18.0	60	1.5		
22	21.60	22.40	21.30	22.70	20.8	23.3	60	250	20	55	16.4	18.4	20.0	60	1.25		
24	23.50	24.50	23.30	24.70	22.8	25.6	60	250	25	70	18.4	20.4	22.0	55	1.25		

Voltage regulator diodes

BZV55 series

Table 2 Per type BZV55-B/F/C27 to B/F/C75
 $T_j = 25\text{ }^\circ\text{C}$; unless otherwise specified.

BZV55-B or F or C XXX	WORKING VOLTAGE V_z (V) at $I_{z\text{test}} = 2\text{ mA}$						DIFFERENTIAL RESISTANCE r_{diff} (Ω)						TEMP. COEFF. S_z (mV/K) at $I_{z\text{test}} = 2\text{ mA}$ (see Figs 5 and 6)			DIODE CAP. C_d (pF) at $f = 1\text{ MHz}$; $V_R = 0\text{ V}$	NON-REPETITIVE PEAK REVERSE CURRENT $I_{z\text{SM}}$ (A) at $t_p = 100\text{ }\mu\text{s}$; $T_{\text{amb}} = 25\text{ }^\circ\text{C}$	
	Tol. $\pm 2\%$ (B)			Tol. $\pm 3\%$ (F)			Tol. $\pm 5\%$ (C)			at $I_{z\text{test}} = 0.5\text{ mA}$		at $I_{z\text{test}} = 2\text{ mA}$		MIN.	TYP.			MAX.
	MIN.	MAX.		MIN.	MAX.		MIN.	MAX.		TYP.	MAX.	TYP.	MAX.					
27	26.50	27.50	26.20	27.80	25.1	28.9	65	300	80	25	80	21.4	23.4	25.3	50	1.0		
30	29.40	30.60	29.10	30.90	28.0	32.0	70	300	80	30	80	24.4	26.6	29.4	50	1.0		
33	32.30	33.70	32.00	34.00	31.0	35.0	75	325	80	35	80	27.4	29.7	33.4	45	0.9		
36	35.30	36.70	34.90	37.10	34.0	38.0	80	350	90	35	90	30.4	33.0	37.4	45	0.8		
39	38.20	39.80	37.80	40.20	37.0	41.0	80	350	130	40	130	33.4	36.4	41.2	45	0.7		
43	42.10	43.90	41.70	44.30	40.0	46.0	85	375	150	45	150	37.6	41.2	46.6	40	0.6		
47	46.10	47.90	45.60	48.40	44.0	50.0	85	375	170	50	170	42.0	46.1	51.8	40	0.5		
51	50.00	52.00	49.50	52.50	48.0	54.0	90	400	180	60	180	46.6	51.0	57.2	40	0.4		
56	54.90	57.10	54.30	57.70	52.0	60.0	100	425	200	70	200	52.2	57.0	63.8	40	0.3		
62	60.80	63.20	60.10	63.90	58.0	66.0	120	450	215	80	215	58.8	64.4	71.6	35	0.3		
68	66.60	69.40	66.00	70.00	64.0	72.0	150	475	240	90	240	65.6	71.7	79.8	35	0.25		
75	73.50	76.50	72.80	77.20	70.0	79.0	170	500	255	95	255	73.4	80.2	88.6	35	0.2		

Voltage regulator diodes

BZV55 series


THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j-t_p}$	thermal resistance from junction to tie-point		300	K/W
$R_{th\ j-a}$	thermal resistance from junction to ambient	see Fig.2 and note 1	380	K/W

Note


1. Device mounted on a ceramic substrate of $10 \times 10 \times 0.6$ mm.

GRAPHICAL DATA




Voltage regulator diodes

BZV55 series




- (1) $T_j = 25\text{ °C}$ (prior to surge).
- (2) $T_j = 150\text{ °C}$ (prior to surge).

Fig.3 Maximum permissible non-repetitive peak reverse power dissipation versus duration.




$T_j = 25\text{ °C}$.

Fig.4 Forward current as a function of forward voltage; typical values.



BZV55-B/F/C2V4 to B/F/C4V3.
 $T_j = 25\text{ to }150\text{ °C}$.

Fig.5 Temperature coefficient as a function of working current; typical values.



BZV55-B/F/C4V7 to B/F/C12.
 $T_j = 25\text{ to }150\text{ °C}$.

Fig.6 Temperature coefficient as a function of working current; typical values.