



SPECIFICATIONS

Current Rating: 3A Max.
 Voltage Rating: 250V AC,DC
 Withstanding: 1500V AC/minute
 Temperature Range: -40°C ~ 105°C

Dimensions		
Circuits	A	B
2	2.5	5.0
3	5.0	7.5
4	7.5	10.0
5	10.0	12.5
6	12.5	15.0
7	15.0	17.5
8	17.5	20.0
9	20.0	22.5
10	22.5	25.0
11	25.0	27.5
12	27.5	30.0
13	30.0	32.5
14	32.5	35.0
15	35.0	37.5
16	37.5	40.0
17	40.0	42.5
18	42.5	45.0
19	45.0	47.5
20	47.5	50.0

RoHS compliant

P.C.B. Hole Dimensions

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	07/15/82
				Checked	Lizzy	07/15/82
				Drawn	Tina	07/15/82
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-8813-XX**

Description: .098" Right Angle Pin Friction Lock Header