


## 3A SCHOTTKY BARRIER RECTIFIERS

 <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th colspan="3">Value Inch[mm]</th> </tr> <tr> <th>Dim.</th> <th>Min.</th> <th>Max.</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>1.000[25.40]</td> <td>---</td> </tr> <tr> <td>B</td> <td>0.335[8.51]</td> <td>0.375[9.52]</td> </tr> <tr> <td>C</td> <td>0.197[5.00]</td> <td>0.220[5.59]</td> </tr> <tr> <td>D</td> <td>0.048[1.22]</td> <td>0.052[1.32]</td> </tr> </tbody> </table>	Value Inch[mm]			Dim.	Min.	Max.	A	1.000[25.40]	---	B	0.335[8.51]	0.375[9.52]	C	0.197[5.00]	0.220[5.59]	D	0.048[1.22]	0.052[1.32]	<h3>PRODUCT FEATURES</h3> <ol style="list-style-type: none"> <li>1. FLAMMABILITY CLASSIFICATION 94V-0</li> <li>2. EXTREMELY LOW <math>V_f</math></li> <li>3. LOW STORED CHARGE</li> <li>4. MAJORITY CARRIER CONDUCTION</li> <li>5. LOW POWER LOSS/HIGH EFFICIENCY</li> <li>6. CASE: TRANSFER MOLDED, DO-201AD</li> <li>7. DIMENSIONS IN INCHES AND (MILLIMETERS)</li> <li>8. LEADS: SOLDERABILITY PER MIL-STD-202 METHOD 208</li> <li>9. WEIGHT: 1.1 GRAMS</li> <li>10. RoHS COMPLIANT AND HALOGEN FREE</li> </ol>
Value Inch[mm]																			
Dim.	Min.	Max.																	
A	1.000[25.40]	---																	
B	0.335[8.51]	0.375[9.52]																	
C	0.197[5.00]	0.220[5.59]																	
D	0.048[1.22]	0.052[1.32]																	

## ELECTRICAL CHARACTERISTICS

### MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED) AND ELECTRICAL CHARACTERISTICS

RATING	SYMBOL		UNITS
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT, SEE FIG.1	$I_o$	3.0	A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD	$I_{FSM}$	80	A
STORAGE TEMPERATURE RANGE	$T_{STG}$	- 55 TO +150	$^\circ\text{C}$
OPERATING TEMPERATURE RANGE	$T_{OP}$	- 55 TO +125	$^\circ\text{C}$
MAXIMUM REVERSE CURRENT AT $25^\circ\text{C}$	$I_R$	0.5	mA

PART NUMBER	MAX RECURRENT PK REVERSE VOLTAGE/DC BLOCKING $V_{RRM}/V_R$ (V)	MAX $V_{RMS}$ (V)	MAXIMUM FORWARD VOLTAGE @ $I_o$ DC $V_f$ (V)	TYPICAL JUNCTION CAPACITANCE $C_J$ (pF)
SR340	40	28	0.55	90
SR360	60	42	0.70	110
SR3100	100	70	0.85	110

- NOTE :
1. MEASURED AT 1MHz WITH APPLIED REVERSE VOLTAGE OF 4V.
  2. BOTH LEADS ATTACHED TO HEAT SINK 20x20x1T (mm) COPPER PLATE AT LEAD LENGTH 5mm.
  3. CURRENT RATING IS BASED ON SINGLE PHASE, 1/2 WAVE, 60HZ, RESISTIVE, OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%.
  4. SR3100 OPERATING TEMPERATURE CAN GO UP TO  $+150^\circ\text{C}$ .

## RATINGS AND CHARACTERISTIC CURVES

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE

