


## TIP140F/141F/142F

### Monolithic Construction With Built In Base-Emitter Shunt Resistors

- Complement to TIP145F/146F/147F
- High DC Current Gain :  $h_{FE} = 1000$  @  $V_{CE} = 4V$ ,  $I_C = 5A$  (Min.)
- Industrial Use




### NPN Epitaxial Darlington Transistor

#### Absolute Maximum Ratings $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
$V_{CBO}$	Collector-Base Voltage : TIP140F	60	V
	: TIP141F	80	V
	: TIP142F	100	V
$V_{CEO}$	Collector-Emitter Voltage : TIP140F	60	V
	: TIP141F	80	V
	: TIP142F	100	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current (DC)	10	A
$I_{CP}$	Collector Current (Pulse)	15	A
$I_B$	Base Current (DC)	0.5	A
$P_C$	Collector Dissipation ( $T_C=25^\circ\text{C}$ )	60	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature	- 65 ~ 150	$^\circ\text{C}$

Equivalent Circuit



#### Electrical Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
$V_{CEO(sus)}$	Collector-Emitter Sustaining Voltage	$I_C = 30\text{mA}$ , $I_B = 0$	60 80 100			V
	: TIP140F					V
	: TIP141F					V
	: TIP142F					V
$I_{CEO}$	Collector Cut-off Current	$V_{CE} = 30V$ , $I_B = 0$ $V_{CE} = 40V$ , $I_B = 0$ $V_{CE} = 50V$ , $I_B = 0$			2 2 2	mA mA mA
	: TIP140F					mA
	: TIP141F					mA
	: TIP142F					mA
$I_{CBO}$	Collector Cut-off Current	$V_{CB} = 60V$ , $I_E = 0$ $V_{CB} = 80V$ , $I_E = 0$ $V_{CB} = 100V$ , $I_E = 0$			1 1 1	mA mA mA
	: TIP140F					mA
	: TIP141F					mA
	: TIP142F					mA
$I_{EBO}$	Emitter Cut-off Current	$V_{BE} = 5V$ , $I_C = 0$			2	mA
$h_{FE}$	DC Current Gain	$V_{CE} = 4V$ , $I_C = 5A$	1000			
		$V_{CE} = 4V$ , $I_C = 10A$	500			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 5A$ , $I_B = 10\text{mA}$			2	V
		$I_C = 10A$ , $I_B = 40\text{mA}$			3	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = 10A$ , $I_B = 40\text{mA}$			3.5	V
$V_{BE(on)}$	Base-Emitter ON Voltage	$V_{CE} = 4V$ , $I_C = 10A$			3	V
$t_D$	Delay Time	$V_{CC} = 30V$ , $I_C = 5A$ $I_B 1 = 20\text{mA}$ , $I_B 2 = -20\text{mA}$ $R_L = 6\Omega$		0.15		$\mu\text{s}$
$t_R$	Rise Time			0.55		$\mu\text{s}$
$t_{STG}$	Storage Time			2.5		$\mu\text{s}$
$t_F$	Fall Time			2.5		$\mu\text{s}$
						$\mu\text{s}$

# Typical Characteristics




Figure 1. Static Characteristics




Figure 2. DC current Gain




Figure 3. Base-Emitter Saturation Voltage  
Collector-Emitter Saturation Voltage




Figure 4. Collector Output Capacitance




Figure 5. Safe Operating Area





Figure 6. Power Derating

# Package Dimensions

## TO-3PF

TIP140F/141F/142F



Dimensions in Millimeters

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST®	OPTOPLANAR™	STAR*POWER™
Bottomless™	FASTr™	PACMAN™	Stealth™
CoolFET™	FRFET™	POP™	SuperSOT™-3
CROSSVOLT™	GlobalOptoisolator™	Power247™	SuperSOT™-6
DenseTrench™	GTO™	PowerTrench®	SuperSOT™-8
DOMET™	HiSeC™	QFET™	SyncFET™
EcoSPARK™	ISOPLANAR™	QS™	TruTranslation™
E <sup>2</sup> CMOS™	LittleFET™	QT Optoelectronics™	TinyLogic™
EnSigna™	MicroFET™	Quiet Series™	UHC™
FACT™	MICROWIRE™	SLIENT SWITCHER®	UltraFET®
FACT Quiet Series™	OPTOLOGIC™	SMART START™	VCX™

STAR\*POWER is used under license

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

Fairchild Semiconductor

SEARCH | [Parametric](#) | [Cross Reference](#)

space

Product Folders and

Applies

find products

[Home](#) >> [Find products](#) >>

[Products groups](#)

[Analog and Mixed](#)

[Signal](#)

[Discrete](#)

[Interface](#)

[Logic](#)

[Microcontrollers](#)

[Non-Volatile](#)

[Memory](#)

[Optoelectronics](#)

[Markets and](#)

[applications](#)

[New products](#)

[Product selection and](#)

[parametric search](#)

[Cross-reference](#)

[search](#)

TIP141F  
NPN Epitaxial Darlington Transistor

[Contents](#)

[Features](#) | [Product status/pricing/packaging](#) |

[Models](#)

Features

**Monolithic Construction with Built In Base-  
Emitter Shunt Resistors**

- Complement to TIP145F/146F/147F
- High DC Current Gain:  $h_{FE}=1000$  @  $V_{CE}=4V, I_C=5A$  (Min.)
- Industrial Use

[Datasheet](#)

[Download this  
datasheet](#)

PDF

[e-mail this datasheet](#)

[E-]

This page [Print version](#)

[Related Links](#)

[Request samples](#)

[How to order products](#)

[Product Change Notices  
\(PCNs\)](#)

[Support](#)

[Distributor and field sales  
representatives](#)

[Quality and reliability](#)

[Design tools](#)

technical information

buy products

technical support

my Fairchild

company

[back to top](#)

[Product status/pricing/packaging](#)

Product	Product status	Pricing*	Package type	Leads	Packing method
TIP141FTU	Full Production	\$0.97	<a href="#">TO-3PF</a>	3	RAIL

\* 1,000 piece Budgetary Pricing

[back to top](#)

Models

Package & leads	Condition	Temperature range	Software version	Revision date
PSPICE				
TO-3PF-3	<a href="#">Electrical/Thermal</a>	-25°C to 100°C	9.2	Feb 28, 2001

[back to top](#)

[Home](#) | [Find products](#) | [Technical information](#) | [Buy products](#) |  
[Support](#) | [Company](#) | [Contact us](#) | [Site index](#) | [Privacy policy](#)

---

[© Copyright 2002 Fairchild Semiconductor](#)

---

Fairchild Semiconductor

SEARCH | Parametric | Cross Reference

space

Product Folders and

Applies

find products

Home >> Find products >>

Products groups

Analog and Mixed

Signal

Discrete

Interface

Logic

Microcontrollers

Non-Volatile

Memory

Optoelectronics

Markets and

applications

New products

Product selection and

parametric search

Cross-reference

search

TIP142F  
NPN Epitaxial Darlington Transistor

Contents

Features | [Product status/pricing/packaging](#) |

[Models](#)

Features

**Monolithic Construction with Built In Base-  
Emitter Shunt Resistors**

- Complement to TIP145F/146F/147F
- High DC Current Gain:  $h_{FE}=1000$  @  $V_{CE}=4V$ ,  $I_C=5A$  (Min.)
- Industrial Use

Datasheet

[Download this  
datasheet](#)

PDF

[e-mail this datasheet](#)

[E-]

This page [Print version](#)

Related Links

[Request samples](#)

[How to order products](#)

[Product Change Notices  
\(PCNs\)](#)

[Support](#)

[Distributor and field sales  
representatives](#)

[Quality and reliability](#)

[Design tools](#)

technical information

buy products

technical support

my Fairchild

company

[back to top](#)

Product status/pricing/packaging

Product	Product status	Pricing*	Package type	Leads	Packing method
TIP142FTU	Full Production	\$0.96	<a href="#">TO-3PF</a>	3	RAIL

\* 1,000 piece Budgetary Pricing

[back to top](#)

Models

Package & leads	Condition	Temperature range	Software version	Revision date
PSPICE				
TO-3PF-3	<a href="#">Electrical/Thermal</a>	-25°C to 100°C	9.2	Feb 28, 2001

[back to top](#)

[Home](#) | [Find products](#) | [Technical information](#) | [Buy products](#) |  
[Support](#) | [Company](#) | [Contact us](#) | [Site index](#) | [Privacy policy](#)

---

[© Copyright 2002 Fairchild Semiconductor](#)

---



Fairchild Semiconductor

SEARCH | [Parametric](#) | [Cross Reference](#)

space

Product Folders and

Applies

find products

[Home](#) >> [Find products](#) >>

[Products groups](#)

[Analog and Mixed](#)

[Signal](#)

[Discrete](#)

[Interface](#)

[Logic](#)

[Microcontrollers](#)

[Non-Volatile](#)

[Memory](#)

[Optoelectronics](#)

[Markets and](#)

[applications](#)

[New products](#)

[Product selection and](#)

[parametric search](#)

[Cross-reference](#)

[search](#)

TIP140F  
NPN Epitaxial Darlington Transistor

[Contents](#)

[Features](#) | [Product status/pricing/packaging](#) |

[Models](#)

Features

**Monolithic Construction with Built In Base-  
Emitter Shunt Resistors**

- Complement to TIP145F/146F/147F
- High DC Current Gain:  $h_{FE}=1000$  @  $V_{CE}=4V, I_C=5A$  (Min.)
- Industrial Use

[Datasheet](#)

[Download this  
datasheet](#)

PDF

[e-mail this datasheet](#)

[E-]

This page [Print version](#)

[Related Links](#)

[Request samples](#)

[How to order products](#)

[Product Change Notices  
\(PCNs\)](#)

[Support](#)

[Distributor and field sales  
representatives](#)

[Quality and reliability](#)

[Design tools](#)

technical information

buy products

technical support

my Fairchild

company

[back to top](#)

[Product status/pricing/packaging](#)

Product	Product status	Pricing*	Package type	Leads	Packing method
TIP140FTU	Full Production	\$0.97	<a href="#">TO-3PF</a>	3	RAIL

\* 1,000 piece Budgetary Pricing

[back to top](#)

Models

Package & leads	Condition	Temperature range	Software version	Revision date
PSPICE				
TO-3PF-3	<a href="#">Electrical/Thermal</a>	-25°C to 100°C	9.2	Feb 28, 2001

[back to top](#)

[Home](#) | [Find products](#) | [Technical information](#) | [Buy products](#) |  
[Support](#) | [Company](#) | [Contact us](#) | [Site index](#) | [Privacy policy](#)

---

[© Copyright 2002 Fairchild Semiconductor](#)

---