

STC

# BIPOLAR

BIPOLAR

## PNP SMALL SIGNAL TRANSISTORS

PACKAGE  
TO-18



DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N2906A**	60	600	40/120	0.4	150/15
2N2907A**	60	600	100/300	0.4	10/1.0

TO-39




DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N2904**	60	600	40/120	0.3	150/15
2N2905A**	60	600	100/300	0.3	150/15

TO-46




DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N3486A**	60	600	100/300	0.3	150/15

QUAD 14 PIN




DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N6987**	60	600	100/300	0.4	150/15

QUAD FLAT PAK



DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N6988**	60	600	100/300	0.4	150/15

DUAL



DEVICE TYPE	$V_{CE0}$ VOLTS	PEAK $I_C$ AMPS	$h_{FE}$ min/max	$V_{CE(sat)}$ VOLTS	$I_C @ I_B$ mA mA
2N5795**	60	600	40/120	0.4	150/15
2N5796**	60	600	100/300	0.4	150/15

Electrical Characteristics at 25°C unless otherwise noted.  
\*\* Available in JANTEX & TXV.