

# LED lamp

## 三角形型及び角型LED

## Triangular & Angular type LED

Ta=25°C

機種名 Type No.	ピーク発光波長 Peak-emission wavelength nm (Color)	樹脂外観 Lens appearance	絶対最大定格 Absolute maximum ratings				電気的光学的特性 Electro-optical characteristics					
			IF	VR	PD	Topr	Vf Typ.	IF	Luminous lv. Typ.	intensity IF	IR Max.	
			mA	V	mW	°C	V	mA	mod	mA	(VR=3V) μA	
三角型	SLP-139B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	0.55	5	10
	SLP-239B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	1.8	20	10
	SLP-439B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	2.0	20	10
1 X 5	SLP-532D-40	700 (R)	White diffused	25	3	70	-25~+80	1.9	5	0.3	5	10
		565 (G)		25	3	70		2.1	20	1.0	20	10
	SLP-151B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	0.45	5	10
	SLP-251B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	1.5	20	10
	SLP-451B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	2.8	20	10
1.3 X 3.9	SLP-178C	700 (R)	Colored clear	25	3	70	-25~+80	1.9	5	0.2	5	10
	SLP-278C	565 (G)	Colored clear	25	3	70	-25~+80	2.1	20	1.4	20	10
	SLP-478C	585 (Y)	Colored clear	25	3	70	-25~+80	2.1	20	1.7	20	10
□1.8	SLP-575D-40	700 (R)	White diffused	25	3	70	-25~+80	1.95	5	0.4	5	10
		565 (G)		25	3	70		2.1	20	1.0	20	10
1.8 X 3.9	SLP-174B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	0.4	5	10
	SLP-274B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	1.5	20	10
	SLP-474B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	2.8	20	10

### ■外觀図 Package dimensions

Tolerance : ±0.2  
Unit : mm

