



1-91

LED INDICATOR ASSEMBLIES							
Description	Part No.	Color	Peak Wavelength	LED Series	Iv @ 10 mA (mcd) Typ	Figure	
PCB-Mounted Right-Angle Indicators							
T-5/8, 1.7 mm Round	G170B/H	Red	697	D0580	1.0	1	
	G170B/G	Green	565		2.8		
	G170B/Y	Yellow	585		2.8		
For 5-volt Operation	G170B/H-5	Red	697	D0580/HV-5	0.8		
	G170B/G-5	Green	565		1.2		
	G170B/Y-5	Yellow	585		1.2		
Clear Epoxy Lens	G170B/EC	Orange/Red	635	C0580	6.0		
	G170B/GC	Green	565		4.0		
	G170B/YC	Yellow	585		4.0		
Four-in-row Style	G174B/4H	Red	697	D0580	1.0	2	
	G174B/4G	Green	565		2.8		
	G174B/4Y	Yellow	585		2.8		
	G174B/X+X+X+X	Any Combination of the Above					
T-1, 3 mm Round, Centered	G60B/G	Green	565	D2252	3.5	3	
	G60B/H	Red	697		1.0		
	G60B/I	Orange/Red	635		3.5		
	G60B/R	Red	655		0.8		
	G60B/Y	Yellow	585		2.5		
Offset	G61B/G	Green	565	D2351	4.5	4	
	G61B/H	Red	697		1.6		
	G61B/I	Orange/Red	635		4.5		
	G61B/R	Red	655		1.0		
	G61B/Y	Yellow	585		4.5		
Four-in-row Style	G61B/4X	Any One of the D2351 Colors Above				5	
	G61B/X+X+X+X	Any Combination of the Above					
Bi-level	G78B/2X	Any One of the D2351 Colors Above				6	
	G78B/X+X	Any Combination of the Above					
T-1-3/4, 4.7 mm Round 7 mm Long LED	G62B/A	Amber	585	D4451	5.0	7	
	G62B/E	Orange	635		5.0		
	G62B/G	Green	565		5.0		
	G62B/H	Red	697		1.6		
	G62B/I	Orange/Red	635		5.0		
	G62B/R	Red	655		0.7		
	G62B/Y	Yellow	585		5.0		
	G62B/EGW	Bi-Color	635/565		2.5/2.5		
	G62B/HGW	Bi-Color	697/565		1.0/2.5		
Two-in-row Style	G62B/2X	Any One of the D4451 Colors Above				8	
	G62B/X+X	Any Combination of the Above					
Four-in-row Style	G62B/4X	Any One of the D4451 Colors Above					
	G62B/X+X+X+X	Any Combination of the Above					
Five-in-row Style	G62B/5X	Any One of the D4451 Colors Above					
	G62B/X+X...+X	Any Combination of the Above					
T-1-3/4, 4.7 mm Round 7 mm Long LED in Bi-level	G72B/2X	Any One of the D4451 Colors Above					9
	G72B/X+X	Any Combination of the Above					