



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0
 Pantone color: 7529C

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A1253H-02P	1.25	4.25
A1253H-03P	2.50	5.50
A1253H-04P	3.75	6.75
A1253H-05P	5.00	8.00
A1253H-06P	6.25	9.25
A1253H-07P	7.50	10.50
A1253H-08P	8.75	11.75
A1253H-09P	10.00	13.00
A1253H-10P	11.25	14.25
A1253H-11P	12.50	15.50
A1253H-12P	13.75	16.75
A1253H-13P	15.00	18.00
A1253H-14P	16.25	19.25
A1253H-15P	17.50	20.50
A1253H-20P	23.75	26.75
A1253H-21P	25.00	28.00
A1253H-25P	30.00	33.00
A1253H-30P	36.25	39.25

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	1.25mm PITCH HOUSING ULTRA LOW PROFILE
		DRAWN BY 董正一 2001.02.01	APPROVED BY 董正一 2001.02.01		
B2	REVISE	2008.01.25	GENERAL TOLERANCE		
B1	REVISE	2007.01.03	X. X±0.25	ANGLE±	
B0	NEW RELEASE	2005.12.08	X. XX±0.15		
REV.	DESCRIPTION	DATE	X. XXX±0.05	DRAW NO. : A1253H-XP	
					REV. B2