

Low Power Spread Spectrum Frequency Multiplier

Features

- Produces a 1-time or 2-time spread spectrum clock signal from input frequency
- 3.3V power supply operation
- Input frequency range from 13MHz to 33.3333MHz
- Output Frequency Selection by a control pin: FSEL pin
- Frequency Spreading Ratio : -0.9% (Typical @ 33.3333MHz output frequency) and -0.7% (Typical @ 66.6666MHz output frequency)
- Modulation Rate : $F_{in}/640$
- Low power consumption design
- 6-pin SOT-23, 6-pin TDFN, 8-pin TSSOP, and 8-pin SOIC Packages

Description


The PI6C3502 is a Low Power Frequency Multiplier with Spread Spectrum function to reduce EMI interference. The PI6C3502 provides a 1 time or 2 times Spread Spectrum modulated output from a single clock source or a crystal. The PI6C3502 can reduce EMI at the clock output and it allows significant system cost savings by reducing the number of circuit board layers ferrite beads and shielding that are traditionally required to pass EMI regulations.

Frequency multiplication control is selectable through external logic state setting. The various and small package outlines can save board size and is easy for layout.


The PI6C3502 can be used in most portable devices with low power requirements like PDA, DSC, MFP, Media player, portable-TV, and LCM (LCD Panel Module).

PI6C3502 is one of Pericom clock products, if you have application need with clock input or output not specified here, please contact with Pericom for further information or custom clock design.

Block Diagram



Pin Configuration



6 Pin Description

Pin Name	Pin No.	IO TYPE	Descriptions
FSEL	1	I	Frequency select pin for 1 time and 2 times output frequency options. Please refer to the Frequency Selection Table for more details.
X2	2	O	Crystal connection. If using an external reference, this pin must be left unconnected.
X1/CLKIN	3	I	Crystal connection or reference frequency input. This pin has dual functions. It can be connected either to an external crystal or an external reference clock.
VDD	4	Power	Power Supply.
CLKOUT	5	O	Spread spectrum clock output.
GND	6	GND	Ground.

8 Pin Description

Pin Name	Pin No.	IO TYPE	Descriptions
X1/CLKIN	1	I	Crystal connection or external reference frequency input. This pin has dual functions. It can be connected either to an external crystal or an external reference clock.
X2	2	O	Crystal connection. If using an external reference, this pin must be left unconnected.
FSEL	3	I	Frequency select pin for 1 time and 2 times output frequency options. Please refer to the Frequency Selection Table for more details.
NC	4	NC	No Connection
GND	5	GND	Ground.
CLKOUT	6	O	Spread spectrum clock output.
NC	7	NC	No connection.
VDD	8	Power	Power Supply.

Frequency Selection Table

FSEL Pin	Input Frequency (MHz)	Output Frequency (MHz)
0	13-33.3333	26-66.6666
1	13-33.3333	13-33.3333

Electrical Specification

Maximum Ratings

Item	Rating
Supply Voltage to Ground	5.5V
All Inputs and Outputs	-0.5V to VDD+0.5V
Storage Temperature	-65 to +150°C
Junction Temperature	150°C
Soldering Temperature	260°C

Note:

Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended period may affect reliability.

DC Characteristics

VDD = 3.3V ±10%, Ambient Temperature 0 to +70°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V _{DD}	Operating Voltage		3.0	3.3	3.6	V
V _{IH}	Input High Voltage		2.0	–	–	V
V _{IL}	Input Low Voltage		–	–	0.8	V
V _{OH}	Output High Voltage	VDD=3.3V, I _{OH} =-8mA	2.5	–	–	V
V _{OL}	Output Low Voltage	VDD=3.3V, I _{OL} =8mA	–	–	0.4	V
I _{DD}	Supply Current	13MHz output, no load and FSEL=1	–	3.5	4.8	mA
Z _{OUT_DOWN}	Nominal output impedance	Down side buffer	–	28	–	Ω
Z _{OUT_UP}	Nominal output impedance	Up side buffer	–	29	–	Ω
C _{IN}	Input Capacitance	X1 input pin	–	5	–	pF

AC Characteristics


VDD = 3.3V ±10%, Ambient Temperature 0 to +70°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
CLKIN	Input Frequency		12	–	30	MHz
CLKOUT	Output Frequency	FSEL = 0	26	–	60	MHz
		FSEL = 1	13	–	30	
S _{Ratio_1}	Spreading ratio, FSEL=1	Output Frequency= 13MHz	–	-1.3	–	%
		Output Frequency= 33.3333MHz	–	-0.9	–	
S _{Ratio_0}	Spreading ratio, FSEL=0	Output Frequency= 26MHz	–	-1.3	–	%
		Output Frequency= 66.6666MHz	–	-0.7	–	
t _{Rise}	Output rise time	Measured from 20% to 80% VDD, 15pF load.	–	0.7	–	ns
t _{Fall}	Output fall time	Measured from 80% to 20% VDD. 15pF load.	–	1.0	–	ns
t _{J Short}	Short term jitter	Cycle to cycle jitter	–	155	220	ps
T _{DCIN}	Input duty cycle		30	50	80	%
T _{DCOUT}	Output duty cycle		45	50	55	%

Application Information

Crystal Load Capacitors

If a crystal is used with the device, the external trim capacitors C_{Ltrim} are used to adjust the effective capacitance to match the required crystal load capacitance. The C_{Ltrim} value can be derived from formula $C_{Ltrim} = 2 * CL - (CS + Ci)$. Typical C_{Ltrim} = 28 pF when crystal load = 18pF, stray capacitance C_s = 3pF and XTAL pins capacitance = 5pF.






Physical Dimensions

Packaging Mechanical: 6-Pin, SOT-23

DOCUMENT CONTROL NO.
 PD - 1912

REVISION: C
 DATE: 03/09/05



X.XX DENOTES DIMENSIONS
 X.XX IN MILLIMETERS

Notes:

- 1) Controlling dimensions in millimeters
- 2) Ref: EIAJ SC-74A
- 3) Foot length is measured at flat portion of foot, reference to Datum "A"



Pericom Semiconductor Corporation
 3545 N. 1st Street, San Jose, CA 95134
 1-800-435-2335 • www.pericom.com

DESCRIPTION: 6-Pin Small Outline Transistor
Plastic Package, SOT-23


PACKAGE CODE: T

Physical Dimensions

Packaging Mechanical: 6-Pin, TDFN

DOCUMENT CONTROL NO.
 PD - 2020

REVISION: A
 DATE: 03/09/05



Notes:

- 1) All dimensions are in millimeters
- 2) Coplanarity shall not exceed 0.08mm.
- 3) Warpage shall not exceed 0.10mm.
- 4) JEDEC MO-229C (Ref)



Pericom Semiconductor Corporation
 3545 N. 1st Street, San Jose, CA 95134
 1-800-435-2335 • www.pericom.com

DESCRIPTION: 6-Contact, Thin Dual-in-line Flat No Lead Package, TDFN



PACKAGE CODE: ZC

Physical Dimensions

Packaging Mechanical: 8-Pin, SOIC

DOCUMENT CONTROL NO.
 PD - 1001

REVISION: F
 DATE: 03/09/05



X.XX DENOTES DIMENSIONS
 X.XX IN MILLIMETERS

- Notes:
 1) Controlling dimensions in millimeters.
 2) Ref: JEDEC MS-012D/AA




Pericom Semiconductor Corporation
 3545 N. 1st Street, San Jose, CA 95134
 1-800-435-2335 • www.pericom.com

DESCRIPTION: 8-Pin, 150-Mil Wide, SOIC

PACKAGE CODE: W

Physical Dimensions

Packaging Mechanical: 8-Pin, TSSOP



Ordering Information

Ordering Code	Packaging Code	Package Description
PI6C3502TE	T	Pb-Free & Green, 6-Pin SOT-23
PI6C3502ZCE	ZC	Pb-Free & Green, 6-Pin TDFN
PI6C3502WE	W	Pb-free & Green, 8-Pin SOIC
PI6C3502LE	L	Pb-free & Green, 8-Pin TSSOP

Notes:

1. Thermal characteristics and package top marking can be found at www.pericom.com/packaging.
2. E=Pb-free and Green package
3. Adding an X suffix = Tape/Reel