


## Wirewound, Surface Mount Molded Inductors



STANDARD ELECTRICAL SPECIFICATIONS					
IND. (μH)	TEST FREQ. (MHz)	Q MIN.	SRF MIN. <sup>(1)</sup> (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)
	L & Q				
0.010	100	15	2500	0.13	734
0.012	100	17	2300	0.14	707
0.015	100	19	2100	0.16	661
0.018	100	21	1900	0.18	624
0.022	100	23	1700	0.20	592
0.027	100	23	1500	0.22	564
0.033	100	25	1400	0.24	540
0.039	100	25	1300	0.27	530
0.047	100	26	1200	0.30	483
0.056	100	26	1100	0.33	470
0.068	100	27	1000	0.36	450
0.082	100	27	900	0.40	450
0.10	100	28	700	0.44	450

**Note**

<sup>(1)</sup> All SRF values above 1000 MHz are typical minimums.

**PART MARKING**

- Vishay Dale
- Inductance value
- Date code

**FEATURES**

- Printed marking
- Molded construction provides superior strength and moisture resistance
- Compatible with vapor phase and infrared reflow soldering
- Tape and reel packaging for automatic handling, 2000/reel, EIA-481
- Compliant to RoHS directive 2002/95/EC


**RoHS**  
COMPLIANT

**ELECTRICAL SPECIFICATIONS**


**Inductance and Tolerance:** ± 20 % for 0.010 μH to 0.100 μH standard.  
 ± 10 % for 0.010 μH to 0.100 μH  
 ± 5 % for 0.027 μH to 0.100 μH optional.

**Operating Temperature:** - 55 °C to + 125 °C

**Core Material:** Non-magnetic from 0.010 μH to 0.100 μH

**TEST EQUIPMENT**

- L, Q, SRF: HP4191A RF impedance analyzer
- DCR: Wheatstone bridge or equivalent

**DIMENSIONS** in inches [millimeters]

**DESCRIPTION**

IMC-1210-100	0.010 μH	± 20 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

**GLOBAL PART NUMBER**

I	M	C	1	2	1	0	E	R	1	0	N	K	1	0	0
PRODUCT FAMILY			SIZE				PACKAGE CODE		INDUCTANCE VALUE			TOL.	SERIES		



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**