

2SD2153

Transistor, NPN

Features


- available in MPT3 (MPT, SOT-89, SC-62) package
- package marking: 2SD2153; DN★, where ★ is h_{FE} code
- excellent current-to-gain characteristics
- low collector saturation voltage, typically $V_{CE(sat)} = 0.5 \text{ V (max)}$ for $I_C/I_B = 1 \text{ A/20 mA}$

Applications

- power amplifier

Dimensions (Units : mm)

2SD2153 (MPT3)



Absolute maximum ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Limits	Unit	Conditions
Collector-to-base voltage	V_{CBO}	30	V	
Collector-to-emitter voltage	V_{CEO}	25	V	
Emitter-to-base voltage	V_{EBO}	6	V	
Collector current	I_C	2	A	DC
		3		Single pulse, $P_W = 10 \text{ ms}$
Collector dissipation	P_C	0.5	W	Mounted on $40 \times 40 \times 0.7 \text{ mm}$ ceramic substrate
		2.0		
Junction temperature	T_j	150	$^\circ\text{C}$	
Storage temperature	T_{stg}	$-55 \sim +150$	$^\circ\text{C}$	

2SD2153 Transistor, NPN, 2SD series

Electrical characteristics (unless otherwise noted, $T_a = 25^\circ\text{C}$)

Parameter	Symbol	Min	Typical	Max	Unit	Conditions
Collector-to-base breakdown voltage	BV_{CBO}	30			V	$I_C = 50 \mu\text{A}$
Collector-to-emitter breakdown voltage	BV_{CEO}	25			V	$I_C = 1 \text{ mA}$
Emitter-to-base breakdown voltage	BV_{EBO}	6			V	$I_E = 50 \mu\text{A}$
Collector cutoff current	I_{CBO}			0.5	μA	$V_{CB} = 20 \text{ V}$
Emitter cutoff current	I_{EBO}			0.5	μA	$V_{EB} = 5 \text{ V}$
DC current gain	h_{FE}	390		2700		$V_{CE} = 6 \text{ V}$, $I_C = 0.5 \text{ A}$, single pulse
Collector-to-emitter saturation voltage	$V_{CE(sat)}$			0.5	V	$I_C/I_B = 1 \text{ A}/20 \text{ mA}$, single pulse
Transition frequency	f_T		110		MHz	$V_{CE} = 10 \text{ V}$, $I_E = -10 \text{ mA}$, $f = 100 \text{ MHz}$, single pulse
Output capacitance	C_{ob}		22		pF	$V_{CB} = 10 \text{ V}$, $I_E = 0 \text{ A}$, $f = 1 \text{ MHz}$

h_{FE} rankings

Item	E	U	V	W
h_{FE}	390 ~ 820	560 ~ 1200	820 ~ 1800	1200 ~ 2700

Electrical characteristic curves




Figure 1




Figure 2




Figure 3




Figure 4

Ordering information

Package	Tape
Code	T100
Basic order quantity	1000
2SD2153	☆
★ = Standard, ☆ = Semi-standard, * = Special order	