

BZW04-5V8 BZW04-376

400WATT AXIAL LEAD TRANSIENT VOLTAGE SUPPRESSORS

DO-41

DEVICE TYPE	BREAKDOWN VOLTAGE			WORKING PEAK REV. VOLTAGE (VRWM) VOLTS	MAX. REV. LEAKAGE at VRWM IR (A)	MAX. REV. (CURRENT (IRSM) NOTE 2 AMPS	MAX. REV. VOLTAGE at IRSM (VRSM) VOLT	MAX TEMP COEFF OF VBR (%/°C)
	V (BR) VOLTS		@ IT mA					
	MIN	MAX						
BZW04-5V8	6.45	7.14	10	5.8	1000	38	10.5	.057
BZW04-6V4	6.13	7.88	10	6.4	500	35.4	11.3	.061
BZW04-7V0	7.79	8.61	10	7.02	200	33	12.1	.065
BZW04-7V8	8.65	9.55	1	7.78	50	30	13.4	.068
BZW04-8V5	9.50	10.5	1	8.55	10	27.6	14.5	.073
BZW04-9V4	10.5	11.6	1	9.4	5	25.7	15.6	.075
BZW04-10	11.4	12.6	1	10.2	5	24	16.7	.078
BZW04-11	12.4	13.7	1	11.1	5	22	18.2	.081
BZW04-13	14.3	15.8	1	12.8	5	19	21.2	.084
BZW04-14	15.2	16.8	1	13.6	5	17.8	22.5	.086
BZW04-15	17.1	18.9	1	15.3	5	16	25.2	.088
BZW04-17	19	21	1	17.1	5	14.5	27.7	.090
BZW04-19	20.9	23.1	1	18.8	5	13	30.6	.092
BZW04-20	22.8	25.2	1	20.5	5	12	33.2	.094
BZW04-23	25.7	28.4	1	23.1	5	10.7	37.5	.096
BZW04-26	28.5	31.5	1	25.6	5	9.6	41.6	.097
BZW04-28	31.4	34.7	1	28.2	5	8.8	45.7	.098
BZW04-31	34.2	37.8	1	30.8	5	8	49.9	.099
BZW04-33	37.1	41	1	33.3	5	7.4	53.9	.100
BZW04-37	40.9	45.2	1	36.8	5	6.7	59.3	.101
BZW04-40	44.7	49.4	1	40.2	5	6.2	64.8	.101
BZW04-44	48.5	53.6	1	46.6	5	5.7	70.1	.102
BZW04-48	53.2	58.8	1	47.8	5	5.2	77	.103
BZW04-53	58.9	68.2	1	53	5	4.7	85	.104
BZW04-58	64.8	71.4	1	58.1	5	4.3	92	.104
BZW04-64	71.3	78.8	1	64.1	5	3.9	103	.105
BZW04-70	77.9	86.1	1	70.1	5	3.5	113	.105
BZW04-78	86.5	95.5	1	77.8	5	3.2	125	.106
BZW04-85	95	105	1	85.5	5	2.9	137	.106
BZW04-94	105	116	1	94	5	2.6	152	.107
BZW04-102	114	125	1	102	5	2.4	165	.107
BZW04-111	124	137	1	111	5	2.2	179	.107
BZW04-128	143	158	1	128	5	2.0	207	.108
BZW04-136	152	168	1	136	5	1.8	218	.108
BZW04-145	161	179	1	145	5	1.7	234	.108
BZW04-154	171	189	1	154	5	1.6	246	.108
BZW04-171	190	210	1	171	5	1.5	274	.108
BZW04-188	209	231	1	188	5	1.4	301	.108
BZW04-213	237	263	1	213	5	1.5	344	.110
BZW04-239	266	294	1	239	5	1.5	384	.110
BZW04-256	285	315	1	256	5	1.2	414	.110
BZW04-273	304	336	1	273	5	1.2	438	.110
BZW04-299	332	368	1	299	5	0.9	482	.110
BZW04-342	380	420	1	342	5	0.9	548	.110
BZW04-376	418	462	1	376	5	0.8	603	.110