



SRAM

8K x 8 SRAM

FEATURES

- High speed: 12, 15, 20, 25, 30 and 35ns
- High-performance, low-power, CMOS double metal process
- Single +5V (±10%) power supply
- Easy memory expansion with $\overline{CE1}$, $\overline{CE2}$ and \overline{OE} options
- All inputs and outputs are TTL compatible

OPTIONS

- Timing
 - 12ns access
 - 15ns access
 - 20ns access
 - 25ns access
 - 30ns access
 - 35ns access


MARKING

- Packages

Plastic DIP (300 mil)	None
Ceramic DIP (300 mil)	C
Plastic SOJ (300 mil)	DJ
Ceramic LCC (28 pin)	EC
Ceramic LCC (32 pin)	ECW
- Two Volt Data Retention

	L
--	---

PIN ASSIGNMENT (Top View)




MICRON

MT5C6408

T-46-23-12

FUNCTIONAL BLOCK DIAGRAM

FAST SRAM



TRUTH TABLE

MODE	CE1	CE2	WE	OE	DQ OPERATION	POWER
STANDBY	H	X	X	X	HIGH-Z	STANDBY
STANDBY	X	L	X	X	HIGH-Z	STANDBY
READ	L	H	H	L	Q	ACTIVE
READ	L	H	H	H	HIGH-Z	ACTIVE
WRITE	L	H	L	X	D	ACTIVE



MT5C6408

T-46-23-12

ABSOLUTE MAXIMUM RATINGS*

Voltage on Vcc supply relative to Vss -1.0V to +7.0V
 Storage Temperature (Ceramic) -65°C to +150°C
 Storage Temperature (Plastic) -55°C to +150°C
 Power Dissipation 1W
 Short Circuit Output Current 50mA

*Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

ELECTRICAL CHARACTERISTICS AND RECOMMENDED DC OPERATING CONDITIONS

(0°C ≤ T_A ≤ 70°C; Vcc = 5.0V ± 10%)

DESCRIPTION	CONDITIONS	SYMBOL	MIN	MAX	UNITS	NOTES
Input High (Logic 1) Voltage		V _{IH}	2.2	Vcc +1	V	1
Input Low (Logic 0) Voltage		V _{IL}	-0.5	0.8	V	1, 2
Input Leakage Current	0V ≤ V _{IN} ≤ Vcc	I _{LI}	-5	5	μA	
Output Leakage Current	Output(s) Disabled, 0V ≤ V _{OUT} ≤ Vcc	I _{LO}	-5	5	μA	
Output High Voltage	I _{OH} = -4.0mA	V _{OH}	2.4		V	1
Output Low Voltage	I _{OL} = 8.0mA	V _{OL}		0.4	V	1

FAST SRAM

DESCRIPTION	CONDITIONS	SYMBOL	MAX						UNITS	NOTES
			-12	-15	-20	-25	-30	-35		
Power Supply Current: Operating	CE ≤ V _{IL} ; Vcc = MAX f = MAX = 1/τRC, Outputs Open	I _{CC}	140	130	120	110	100	100	mA	3
Power Supply Current: Standby	CE ≥ V _{IH} ; Vcc = MAX f = MAX = 1/τRC, Outputs Open	I _{SB1}	60	50	40	30	30	30	mA	
	CE ≥ Vcc - 0.2V; Vcc = MAX V _{IL} ≤ Vss + 0.2V; V _{IH} ≥ Vcc - 0.2V; f = 0	I _{SB2}	5	5	5	5	5	5	mA	

CAPACITANCE

DESCRIPTION	CONDITIONS	SYMBOL	MIN	MAX	UNITS	NOTES
Input Capacitance	T _A = 25°C; f = 1MHz Vcc = 5V	C _I		7	pF	4
Output Capacitance		C _O		7	pF	4



T-46-23-12

ELECTRICAL CHARACTERISTICS AND RECOMMENDED AC OPERATING CONDITIONS

(Note 5, 13) ($0^{\circ}\text{C} \leq T_A \leq 70^{\circ}\text{C}$; $V_{CC} = 5V \pm 10\%$)

FAST SRAM

DESCRIPTION	SYM	-12		-15		-20		-25		-30		-35		UNITS	NOTES
		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX		
READ Cycle															
READ cycle time	t_{RC}	12		15		20		25		30		35		ns	
Address access time	t_{AA}		12		15		20		25		30		35	ns	
Chip Enable access time	t_{ACE}		12		12		15		20		25		30	ns	
Output hold from address change	t_{OH}	3		3		3		3		3		3		ns	
Chip Enable to output in Low-Z	t_{LZCE}	3		3		5		5		5		5		ns	
Chip Disable to output in High-Z	t_{HZCE}		7		7		10		10		15		20	ns	6, 7
Chip Enable to power-up time	t_{PU}	0		0		0		0		0		0		ns	
Chip Disable to power-down time	t_{PD}		12		15		20		25		30		35	ns	
Output Enable access time	t_{AOE}		7		7		9		10		15		20	ns	
Output Enable to output in Low-Z	t_{LZOE}	0		0		0		0		0		0		ns	
Output Disable to output in High-Z	t_{HZOE}		6		6		10		10		15		20	ns	6
WRITE Cycle															
WRITE cycle time	t_{WC}	12		15		20		25		30		35		ns	
Chip Enable to end of write	t_{CW}	10		12		15		20		25		25		ns	
Address valid to end of write	t_{AW}	12		12		15		20		25		25		ns	
Address setup time	t_{AS}	0		0		0		0		0		0		ns	
Address hold from end of write	t_{AH}	0		0		0		0		0		0		ns	
Write pulse width	t_{WP}	10		12		15		20		25		25		ns	
Data setup time	t_{DS}	8		8		10		10		15		15		ns	
Data hold time	t_{DH}	0		0		0		0		0		0		ns	
Write Disable to output in Low-Z	t_{LZWE}	2		2		2		2		2		2		ns	
Write Enable to output in High-Z	t_{HZWE}		6		6		8		10		12		15	ns	6

MICRON **MT5C6408**

T-46-23-12

AC TEST CONDITIONS

Input pulse levels	V _{ss} to 3.0V
Input rise and fall times	5ns
Input timing reference levels	1.5V
Output reference levels	1.5V
Output load	See Figures 1 and 2




Fig. 1 OUTPUT LOAD EQUIVALENT




Fig. 2 OUTPUT LOAD EQUIVALENT

NOTES


- All voltages referenced to V_{ss} (GND).
- 3.0V for pulse width < 20ns.
- I_{cc} is dependent on output loading and cycle rates.
- This parameter is sampled.
- Test conditions as specified with the output loading as shown in Fig. 1 unless otherwise noted.
- t_{HZCE}, t_{HZWE} and t_{HZOE} are specified with CL = 5pF as in Fig. 2. Transition is measured ± 500mV from steady state voltage.
- At any given temperature and voltage condition, t_{HZCE} is less than t_{LZCE}.
- \overline{WE} is HIGH for READ cycle.
- Device is continuously selected. All chip enables held in their active state.
- Address valid prior to or coincident with latest occurring chip enable.
- t_{RC} = Read Cycle Time.
- Chip enable (\overline{CE}) and write enable (\overline{WE}) can initiate and terminate a WRITE cycle.
- For automotive, industrial and extended temperature specifications refer to page 4-167.

FAST SRAM

DATA RETENTION ELECTRICAL CHARACTERISTICS (L Version Only)

DESCRIPTION	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNITS	NOTES
V _{cc} for Retention Data		V _{DR}	2		—	V	
Data Retention Current	$\overline{CE} \geq (V_{cc} - 0.2V)$ $V_{IN} \geq (V_{cc} - 0.2V)$ or $\leq 0.2V$	I _{ccDR}		95	250	μA	
			V _{cc} = 3v		300	400	μA
Chip Deselect to Data Retention Time		t _{CDR}	0		—	ns	4
Operation Recovery Time		t _R	t _{RC}			ns	4, 11

LOW V_{cc} DATA RETENTION WAVEFORM




MICRON


MT5C6408

T-46-23-12

READ CYCLE NO. 1 8, 9



READ CYCLE NO. 2 7, 8, 10



 DON'T CARE
 UNDEFINED


FAST SRAM




MT5C6408

T-46-23-12

WRITE CYCLE NO. 1
(Write Enable Controlled) 7, 12



WRITE CYCLE NO. 2
(Chip Enable Controlled) 12



▨ DON'T CARE
▩ UNDEFINED

FAST SRAM