



# PPC PRODUCTS CORPORATION SEMICONDUCTOR SPECIALIST

NPN DEVICE	CASE	BREAKDOWN VOLTAGES			h <sub>FE</sub>				SAT. VOLTAGES (Max.)			
		V <sub>CB</sub>	V <sub>CE</sub>	V <sub>EB</sub>	V <sub>CE</sub> (V)	I <sub>C</sub> (A)	Min.	Max.	I <sub>C</sub> (A)	I <sub>B</sub> (A)	V <sub>CE</sub> (V)	V <sub>BE</sub> (V)
2N3598	TO-63	80	60	8	2	10	40	120	10	1	0.5	2
2N3599	TO-63	100	80	8	2	10	40	120	10	1	0.5	2
2N3619	TO-5	75	40	4	5	1	40		1	0.1	0.75	1
2N3620	TO-5(s)	75	40	4	5	10	3		10	0.3	1	2
2N3621	TO-61	75	40	4	5	10	40		10	0.5	0.75	2
2N3622	TO-61	75	40	4	5	10	40		10	0.5	0.75	2
2N3623	TO-5	75	40	4	5	1	40		1	0.1	0.75	1
2N3627	TO-5	100	50	4	5	1	40		1	0.1	0.75	1
2N3628	TO-5	75	40	4	10	5	30		5	0.5	1.5	2
2N3629	TO-61	75	40	4	10	5	40		5	0.5	1.5	2
2N3630	TO-61	75	40	4	10	5	40		5	0.5	1.5	2
2N3675	TO-5	90	55	7	1	1	12	60	1	0.1	0.8	2
2N3676	TO-5	90	90	7	1	1	12	60	1	0.1	0.8	2
2N3738	TO-66	250	225	6	10	0.1	40	200	0.1	0.025	2.5	1
2N3739	TO-66	325	300	6	10	0.1	40	200	0.1	0.025	2.5	1
2N3744	TO-111/I	60	40	7	5	1	20	60	1	0.1	0.25	1
2N3745	TO-111/I	80	60	8	5	1	20	60	1	0.1	0.25	1
2N3746	TO-111/I	100	80	8	5	1	20	60	1	0.1	0.25	1
2N3747	TO-111/I	60	40	7	5	1	40	120	1	0.1	0.25	1
2N3748	TO-111/I	80	60	8	5	1	40	120	1	0.1	0.25	1
2N3749	TO-111/I	100	80	8	5	1	40	120	1	0.1	0.25	1
2N3750	TO-111/I	60	40	7	5	1	100	300	1	0.1	0.25	1
2N3751	TO-111/I	80	60	8	5	1	100	300	1	0.1	0.25	1
2N3752	TO-111/I	100	80	8	5	1	100	300	1	0.1	0.25	1
2N3766	TO-66	80	60	6	10	0.5	40	160	0.5	0.1	2.5	2
2N3767	TO-66	100	80	6	10	0.5	40	160	0.5	0.1	2.5	2
2N3788	TO-3	400	325	5	5	0.5	20	80	0.5	0.3	1	1
2N3846	TO-63	300	200	10	3	10	10	60	10	1.6	0.75	1
2N3847	TO-63	400	300	10	3	10	10	60	10	1.6	0.75	1
2N3848	TO-63	300	200	10	4	15	40	200	15	2	1	1
2N3849	TO-63	400	300	10	4	15	40	200	15	2	1	1
2N3850	TO-59	100	80	5	1	1	50	150	1	0.2	0.5	1

■ 6856191 0001034 069 ■