

SCHOTTKY RECTIFIER DIODES, MODULE, DUAL

ISI Part Number	Maximum Average Rectified Current @ T _v		Peak Inverse Voltage	Peak Forward Surge Current @ 5.2ms Superimposed	Maximum Fwd Voltage @ Rated I _f & T _v =25°C	Maximum Reverse Current @ T _v =25°C		Typical Junction Capacitance at 1.0 MHz		Outline																																																																																	
	I _r (A)	T _v (°C)				I _{rrm} (Amps)	V _{rrm} (Volts)	I _r (mA)	V _r (V)		C (pF)	V _c (V)																																																																															
										Inches/millimeters																																																																																	
CPT12035 CPT12040 CPT12045 CPT12050	120	140	35	1000	.80	3.0	35	2700	5.0																																																																																		
140		40	40				40																																																																																				
140		45	45				45																																																																																				
140		50	50				50																																																																																				
CPT20035 CPT20040 CPT20045 CPT20050	200	140	35	2000	.80	4.0	35	4600	5.0																																																																																		
140		40	40				40																																																																																				
140		45	45				45																																																																																				
140		50	50				50																																																																																				
CPT30035 CPT30040 CPT30045 CPT30050 CPT30060 CPT30080 CPT30090	300	136	35	2000	.76	4.0	35	4600	5.0			<table border="1"> <thead> <tr> <th colspan="5">DIMENSIONS</th> </tr> <tr> <th rowspan="2"></th> <th colspan="2">Inches</th> <th colspan="2">Millimeters</th> <th rowspan="2">Notes</th> </tr> <tr> <th>Min</th> <th>Max</th> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>0.700</td> <td>3.630</td> <td>17.78</td> <td>92.2</td> <td rowspan="7"></td> </tr> <tr> <td>B</td> <td>0.700</td> <td>0.800</td> <td>17.78</td> <td>20.32</td> </tr> <tr> <td>C</td> <td>0.120</td> <td>0.625</td> <td>3.05</td> <td>15.87</td> </tr> <tr> <td>E</td> <td>0.120</td> <td>0.130</td> <td>3.05</td> <td>3.30</td> </tr> <tr> <td>F</td> <td>0.490</td> <td>0.510</td> <td>12.45</td> <td>12.95</td> </tr> <tr> <td>G</td> <td>0.010</td> <td></td> <td>0.25</td> <td></td> </tr> <tr> <td>H</td> <td>0.275</td> <td>0.290</td> <td>6.99</td> <td>7.37</td> <td>Dia</td> </tr> <tr> <td>N</td> <td>0.600</td> <td></td> <td>15.24</td> <td></td> <td rowspan="4">Dia</td> </tr> <tr> <td>Q</td> <td>0.312</td> <td>0.340</td> <td>7.92</td> <td>8.64</td> </tr> <tr> <td>R</td> <td>0.180</td> <td>0.195</td> <td>4.57</td> <td>4.95</td> </tr> <tr> <td>W</td> <td>1.375 BSC</td> <td></td> <td>34.92 BSC</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>80.01 BSC</td> <td></td> <td>1/4-28</td> </tr> </tbody> </table>	DIMENSIONS						Inches		Millimeters		Notes	Min	Max	Min	Max	A	0.700	3.630	17.78	92.2		B	0.700	0.800	17.78	20.32	C	0.120	0.625	3.05	15.87	E	0.120	0.130	3.05	3.30	F	0.490	0.510	12.45	12.95	G	0.010		0.25		H	0.275	0.290	6.99	7.37	Dia	N	0.600		15.24		Dia	Q	0.312	0.340	7.92	8.64	R	0.180	0.195	4.57	4.95	W	1.375 BSC		34.92 BSC					80.01 BSC		1/4-28
DIMENSIONS																																																																																											
		Inches			Millimeters		Notes																																																																																				
		Min	Max		Min					Max																																																																																	
A		0.700	3.630		17.78		92.2																																																																																				
B		0.700	0.800		17.78		20.32																																																																																				
C		0.120	0.625		3.05		15.87																																																																																				
E	0.120	0.130	3.05	3.30																																																																																							
F	0.490	0.510	12.45	12.95																																																																																							
G	0.010		0.25																																																																																								
H	0.275	0.290	6.99	7.37	Dia																																																																																						
N	0.600		15.24		Dia																																																																																						
Q	0.312	0.340	7.92	8.64																																																																																							
R	0.180	0.195	4.57	4.95																																																																																							
W	1.375 BSC		34.92 BSC																																																																																								
			80.01 BSC		1/4-28																																																																																						
136	40	.76	40																																																																																								
136	45	.76	45																																																																																								
136	50	.76	50																																																																																								
127	60	.82	60																																																																																								
112	80	.86	80																																																																																								
112	90	.86	90																																																																																								
CPT40035 CPT40040 CPT40045 CPT40050 CPT40060 CPT40080 CPT40090	400	127	35	3000	.78	5.0	35	7200	5.0																																																																																		
127		40	.78		40																																																																																						
127		45	.78		45																																																																																						
127		50	.78		50																																																																																						
125		60	.80		60																																																																																						
108		80	.91		80																																																																																						
108		90	.91		90																																																																																						
CPT50035 CPT50040 CPT50045 CPT50050 CPT50060 CPT50080 CPT50090	500	134	35	5000	.70	8.0	35	9800	5.0		<p>MODULES</p>																																																																																
134		40	.70		40																																																																																						
134		45	.70		45																																																																																						
134		50	.70		50																																																																																						
125		60	.73		60																																																																																						
120		80	.85		80																																																																																						
120		90	.85		90																																																																																						