


✓ 54/7422 611049
 ✓ 54H/74H22 011051
 ✓ 54S/74S22 011052
 ✓ 54LS/74LS22 611050
DUAL 4-INPUT NAND GATE
 (With Open-Collector Output)


CONNECTION DIAGRAMS
PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		V _{CC} = +5.0 V ±5%, T _A = 0°C to +70°C	V _{CC} = +5.0 V ±10%, T _A = -55°C to +125°C	
Plastic DIP (P)	A	7422PC, 74H22PC 74S22PC, 74LS22PC		9A
Ceramic DIP (D)	A	7422DC, 74H22DC 74S22DC, 74LS22DC	5422DM, 54H22DM 54S22DM, 54LS22DM	6A
Flatpak (F)	A	7422FC, 74S22FC 74LS22FC	5422FM, 54S22FM 54LS22FM	3I
	B	74H22FC	54H22FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	OC**/10	OC**/12.5	OC**/12.5	OC**/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74H		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max	Min	Max			
I _{CC} H	Power Supply	4.0	5.0	6.6	0.8	mA	V _{IN} = Gnd V _{CC} = Max					
I _{CC} L	Current	11	20	18	2.2							
t _{PLH}	Propagation Delay	45	15	2.0	7.5	ns	Figs. 3-2, 3-4					
t _{PHL}		15	12	2.0	7.0				18			

*DC limits apply over operating temperature range; AC limits apply at T_A = +25°C and V_{CC} = +5.0 V.
 **OC — Open Collector