

HSM83

Silicon Epitaxial Planar Diode for High Voltage Switching


Features

- High reverse voltage. ($V_R=250V$)
- MPAK package is suitable for high density surface mounting and high speed assembly.

Ordering Information

Type No.	Laser Mark	Package Code
HSM83	F 7	MPAK

Pin Arrangement




Absolute Maximum Ratings ($T_a = 25^\circ C$)

Item	Symbol	Value	Unit
Peak reverse voltage	V_{RM}	300	V
Reverse voltage	V_R	250	V
Peak forward current	I_{FM}	300	mA
Non-Repetitive peak forward surge current	I_{FSM}^*	2	A
Average forward current	I_o	100	mA
Junction temperature	T_j	125	°C
Storage temperature	T_{stg}	-55 to +125	°C


* Within 10ms forward surge current.

Electrical Characteristics ($T_a = 25^\circ C$)


Item	Symbol	Min	Typ	Max	Unit	Test Condition
Forward voltage	V_F	—	—	1.2	V	$I_F = 100 \text{ mA}$
Reverse current	I_{R1}	—	—	0.2	μA	$V_R = 250 \text{ V}$
	I_{R2}	—	—	100		$V_R = 300 \text{ V}$
Capacitance	C	—	1.5	3.0	pF	$V_R = 0 \text{ V}, f = 1 \text{ MHz}$
Reverse recovery time	trr	—	—	100	ns	$I_F=I_R=30\text{mA}, I_{rr}=3\text{mA}, R_L=100\Omega$



**Fig.1 Forward current Vs.
Forward voltage**



**Fig.2 Reverse current Vs.
Reverse voltage**



**Fig.3 Capacitance Vs.
Reverse voltage**