



Female connectors, straight

Identification Number of contacts Part No. Dimensions in mm

Female connector, straight, stacking heights 6.25 / 9.05 mm

6	15 2 . 006 . 601
8	15 2 . 008 . 601
10	15 2 . 010 . 601
12	15 2 . 012 . 601
14	15 2 . 014 . 601
16	15 2 . 016 . 601
18	15 2 . 018 . 601
20	15 2 . 020 . 601
22	15 2 . 022 . 601
24	15 2 . 024 . 601
26	15 2 . 026 . 601
28	15 2 . 028 . 601
30	15 2 . 030 . 601
32	15 2 . 032 . 601
34	15 2 . 034 . 601
36	15 2 . 036 . 601
38	15 2 . 038 . 601
40	15 2 . 040 . 601
42	15 2 . 042 . 601
44	15 2 . 044 . 601
46	15 2 . 046 . 601
48	15 2 . 048 . 601
50	15 2 . 050 . 601
52	15 2 . 052 . 601
54	15 2 . 054 . 601
56	15 2 . 056 . 601
58	15 2 . 058 . 601
60	15 2 . 060 . 601
62	15 2 . 062 . 601
64	15 2 . 064 . 601
66	15 2 . 066 . 601
68	15 2 . 068 . 601
70	15 2 . 070 . 601
72	15 2 . 072 . 601
74	15 2 . 074 . 601
76	15 2 . 076 . 601
78	15 2 . 078 . 601
80	15 2 . 080 . 601
82	15 2 . 082 . 601
84	15 2 . 084 . 601
86	15 2 . 086 . 601
88	15 2 . 088 . 601
90	15 2 . 090 . 601
92	15 2 . 092 . 601
94	15 2 . 094 . 601
96	15 2 . 096 . 601
98	15 2 . 098 . 601
100	15 2 . 100 . 601

A	B	C	D	E	G
2.54	6.96	8.89	5.56	4.56	1.19
3.81	8.23	10.16	6.83	5.83	1.19
5.08	9.50	11.43	8.10	7.10	2.46
6.35	10.77	12.70	9.37	8.37	2.46
7.62	12.04	13.97	10.64	9.64	3.73
8.89	13.31	15.24	11.91	10.91	3.73
10.16	14.58	16.51	13.18	12.18	5.00
11.43	15.85	17.78	14.45	13.45	5.00
12.70	17.12	19.05	15.72	14.72	6.27
13.97	18.39	20.32	16.99	15.99	6.27
15.24	19.66	21.59	18.26	17.26	7.54
16.51	20.93	22.86	19.53	18.53	7.54
17.78	22.20	24.13	20.80	19.80	8.81
19.05	23.47	25.40	22.07	21.07	8.81
20.32	24.74	26.67	23.34	22.34	10.08
21.59	26.01	27.94	24.61	23.61	10.08
22.86	27.28	29.21	25.88	24.88	11.35
24.13	28.55	30.48	27.15	26.15	11.35
25.40	29.82	31.75	28.42	27.42	12.62
26.67	31.09	33.02	29.69	28.69	12.62
27.94	32.36	34.29	30.96	29.96	13.89
29.21	33.63	35.56	32.23	31.23	13.89
30.48	34.90	36.83	33.50	32.50	15.16
31.75	36.17	38.10	34.77	33.77	15.16
33.02	37.44	39.37	36.04	35.04	16.43
34.29	38.71	40.64	37.31	36.31	16.43
35.56	39.98	41.91	38.58	37.58	17.70
36.83	41.25	43.18	39.85	38.85	17.70
38.10	42.52	44.45	41.12	40.12	18.97
39.37	43.79	45.72	42.39	41.39	18.97
40.64	45.06	46.99	43.66	42.66	20.24
41.91	46.33	48.26	44.93	43.93	20.24
43.18	47.60	49.53	46.20	45.20	21.51
44.45	48.87	50.80	47.47	46.47	21.51
45.72	50.14	52.07	48.74	47.74	22.78
46.99	51.41	53.34	50.01	49.01	22.78
48.26	52.68	54.61	51.28	50.28	24.05
49.53	53.95	55.88	52.55	51.55	24.05
50.80	55.22	57.15	53.82	52.82	25.32
52.07	56.49	58.42	55.09	54.09	25.32
53.34	57.76	59.69	56.36	55.36	26.59
54.61	59.03	60.96	57.63	56.63	26.59
55.88	60.30	62.23	58.90	57.90	27.86
57.15	61.57	63.50	60.17	59.17	27.86
58.42	62.84	64.77	61.44	60.44	29.13
59.69	64.11	66.04	62.71	61.71	29.13
60.96	65.38	67.31	63.98	62.98	30.40
62.23	66.65	68.58	65.25	64.25	30.40

Please insert digit for stacking height

6.25 mm ▶ 1
9.05 mm ▶ 2

for performance level 1
for performance level S4
for performance level 2

2
5
6

333
000

for samples
for 280 pieces on reel