



**SPECIFICATIONS**  
 Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 650V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Black



**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
A2005H-02P	2.00	6.00
A2005H-03P	4.00	8.00
A2005H-04P	6.00	10.00
A2005H-05P	8.00	12.00
A2005H-06P	10.00	14.00
A2005H-07P	12.00	16.00
A2005H-08P	14.00	18.00
A2005H-09P	16.00	20.00
A2005H-10P	18.00	22.00
A2005H-11P	20.00	24.00
A2005H-12P	22.00	26.00
A2005H-13P	24.00	28.00
A2005H-14P	26.00	30.00
A2005H-15P	28.00	32.00

UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	<b>2.00mm PITCH HOUSING</b>
DRAWN BY	APPROVED BY		
董正一	董正一		
2005.04.16	2005.04.16		
GENERAL TOLERANCE			
B1	REVISE	2006.12.12	X. X±0.25
B0	NEW RELEASE	2005.11.24	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
DRAW NO.:			REV.:
A2005H-XP			B1