



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, CA 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPD5807 thru SPD5811 SPD5807SMS thru SPD5811SMS

Designer's Data Sheet

Part Number/Ordering Information ^{1/}

SPD _ _ _

L Screening ^{2/}

- _ = Not Screened
- TX = TX Level
- TXV = TXV Level
- S = S Level

L Package Type

- _ = Axial Leaded
- SMS = Surface Mount Square Tab
- ASMS = SMS with .240" max Body Length

Voltage/Family

- 5807 = 50V
- 5809 = 100V
- 5811 = 150V

6.0 AMPS
50 – 150 VOLTS
40 ns HYPERFAST RECOVERY
RECTIFIER

FEATURES:

- Hyper Fast Reverse Recovery: 40ns Maximum ^{4/}
- PIV to 150 Volts (Voltages Up To 300V Available)
- Hermetically Sealed
- Low Forward Voltage Drop
- Void Free Chip Construction
- For High Efficiency Applications
- Available in Axial & Square Tab Versions
- TX, TXV, and S-Level Screening Available ^{2/}
- Replacement for: 1N5807, US thru 1N5811, US
- For Solid Silver Leads Version (Includes Formed / Flat Leads Option), See 1N5807 – 1N5811 Series


MAXIMUM RATINGS ^{3/}

RATING		SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage And DC Blocking Voltage	SPD5807	V_{RRM}	50	Volts
	SPD5809	V_{RWM}	100	
	SPD5811	V_R	150	
Average Rectified Forward Current (Resistive Load, 60Hz, Sine Wave, $T_A = 25^\circ\text{C}$)		I_o	6.0	Amps
Peak Surge Current (8.3 ms pulse, half sine wave, superimposed on I_o , allow junction to reach equilibrium between pulses, $T_A = 25^\circ\text{C}$)		I_{FSM}	125	Amps
Operating & Storage Temperature		T_J and T_{STG}	-65 to +175	$^\circ\text{C}$
Thermal Resistance	Junction to Lead for Axial, $L = .375"$	$R_{\theta JL}$	20	$^\circ\text{C/W}$
	Junction to End Tab for Surface Mount	$R_{\theta JE}$	12	


NOTES:

- ^{1/} For ordering Information, price, operating curves, and availability- Contact factory.
- ^{2/} Screening based on MIL-PRF-19500. Screening flows available on request.
- ^{3/} Unless otherwise specified, all electrical characteristics @25 $^\circ\text{C}$.
- ^{4/} $I_F = 500\text{mA}$, $I_R = 1\text{A}$, $I_{RR} = 250\text{mA}$, $T_A = 25^\circ\text{C}$.

Axial Leaded



SMS



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0108F

DOCX



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, CA 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SPD5807 thru SPD5811
SPD5807SMS thru SPD5811SMS

ELECTRICAL CHARACTERISTICS ^{3/}				
CHARACTERISTICS		SYMBOL	VALUE	UNIT
			MAX	
Instantaneous Forward Voltage Drop $I_F = 6.0 \text{ Adc}, 300\mu\text{s pulse}$	$T_A = +25^\circ\text{C}$ $T_A = -55^\circ\text{C}$	V_{F1} V_{F2}	0.975 1.08	Vdc
Reverse Leakage Current Rated V_R , 300 μs pulse min	$T_A = +25^\circ\text{C}$ $T_A = +100^\circ\text{C}$	I_{R1} I_{R2}	20 1	μA mA
Junction Capacitance $V_R = 10 \text{ Vdc}, f = 1\text{MHz}, T_A = 25^\circ\text{C}$		C_J	100	μF
Reverse Recovery Time $I_F = 500\text{mA}, I_R = 1\text{A}, I_{RR} = 250\text{mA}, T_A = 25^\circ\text{C}$		t_{rr}	40	ns

Package Outlines:

DIMENSIONS (inches)			DIMENSIONS (inches)		
DIM.	Minimum	Maximum	DIM.	Minimum	Maximum
A	.130	.170	A	.172	.180
B	---	.240	B	.200	.290 (SMS)
C	.038	.042	B	.200	.240 (ASMS)
D	1.000	---	C	.020	.035
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>AXIAL</p> </div> <div style="width: 45%;"> <p>SMS</p> </div> </div>			D	.002	---

NOTES:

- 1/ For Ordering Information, Price, Operating Curves, and Availability- Contact Factory.
- 2/ Screening Based on MIL-PRF-19500. Screening Flows Available on Request.
- 3/ Unless Otherwise Specified, All Electrical Characteristics @25°C.
- 4/ $I_F = 500\text{mA}, I_R = 1\text{A}, I_{RR} = 250\text{mA}, T_A = 25^\circ\text{C}$.