

BRIDGE RECTIFIERS, Standard Recovery, Plastic Package

ISI Part Number	Maximum Average Rectified Current at T _a		Peak Inverse Voltage	Peak Forward Surge Current @ 8.3ms Superimposed	Maximum Forward Voltage @ Rated I _F and T _a = 25°C		Maximum Reverse Current @ Rated PIV and T _a = 25°C	Package Quantities	Outline
	I _F (Amps)	T _a (°C)			V _{FM} (Volts)	I _{FSM} (Amps)			
PB605	6.0	50	50	200	3.0	3.0	10	200	<p>PB-6</p>
PB61									
PB62									
PB64									
PB66									
PB68									
PB610									
MB605	8.0	75	50	125	1.0	4.0	5.0	200	<p>BR-6 Ceramic Case</p>
MB61									
MB62									
MB64									
MB66									
MB68									
MB610									
MB1005	10	75	50	150	1.0	5.0	5.0	200	<p>BR-6 Ceramic Case</p>
MB101									
MB102									
MB104									
MB106									
MB108									
MB1010									
MB1505	15	55	50	300	7.5	1.1	10	50	<p>MB-35 Metal Case</p>
MB151									
MB152									
MB154									
MB156									
MB158									
MB1510									
MB1505W	15	55	50	300	7.5	1.1	10	50	<p>MB-35W Metal Case</p>
MB151W									
MB152W									
MB154W									
MB156W									
MB158W									
MB1510W									
MB2505	25	55	50	300	12.5	1.1	10	50	<p>MB-35 Metal Case</p>
MB251									
MB252									
MB254									
MB256									
MB258									
MB2510									
MB2505W	25	55	50	300	12.5	1.1	10	50	<p>MB-35W Metal Case</p>
MB251W									
MB252W									
MB254W									
MB256W									
MB258W									
MB2510W									