

3.3V, MEMS, LVDS Oscillator



Model: 4MA_Z4AACUGI8

RoHS Compliant / Pb Free/REACH Compliant

Rev. 4/2013

Page 1 of 3

http://www.foxonline.com/need_a_sample.htm

Need a
Sample®

FEATURES

- MEMS Technology
- 3.3V Supply Voltage
- 40 to +85°C Operating Temperature
- 7x5mm Plastic Package
- Low Phase Jitter (0.6pS RMS Typical - 12kHz to 20MHz)
- LVDS Output

Developed Frequencies and Part Number Selection

Frequency	Model Number	Part Number
100.000 MHz	4MA100000Z4AACUGI8	848B-100-xxxxx
125.000 MHz	4MA125000Z4AACUGI8	848B-125-xxxxx
148.500 MHz	4MA148500Z4AACUGI8	848B-148.5-xxxxx
150.000 MHz	4MA150000Z4AACUGI8	848B-150-xxxxx
156.250 MHz	4MA156250Z4AACUGI8	848B-156.25-xxxxx
200.000 MHz	4MA200000Z4AACUGI8	848B-200-xxxxx

ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency (Fo)	50.000 ~ 625.000 MHz ¹
Operating Temperature Range (T _{OPR})	-40 ~ +85°C
Frequency Stability	±50 PPM ²
Supply Voltage (V _{DD})	3.3V ± 10%
Input Current (I _{DD}) (no load)	100mA Typical
Output Symmetry (50% V _A)	48/52%
Rise Time (T _R) (20% ~ 80% V _A)	600 pS
Fall Time (T _F) (80% ~ 20% V _A)	600 pS
Output Voltage (V _{OL}) (V _{OH})	1.05V Typical 1.4V Typical
Output Amplitude (Single Ended) (V _A)	0.35Vp-p Typical
Mid Level (V _M)	1.22V Typical
Output Load	100 Ohms Typical
Start-up Time (T _S)	10ms
Output Disable Time ³	1 uS
Output Enable Time ³	1 uS
Aging (10 years @ 25°C)	±5 PPM Typical
Phase Jitter (12kHz to 20MHz)	0.6 pS RMS Typical
Period Jitter	3.9 pS RMS Typical
Cycle-to-Cycle Jitter (1,000 cycles)	30 pS Peak Typical
Maximum Soldering Temp / Time	260°C / 10 Seconds
Termination Finish	Matte Sn


¹ Check for available frequencies.

² Inclusive of 25°C tolerance after reflow, operating temperature range, supply voltage change and aging.

³ An internal pull-up resistor from pin 1 to pin 6 allows active output if pin 1 is left open.

Note: A 0.01µF bypass capacitor should be placed between V_{DD} (Pin 6) and GND (Pin 3) to minimize power supply line noise.

All specifications subject to change without notice.



ENABLE / DISABLE FUNCTION

(Pin 1)	OUT (Pin 4, Pin 5)
OPEN ³	ACTIVE
'1' Level V _{IH} ≥ 70%V _{DD}	ACTIVE
'0' Level V _{IL} ≤ 30%V _{DD}	High Z

3.3V, MEMS, LVDS Oscillator



Model: 4MA_Z4AACUGI8

RoHS Compliant / Pb Free/REACH Compliant


Rev. 4/2/2013

Page 2 of 3


http://www.foxonline.com/need_a_sample.htm




Block Diagram



Recommended Circuit



Waveform Characteristics



3.3V, MEMS, LVDS Oscillator



Model: 4MA_Z4AACUGI8

RoHS Compliant / Pb Free/REACH Compliant

Rev. 4/2/2013


Page 3 of 3

http://www.foxonline.com/need_a_sample.htm



• TAPE SPECIFICATIONS (millimeters)					
A	B	C	D	E	F
Ø1.5	4.0	8.0	7.5	16.0	1.1

• REEL SPECIFICATIONS (millimeters)						
G	H	I	J	K	L	M
2.0	Ø13	Ø21	Ø180	Ø332	18.4	2.0



DISCLAIMER FOX and Integrated Device Technology, Inc. (IDT) reserve the right to modify the products and/or specifications described herein at any time and at FOX/IDT's sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of FOX/IDT's products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of FOX/IDT or any third parties. FOX/IDT's products are not intended for use in life support systems or similar devices where the failure or malfunction of a FOX/IDT product can be reasonably expected to significantly affect the health or safety of users. Anyone using a FOX/IDT product in such a manner does so at their own risk, absent an express, written agreement by FOX/IDT.