

角型LED Angular type LED

Ta=25°C

機種名 Type No.	ピーク発光波長 Peak-emission wavelength nm (Color)	樹脂外観 Lens appearance	絶対最大定格 Absolute maximum ratings				電気的光学的特性 Electro-optical characteristics				
			IF	VR	PD	Topr	Vf Typ.	IF	Luminous intensity		IR Max.
			mA	V	mW	°C	V	mA	Iv Typ. mcd	IF mA	(VR=3V) μA
2 X 5	SLP-555D-50	700 (R)	25	3	70	-25~+80	1.9	5	0.7	5	10
		565 (G)	25	3	70	-25~+80	2.1	20	5.5	20	10
	SLP-155B-81	700 (R)	25	3	70	-25~+80	1.9	5	0.8	5	10
	SLP-255B-81	565 (G)	25	3	70	-25~+80	2.1	20	2.3	20	10
2 X 6	SLP-455B-81	585 (Y)	25	3	70	-25~+80	2.1	20	3.3	20	10
	SLP-173B-51	700 (R)	25	3	70	-25~+80	1.9	5	0.5	5	10
	SLP-273B-51	565 (G)	25	3	70	-25~+80	2.1	20	1.5	20	10
2.4 X 9	SLP-473B-51	585 (Y)	25	3	70	-25~+80	2.1	20	2.8	20	10
	SLP-3122C-81	567 (Y.G)	25	3	70	-25~+80	2.1	20	70	20	10
	SLP-4122C-81	585 (Y)	25	3	70	-25~+80	2.1	20	80	20	10
4.9	SLP-9122C-81	630 (U.R)	25	3	70	-25~+80	2.1	20	45	20	10
2.4 X 7.4	SLP-165B-81	700 (R)	25	3	70	-25~+80	1.9	5	0.3	5	10
	SLP-265B-81	565 (G)	25	3	70	-25~+80	2.1	20	1.7	20	10
	SLP-465B-81	585 (Y)	25	3	70	-25~+80	2.1	20	2.7	20	10
□3.6	SLP-153B-51	700 (R)	25	3	70	-25~+80	1.9	5	0.55	5	10
	SLP-253B-51	565 (G)	25	3	70	-25~+80	2.1	20	1.5	20	10
	SLP-453B-51	585 (Y)	25	3	70	-25~+80	2.1	20	3.9	20	10

■外観図 Package dimensions

Tolerance : ±0.2
Unit : mm

