

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE 20 to 200 Volts CURRENT 8.0 Amperes

FEATURES


- * High reliability
- * Low switching loss
- * Low forward voltage drop
- * High current capability
- * High switching capability

MECHANICAL DATA

- * Epoxy: Device has UL flammability classification 94V-0
- * Case: Molded plastic
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting: position: Any
- * Weight: 1.35 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	SR820S	SR830S	SR835S	SR840S	SR845S	SR850S	SR860S	SR880S	SR8100S	SR8150S	SR8200S	UNITS	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	35	40	45	50	60	80	100	150	200	Volts	
Maximum RMS Voltage	V _{RMS}	14	21	25	28	32	35	42	56	70	105	140	Volts	
Maximum DC Blocking Voltage	V _{DC}	20	30	35	40	45	50	60	80	100	150	200	Volts	
Maximum Average Forward Rectified Current at Derating Case Temperature	I _O	8.0											Amps	
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	150											Amps	
Typical Thermal Resistance (Note 1)	R _{θJA}	60											°C/W	
	R _{θJC}	3												
Typical Junction Capacitance (Note 2)	C _J	700					450							pF
Operating Temperature Range	T _J	150											°C	
Storage Temperature Range	T _{STG}	-55 to + 150											°C	

ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)

CHARACTERISTICS	SYMBOL	SR820S	SR830S	SR835S	SR840S	SR845S	SR850S	SR860S	SR880S	SR8100S	SR8150S	SR8200S	UNITS
Maximum Instantaneous Forward Voltage at 8.0A DC	V _F	.65					.75		.85				Volts
Maximum Average Reverse Current at Rated DC Blocking Voltage	I _R	@T _A = 25°C											mA
		@T _A = 100°C											
		2											mA

- NOTES : 1. Thermal Resistance : Heat-sink case mounted or if PCB mounted.
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.
3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".
4. Suffix "R" for Reverse Polarity.
5. Suffix "K" for D-PAK Pkg.

RATING AND CHARACTERISTICS CURVES (SR820S THRU SR8200S)




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL REVERSE CHARACTERISTICS




FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 TYPICAL JUNCTION CAPACITANCE




FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




RECTRON

Attachment information about SR8XXS

1. Internal Circuit



2. Marking on the body



PACKAGING OF DIODE AND BRIDGE RECTIFIERS

BULK PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	GROSS WEIGHT(Kg)
A-405	-B	1,000	194*84*21	450*220*255	50,000	15.64
BR-3/-6	-B	200	206*208*55	450*220*255	1,600	6.00 / 6.80
BR-8/-10	-B	200	236*236*50	497*251*282	2,000	12.24
BR-15/-25/-35/(W)	-B	50	203*205*57	450*220*255	400	12.50 (14.40)
DO-15	-B	500	194*84*21	450*220*255	25,000	12.74
DO-201	-B	500	300*73*40	347*320*271	12,000	15.90
DO-41	-B	1,000	194*75*21	415*220*255	50,000	16.2
HVM	-B	200	165*214*52	353*226*290	2,000	---
HVP	-B	40	236*236*40	502*251*145	240	8.80
MB-15/-25/-35(W)	-B	50	203*205*57	450*220*255	400	13.60 (14.30)
MP-15/-25/-35(W)	-B	50	203*205*57	450*220*255	400	7.7 (8.26)
R-1/-3	-B	1000 / 500	194*84*21	450*220*255	50,000 / 25,000	11.74 / 16.17
R-6	-B	200	300*73*40	347*320*271	4,800	12.93
RB-15	-B	1,000	165*252*59	347*320*271	10,000	11.6
RBU	-B	450	240*239*35	502*251*126	2,700	13.00
RC-2	-B	600	165*252*59	347*320*271	6,000	9.4
RS-1	-B	600	240*239*35	497*255*162	4,800	9.264
RS-2L	-B	400	213*162*52	450*220*255	4,000	13.65
RS-4L	-B	300	230*162*52	502*251*126	1,800	11.3
RS-6/-8	-B	200	236*236*34	497*255*162	1,600	13.6 / 14.5
RS-2M	-B	600	236*236*40	492*255*167	3,600	10.28
RS-4M/-10M	-B	600	236*236*40	497*251*100	2,400	11.09
RS-6/8/15/20/25M	-B	300	230*190*46	410*243*157	1,800	13.37
WOM	-B	600	165*252*59	347*320*271	6,000	11.0

TUBE PACK

PACKAGE	PACKING CODE	EA PER BOX	INNER BOX SIZE (mm)	CARTON SIZE (mm)	EA PER CARTON	WEIGHT(Kg)
BDB	-C	2,000	450*140*84	464*305*283	12,000	14.18
D2PAK	-C	2,000	550*140*92	572*308*120	4,000	10.20
DB-1	-C	2,500	450*140*84	464*305*283	15,000	14.30
DB-LS	-C	4,000	450*140*84	464*305*283	24,000	16.45
DB-S	-C	4,000	450*140*84	464*305*283	24,000	18.44
RBU	-C	1,000	490*135*110	510*293*131	2,000	13.62
RS-1M/-2M	-C	1,350	540*118*118	560*259*144	2,700	12.03
RS-4M/-10M	-C	900	540*118*118	560*259*144	1,800	12.82
RS-6/8/15/20/25M	-C	600	490*135*110	510*293*131	1,200	13.12
(I)TO-220/TO-220(A)	-C	2,000	550*140*92	572*308*120	4,000	11.80
TO-247	-C	900	550*140*92	572*308*120	1,800	7.60

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.