

# PRELIMINARY DATA SHEET

# NEC

## NPN SILICON EPITAXIAL TWIN TRANSISTOR

## UPA833TF

### FEATURES



- **LOW NOISE:**  
 Q1: NF = 1.7 dB TYP at f = 2 GHz, V<sub>CE</sub> = 1 V, I<sub>c</sub> = 3 mA  
 Q2: NF = 1.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 3 mA
- **HIGH GAIN:**  
 Q1: |S<sub>21E</sub>|<sup>2</sup> = 3.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 1 V, I<sub>c</sub> = 3 mA  
 Q2: |S<sub>21E</sub>|<sup>2</sup> = 8.5 dB TYP at f = 2 GHz, V<sub>CE</sub> = 3 V, I<sub>c</sub> = 10 mA
- **6-PIN THIN-TYPE SMALL MINI MOLD PACKAGE**
- **2 DIFFERENT BUILT-IN TRANSISTORS**  
 (Q1: NE688, Q1: NE685)

### DESCRIPTION

The UPA833TF has two different built-in transistors for low cost amplifier and oscillator applications up to L and S band. Low noise figures, high gain, high current capability, and medium output give this device high dynamic range and excellent linearity for two-stage amplifiers. This device is also ideally suited for use in a VCO/buffer amplifier application. The thinner package style allows for higher density designs.

### OUTLINE DIMENSIONS (Units in mm)

Package Outline TS06 (Top View)



#### PIN CONNECTIONS

1. Collector (Q1)
2. Emitter (Q1)
3. Collector (Q2)
4. Base (Q2)
5. Emitter (Q2)
6. Base (Q1)

#### Note:

Pin 1 is the lower left most pin as the package lettering is oriented and read left to right.

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C)

PART NUMBER PACKAGE OUTLINE				UPA833TF TS06		
	SYMBOLS	PARAMETERS AND CONDITIONS	UNITS	MIN	TYP	MAX
Q1	I <sub>CBO</sub>	Collector Cutoff Current at V <sub>CB</sub> = 5 V, I <sub>E</sub> = 0	μA			0.1
	I <sub>EBO</sub>	Emitter Cutoff Current at V <sub>EB</sub> = 1 V, I <sub>C</sub> = 0	μA			0.1
	h <sub>FE</sub>	DC Current Gain <sup>1</sup> at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA		100		145
	f <sub>r</sub>	Gain Bandwidth (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	GHz	4.0	4.5	
	f <sub>r</sub>	Gain Bandwidth (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 20 mA, f = 2 GHz	GHz		9	
	C <sub>re</sub>	Feedback Capacitance <sup>2</sup> at V <sub>CB</sub> = 1 V, I <sub>E</sub> = 0, f = 1 MHz	pF		0.75	0.85
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB	2.5	3.5	
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 20 mA, f = 2 GHz	dB		6.5	
	NF	Noise Figure (1) at V <sub>CE</sub> = 1 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB		1.7	2.5
	NF	Noise Figure (2) at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 7 mA, f = 2 GHz	dB		1.5	
Q2	I <sub>CBO</sub>	Collector Cutoff Current at V <sub>CB</sub> = 5 V, I <sub>E</sub> = 0	μA			0.1
	I <sub>EBO</sub>	Emitter Cutoff Current at V <sub>EB</sub> = 1 V, I <sub>C</sub> = 0	μA			0.1
	h <sub>FE</sub>	DC Current Gain <sup>1</sup> at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA		75		150
	f <sub>r</sub>	Gain Bandwidth at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA, f = 2 GHz	GHz		12	
	C <sub>re</sub> <sup>2</sup>	Feedback Capacitance <sup>2</sup> at V <sub>CB</sub> = 3 V, I <sub>E</sub> = 0, f = 1 MHz	pF		0.4	0.7
	S <sub>21E</sub>   <sup>2</sup>	Insertion Power Gain at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 10 mA, f = 2 GHz	dB	7	8.5	
	NF	Noise Figure at V <sub>CE</sub> = 3 V, I <sub>C</sub> = 3 mA, f = 2 GHz	dB		1.5	2.5

- Notes: 1. Pulsed measurement, pulse width ≤ 350 μs, duty cycle ≤ 2 %.  
 2. Collector to base capacitance when measured with capacitance meter (automatic balanced bridge method), with emitter connected to guard pin of capacitances meter.


**ABSOLUTE MAXIMUM RATINGS<sup>1</sup>** (T<sub>A</sub> = 25°C)

SYMBOLS	PARAMETERS	UNITS	RATINGS	
			Q1	Q2
V <sub>CB0</sub>	Collector to Base Voltage	V	9	9
V <sub>CE0</sub>	Collector to Emitter Voltage	V	6	6
V <sub>EB0</sub>	Emitter to Base Voltage	V	2	2
I <sub>c</sub>	Collector Current	mA	100	30
P <sub>T</sub>	Total Power Dissipation	mW	150	150
			200 <sup>2</sup>	
T <sub>J</sub>	Junction Temperature	°C	150	150
T <sub>STG</sub>	Storage Temperature	°C	-65 to +150	


Note: 1. Operation in excess of any one of these parameters may result in permanent damage.  
 2. When operating both devices, the power dissipation for either device should not exceed 110 mW.

**TYPICAL PERFORMANCE CURVES** (T<sub>A</sub> = 25°C)


**Q1**  
 TOTAL POWER DISSIPATION vs.  
 AMBIENT TEMPERATURE




**Q2**  
 TOTAL POWER DISSIPATION vs.  
 AMBIENT TEMPERATURE









**COLLECTOR CURRENT vs.  
 BASE TO EMITTER VOLTAGE**



**COLLECTOR CURRENT vs.  
 BASE TO EMITTER VOLTAGE**




**TYPICAL PERFORMANCE CURVES** ( $T_A = 25^\circ\text{C}$ )



TYPICAL PERFORMANCE CURVES (TA = 25°C)


Q1

INSERTION POWER GAIN vs. COLLECTOR CURRENT




Q2


INSERTION POWER GAIN vs. COLLECTOR CURRENT




NOISE FIGURE vs. COLLECTOR CURRENT




NOISE FIGURE vs. COLLECTOR CURRENT






FEEDBACK CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE



FEEDBACK CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE



**TYPICAL PERFORMANCE CURVES** ( $T_A = 25^\circ\text{C}$ )



## TYPICAL SCATTERING PARAMETERS

### Q1

VCE = 3 V, IC = 1 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.97	-14.33	2.43	166.54	0.04	80.24	0.99	-7.18
0.20	0.95	-28.67	2.38	154.71	0.07	70.60	0.97	-13.99
0.30	0.91	-42.88	2.36	144.04	0.10	62.11	0.92	-19.89
0.40	0.87	-56.75	2.27	134.07	0.13	54.03	0.88	-25.53
0.50	0.83	-70.72	2.23	125.01	0.15	47.25	0.83	-29.96
0.60	0.79	-84.33	2.16	116.71	0.16	40.79	0.78	-34.25
0.70	0.75	-97.41	2.08	108.43	0.17	35.62	0.75	-37.36
0.80	0.71	-109.76	1.99	101.04	0.17	31.08	0.70	-40.60
0.90	0.68	-122.09	1.92	93.80	0.18	26.89	0.67	-43.12
1.00	0.66	-133.22	1.82	87.30	0.18	23.81	0.64	-45.41
1.20	0.62	-154.11	1.66	75.63	0.18	19.11	0.60	-49.75
1.50	0.61	179.69	1.43	60.93	0.17	15.48	0.56	-56.32
1.70	0.61	165.55	1.29	52.57	0.16	15.97	0.54	-61.07
2.00	0.63	147.73	1.12	41.71	0.15	20.29	0.52	-69.09
2.50	0.67	125.32	0.92	27.04	0.15	33.50	0.50	-85.80
3.00	0.72	109.50	0.76	16.28	0.19	42.71	0.50	-105.83

### Q2

VCE = 3 V, IC = 1 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.98	-5.93	2.43	171.79	0.02	85.64	0.99	-3.75
0.20	0.97	-11.82	2.41	164.40	0.04	80.86	0.99	-7.53
0.30	0.95	-17.85	2.42	157.59	0.05	76.45	0.97	-11.10
0.40	0.93	-23.59	2.39	151.04	0.07	72.26	0.95	-14.56
0.50	0.90	-29.61	2.38	144.91	0.09	68.73	0.93	-17.91
0.60	0.87	-35.62	2.37	139.49	0.10	64.78	0.90	-21.19
0.70	0.84	-41.49	2.34	133.87	0.11	61.52	0.87	-23.71
0.80	0.81	-47.40	2.32	128.66	0.12	58.06	0.85	-26.91
0.90	0.77	-53.49	2.32	123.12	0.13	55.30	0.82	-29.05
1.00	0.73	-59.00	2.26	118.06	0.14	52.86	0.78	-31.52
1.20	0.65	-71.05	2.21	108.31	0.16	48.61	0.73	-35.51
1.50	0.54	-89.53	2.13	94.49	0.17	43.82	0.66	-41.12
1.70	0.47	-101.29	2.02	86.01	0.18	41.68	0.61	-44.56
2.00	0.40	-120.45	1.90	74.87	0.19	39.57	0.55	-49.87
2.50	0.33	-153.17	1.71	57.60	0.21	38.43	0.46	-59.91
3.00	0.33	177.01	1.54	42.57	0.23	38.11	0.38	-74.21

## TYPICAL SCATTERING PARAMETERS

### Q1

$V_{CE} = 3\text{ V}$ ,  $I_C = 5\text{ mA}$ ,  $Z_0 = 50\ \Omega$

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.85	-26.44	10.69	155.98	0.03	73.46	0.92	-19.86
0.20	0.75	-51.20	9.61	139.24	0.06	61.17	0.79	-34.91
0.30	0.64	-75.20	8.75	125.25	0.07	54.17	0.65	-44.33
0.40	0.56	-96.72	7.76	113.92	0.08	50.16	0.55	-51.20
0.50	0.49	-115.03	6.80	104.72	0.09	48.17	0.48	-55.56
0.60	0.45	-130.31	5.95	97.69	0.10	47.13	0.42	-59.25
0.70	0.42	-143.59	5.26	91.52	0.11	46.84	0.38	-61.89
0.80	0.41	-155.39	4.72	86.26	0.11	46.85	0.35	-64.36
0.90	0.40	-165.50	4.25	81.56	0.12	46.62	0.32	-66.67
1.00	0.40	-174.72	3.87	77.29	0.13	46.83	0.30	-68.91
1.20	0.41	169.76	3.28	69.66	0.14	46.94	0.27	-73.69
1.50	0.43	151.58	2.66	59.70	0.16	46.31	0.23	-82.66
1.70	0.45	142.01	2.36	53.73	0.18	45.59	0.22	-89.61
2.00	0.49	130.04	2.01	45.17	0.20	44.01	0.20	-101.67
2.50	0.54	114.93	1.62	32.99	0.24	40.36	0.20	-125.90
3.00	0.60	103.96	1.36	22.18	0.27	36.49	0.21	-149.97

### Q2

$V_{CE} = 3\text{ V}$ ,  $I_C = 5\text{ mA}$ ,  $Z_0 = 50\ \Omega$

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.89	-12.31	10.46	162.72	0.02	81.62	0.96	-9.77
0.20	0.83	-23.63	9.75	149.86	0.03	74.55	0.90	-17.75
0.30	0.75	-34.70	9.25	138.82	0.04	69.69	0.81	-23.24
0.40	0.66	-44.55	8.62	129.30	0.06	66.77	0.74	-27.15
0.50	0.57	-53.23	7.96	120.72	0.06	64.98	0.68	-29.45
0.60	0.50	-60.42	7.27	113.73	0.07	63.78	0.62	-31.18
0.70	0.43	-66.51	6.64	107.23	0.08	63.28	0.58	-32.03
0.80	0.37	-71.94	6.08	101.84	0.09	62.73	0.55	-32.89
0.90	0.33	-76.60	5.57	97.19	0.10	62.37	0.52	-33.36
1.00	0.29	-81.19	5.15	92.96	0.10	62.23	0.49	-33.76
1.20	0.23	-90.41	4.45	85.71	0.12	61.60	0.45	-34.67
1.50	0.17	-106.89	3.70	76.63	0.14	60.08	0.40	-36.32
1.70	0.15	-120.69	3.33	71.22	0.16	58.93	0.37	-38.02
2.00	0.13	-145.48	2.92	63.46	0.19	57.05	0.33	-40.74
2.50	0.15	176.33	2.45	51.77	0.23	52.54	0.26	-48.08
3.00	0.22	153.43	2.12	40.65	0.27	47.15	0.17	-59.19

## TYPICAL SCATTERING PARAMETERS

### Q1

VCE = 3 V, IC = 10 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.71	-39.03	18.58	147.71	0.03	68.69	0.83	-30.16
0.20	0.57	-73.63	15.31	127.39	0.05	59.38	0.63	-48.07
0.30	0.45	-102.58	12.43	112.73	0.06	56.68	0.49	-57.41
0.40	0.39	-124.33	10.08	102.91	0.07	56.27	0.40	-63.51
0.50	0.36	-141.02	8.36	95.89	0.08	56.57	0.34	-67.57
0.60	0.35	-154.37	7.10	90.47	0.09	56.86	0.29	-71.19
0.70	0.34	-165.44	6.16	85.73	0.10	57.18	0.26	-74.31
0.80	0.34	-175.03	5.44	81.61	0.11	57.18	0.24	-77.41
0.90	0.34	176.63	4.87	77.75	0.12	57.09	0.22	-80.56
1.00	0.35	169.25	4.40	74.22	0.13	56.69	0.21	-83.81
1.20	0.37	156.83	3.70	67.77	0.15	55.55	0.19	-91.34
1.50	0.40	142.12	2.98	59.04	0.17	53.03	0.17	-104.99
1.70	0.42	134.21	2.63	53.75	0.19	51.04	0.16	-115.48
2.00	0.46	124.22	2.25	46.04	0.22	47.77	0.16	-131.74
2.50	0.52	111.30	1.81	37.71	0.26	41.70	0.19	-157.66
3.00	0.58	101.61	1.51	24.93	0.30	36.10	0.23	-177.86

### Q2

VCE = 3 V, IC = 10 mA, Z0 = 50 Ω

FREQUENCY (GHz)	S11		S21		S12		S22	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.79	-18.18	17.81	156.05	0.02	79.00	0.92	-14.07
0.20	0.67	-33.75	15.65	139.27	0.03	72.98	0.80	-22.91
0.30	0.55	-46.32	13.67	125.80	0.04	69.74	0.69	-27.06
0.40	0.44	-55.16	11.71	115.64	0.05	69.07	0.61	-28.96
0.50	0.37	-61.11	10.03	108.02	0.06	68.93	0.56	-29.47
0.60	0.31	-65.90	8.70	102.30	0.07	68.67	0.52	-29.62
0.70	0.26	-69.64	7.66	97.45	0.07	68.49	0.49	-29.55
0.80	0.23	-73.22	6.84	93.31	0.08	68.26	0.46	-29.57
0.90	0.20	-76.64	6.18	89.63	0.09	68.18	0.44	-29.61
1.00	0.18	-80.09	5.63	86.38	0.10	67.74	0.43	-29.60
1.20	0.14	-88.42	4.80	80.51	0.12	66.68	0.40	-29.99
1.50	0.10	-107.91	3.94	72.79	0.15	64.56	0.36	-31.58
1.70	0.08	-126.27	3.53	68.12	0.16	62.66	0.33	-33.11
2.00	0.09	-158.61	3.08	61.31	0.19	59.98	0.29	-35.72
2.50	0.13	164.55	2.57	50.55	0.24	54.48	0.22	-42.08
3.00	0.20	146.66	2.21	40.11	0.28	48.32	0.14	-51.14



## TYPICAL SCATTERING PARAMETERS

### Q1

$V_{CE} = 3\text{ V}$ ,  $I_C = 20\text{ mA}$ ,  $Z_0 = 50\ \Omega$

FREQUENCY (GHz)	S <sub>11</sub>		S <sub>21</sub>		S <sub>12</sub>		S <sub>22</sub>	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
0.10	0.52	-60.10	28.62	137.10	0.02	67.35	0.71	-41.30
0.20	0.39	-103.44	19.94	115.16	0.04	63.08	0.48	-59.79
0.30	0.33	-130.53	14.51	103.51	0.05	63.34	0.35	-68.39
0.40	0.31	-148.95	11.26	96.02	0.06	64.33	0.28	-74.25
0.50	0.30	-162.62	9.15	90.56	0.07	65.01	0.24	-78.55
0.60	0.30	-172.99	7.69	86.27	0.08	65.06	0.21	-82.95
0.70	0.31	178.35	6.63	82.36	0.09	64.97	0.19	-87.11
0.80	0.31	170.80	5.84	78.82	0.11	64.40	0.18	-91.38
0.90	0.32	164.26	5.21	75.55	0.12	63.46	0.16	-96.07
1.00	0.33	158.34	4.70	72.35	0.13	62.64	0.16	-100.35
1.20	0.35	148.21	3.94	66.66	0.15	60.45	0.15	-110.63
1.50	0.38	135.96	3.16	58.61	0.18	56.50	0.15	-127.25
1.70	0.41	129.06	2.79	53.72	0.20	53.77	0.15	-138.41
2.00	0.44	120.40	2.38	46.54	0.23	49.64	0.17	-153.87
2.50	0.50	108.77	1.90	35.67	0.27	42.37	0.21	-174.96
3.00	0.56	100.10	1.61	26.09	0.31	35.76	0.26	168.73

### BUILT-IN TRANSISTORS

	Q1	Q2
3-pin small mini mold part No.	NE68830	NE68530

### ORDERING INFORMATION

PART NUMBER	QUANTITY	PACKAGING
UPA833TF-T1	3000	Tape & Reel

The UPA836TF features the Q1 and Q2 in inverted positions.

## BJT NONLINEAR MODEL PARAMETERS(1)

Parameters	Q1	Q2	Parameters	Q1	Q2
IS	3.8e-16	7e-16	MJC	0.48	0.34
BF	135.7	109	XCJC	0.56	0
NF	1	1	CJS	0	0
VAF	28	15	VJS	0.75	0.75
IKF	0.6	0.19	MJS	0	0
ISE	3.8e-15	7.9e-13	FC	0.75	0.5
NE	1.49	2.19	TF	11e-12	3e-12
BR	12.3	1	XTF	0.36	5.2
NR	1.1	1.08	VTF	0.65	4.58
VAR	3.5	12.4	ITF	0.61	0.01
IKR	0.06	Infinity	PTF	50	0
ISC	3.5e-16	0	TR	32e-12	1e-9
NC	1.62	2	EG	1.11	1.11
RE	0.4	1.3	XTB	0	0
RB	6.14	10	XTI	3	3
RBM	3.5	8.34	KF	1.5e-14	0
IRB	0.001	0.009	AF	1.22	1
RC	4.2	10			
CJE	0.796e-12	0.4e-12			
VJE	0.71	0.81			
MJE	0.38	0.5			
CJC	0.549e-12	0.18e-12			
VJC	0.65	0.75			

(1) Gummel-Poon Model

## UNITS

Parameter	Units
time	seconds
capacitance	farads
inductance	henries
resistance	ohms
voltage	volts
current	amps


## MODEL RANGE

Frequency: 0.1 to 3.0 GHz  
Bias:  $V_{CE} = 0.5 \text{ V to } 5 \text{ V}$ ,  $I_C = 1 \text{ mA to } 10 \text{ mA}$   
Date: 11/98

## Note:

This nonlinear model utilized the latest data available. See our Design Parameter Library at [www.cel.com](http://www.cel.com) for this data.

## SCHEMATIC



## MODEL RANGE

Frequency: 0.1 to 3.0 GHz

Bias:  $V_{CE} = 0.5 \text{ V to } 5 \text{ V}$ ,  $I_C = 1 \text{ mA to } 10 \text{ mA}$ 

Date: 11/98

## BUILT-IN TRANSISTORS

	Q1	Q2
3-pin small mini mold part No.	NE68830	NE68530

The UPA836TF features the Q1 and Q2 in inverted positions.

## ORDERING INFORMATION

PART NUMBER	QUANTITY	PACKAGING
UPA833TF-T1	3000	Tape & Reel

EXCLUSIVE NORTH AMERICAN AGENT FOR **NEC** RF, MICROWAVE & OPTOELECTRONIC SEMICONDUCTORS

**CEL** CALIFORNIA EASTERN LABORATORIES • Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • Telex 34-6393 • FAX (408) 988-0279  
24-Hour Fax-On-Demand: 800-390-3232 (U.S. and Canada only) • Internet: <http://WWW.CEL.COM>

DATA SUBJECT TO CHANGE WITHOUT NOTICE



PRINTED IN USA ON RECYCLED PAPER -2/99