

DATA SHEET

BF245A; BF245B; BF245C N-channel silicon field-effect transistors

Product specification

1996 Jul 30

Supersedes data of April 1995

File under Discrete Semiconductors, SC07

N-channel silicon field-effect transistors BF245A; BF245B; BF245C

FEATURES

- Interchangeability of drain and source connections
- Frequencies up to 700 MHz.

APPLICATIONS


- LF, HF and DC amplifiers.

DESCRIPTION

General purpose N-channel symmetrical junction field-effect transistors in a plastic TO-92 variant package.

PINNING

PIN	SYMBOL	DESCRIPTION
1	d	drain
2	s	source
3	g	gate



MAM257

Fig.1 Simplified outline (TO-92 variant) and symbol.

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{DS}	drain-source voltage		–	–	± 30	V
V_{GSoFF}	gate-source cut-off voltage	$I_D = 10 \text{ nA}; V_{DS} = 15 \text{ V}$	-0.25	–	-8	V
V_{GS0}	gate-source voltage	open drain	–	–	-30	V
I_{DSS}	drain current	$V_{DS} = 15 \text{ V}; V_{GS} = 0$				
	BF245A		2	–	6.5	mA
	BF245B		6	–	15	mA
	BF245C		12	–	25	mA
P_{tot}	total power dissipation	$T_{amb} = 75^\circ\text{C}$	–	–	300	mW
$ y_{fs} $	forward transfer admittance	$V_{DS} = 15 \text{ V}; V_{GS} = 0; f = 1 \text{ kHz}; T_{amb} = 25^\circ\text{C}$	3	–	6.5	mS
C_{rs}	reverse transfer capacitance	$V_{DS} = 20 \text{ V}; V_{GS} = -1 \text{ V}; f = 1 \text{ MHz}; T_{amb} = 25^\circ\text{C}$	–	1.1	–	pF

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{DS}	drain-source voltage		–	± 30	V
V_{GDO}	gate-drain voltage	open source	–	–30	V
V_{GSO}	gate-source voltage	open drain	–	–30	V
I_D	drain current		–	25	mA
I_G	gate current		–	10	mA
P_{tot}	total power dissipation	up to $T_{amb} = 75^\circ\text{C}$;	–	300	mW
		up to $T_{amb} = 90^\circ\text{C}$; note 1	–	300	mW
T_{stg}	storage temperature		–65	+150	°C
T_j	operating junction temperature		–	150	°C

Note

1. Device mounted on a printed-circuit board, minimum lead length 3 mm, mounting pad for drain lead minimum 10 mm \times 10 mm.

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th j-a}$	thermal resistance from junction to ambient	in free air	250	K/W
	thermal resistance from junction to ambient		200	K/W

STATIC CHARACTERISTICS $T_j = 25^\circ\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{(BR)GSS}$	gate-source breakdown voltage	$I_G = -1 \mu\text{A}; V_{DS} = 0$	–30	–	V
V_{GSoff}	gate-source cut-off voltage	$I_D = 10 \text{nA}; V_{DS} = 15 \text{V}$	–0.25	–8.0	V
V_{GS}	gate-source voltage BF245A BF245B BF245C	$I_D = 200 \mu\text{A}; V_{DS} = 15 \text{V}$	–0.4	–2.2	V
			–1.6	–3.8	V
			–3.2	–7.5	V
I_{DSS}	drain current BF245A BF245B BF245C	$V_{DS} = 15 \text{V}; V_{GS} = 0$; note 1	2	6.5	mA
			6	15	mA
			12	25	mA
			–	–5	nA
I_{GSS}	gate cut-off current	$V_{GS} = –20 \text{V}; V_{DS} = 0$	–	–0.5	μA
		$V_{GS} = –20 \text{V}; V_{DS} = 0; T_j = 125^\circ\text{C}$	–	–0.5	μA

Note

1. Measured under pulse conditions: $t_p = 300 \mu\text{s}; \delta \leq 0.02$.

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C

DYNAMIC CHARACTERISTICS

Common source; $T_{amb} = 25^{\circ}\text{C}$; unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
C_{is}	input capacitance	$V_{DS} = 20\text{ V}; V_{GS} = -1\text{ V}; f = 1\text{ MHz}$	-	4	-	pF
C_{rs}	reverse transfer capacitance	$V_{DS} = 20\text{ V}; V_{GS} = -1\text{ V}; f = 1\text{ MHz}$	-	1.1	-	pF
C_{os}	output capacitance	$V_{DS} = 20\text{ V}; V_{GS} = -1\text{ V}; f = 1\text{ MHz}$	-	1.6	-	pF
g_{is}	input conductance	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 200\text{ MHz}$	-	250	-	μS
g_{os}	output conductance	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 200\text{ MHz}$	-	40	-	μS
$ y_{fs} $	forward transfer admittance	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 1\text{ kHz}$	3	-	6.5	mS
		$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 200\text{ MHz}$	-	6	-	mS
$ y_{rs} $	reverse transfer admittance	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 200\text{ MHz}$	-	1.4	-	mS
$ y_{os} $	output admittance	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 1\text{ kHz}$	-	25	-	μS
f_{gfs}	cut-off frequency	$V_{DS} = 15\text{ V}; V_{GS} = 0; g_{fs} = 0.7$ of its value at 1 kHz	-	700	-	MHz
F	noise figure	$V_{DS} = 15\text{ V}; V_{GS} = 0; f = 100\text{ MHz}$; $R_G = 1\text{ k}\Omega$ (common source); input tuned to minimum noise	-	1.5	-	dB


 $V_{DS} = 0; V_{GS} = -20\text{ V}$.

Fig.2 Gate leakage current as a function of junction temperature; typical values.






 $V_{DS} = 15\text{ V}; T_j = 25^{\circ}\text{C}$.

Fig.3 Transfer characteristics for BF245A; typical values.

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C

 $V_{DS} = 15\text{ V}; T_j = 25\text{ }^\circ\text{C}$.Fig.4 Output characteristics for BF245A;
typical values. $V_{DS} = 15\text{ V}; T_j = 25\text{ }^\circ\text{C}$.Fig.5 Transfer characteristics for BF245B;
typical values. $V_{DS} = 15\text{ V}; T_j = 25\text{ }^\circ\text{C}$.Fig.6 Output characteristics for BF245B;
typical values. $V_{DS} = 15\text{ V}; T_j = 25\text{ }^\circ\text{C}$.Fig.7 Transfer characteristics for BF245C;
typical values.

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C


 $V_{DS} = 15 \text{ V}; T_j = 25 \text{ }^\circ\text{C}.$

Fig.8 Output characteristics for BF245C; typical values.


 $V_{DS} = 15 \text{ V}.$

Fig.9 Drain current as a function of junction temperature; typical values for BF245A.


 $V_{DS} = 15 \text{ V}.$

Fig.10 Drain current as a function of junction temperature; typical values for BF245B.



 $V_{DS} = 15 \text{ V}.$

Fig.11 Drain current as a function of junction temperature; typical values for BF245C.


N-channel silicon field-effect transistors

BF245A; BF245B; BF245C




$V_{DS} = 15 \text{ V}; V_{GS} = 0; T_{amb} = 25^\circ\text{C}$.

Fig.12 Input admittance; typical values.




$V_{DS} = 15 \text{ V}; V_{GS} = 0; T_{amb} = 25^\circ\text{C}$.

Fig.13 Common source reverse admittance as a function of frequency; typical values.



$V_{DS} = 15 \text{ V}; V_{GS} = 0; T_{amb} = 25^\circ\text{C}$.

Fig.14 Common-source forward transfer admittance as a function of frequency; typical values.



$V_{DS} = 15 \text{ V}; V_{GS} = 0; T_{amb} = 25^\circ\text{C}$.

Fig.15 Common-source output admittance as a function of frequency; typical values.

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C


 $V_{DS} = 20$ V; $f = 1$ MHz; $T_{amb} = 25$ °C.

Fig.16 Input capacitance as a function of gate-source voltage; typical values.


 $V_{DS} = 20$ V; $f = 1$ MHz; $T_{amb} = 25$ °C.

Fig.17 Reverse transfer capacitance as a function of gate-source voltage; typical values.


 $V_{DS} = 15$ V; $f = 1$ kHz; $T_{amb} = 25$ °C.

Fig.18 Forward transfer admittance as a function of drain current; typical values.



 $V_{DS} = 15$ V; $T_j = 25$ °C.

Fig.19 Gate-source cut-off voltage as a function of drain current; typical values.


N-channel silicon field-effect transistors

BF245A; BF245B; BF245C



$V_{DS} = 0$; $f = 1$ kHz; $T_{amb} = 25$ °C.

Fig.20 Drain-source on-state resistance as a function of gate-source voltage; typical values.




$V_{DS} = 15$ V; $V_{GS} = 0$; $R_G = 1$ k Ω ; $T_{amb} = 25$ °C.
Input tuned to minimum noise.

Fig.21 Noise figure as a function of frequency; typical values.

N-channel silicon field-effect transistors

BF245A; BF245B; BF245C

PACKAGE OUTLINE



Dimensions in mm.

(1) Terminal dimensions within this zone are uncontrolled.

Fig.22 TO-92 variant.


N-channel silicon field-effect transistors**BF245A; BF245B; BF245C**

DEFINITIONS

Data Sheet Status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.



Info

Catalog by Function

- Discrete semiconductors
- Audio
- Clocks and Watches
- Data communications
- Microcontrollers
- Peripherals
- Standard analog
- Video
- Wired communications
- Wireless communications

Catalog by System

- Automotive
- Consumer Multimedia Systems
- Communications
- PC/PC-peripherals

Cross reference

Models

Packages

Application notes

Selection guides

Other technical documentation

End of Life information

Datahandbook system

Relevant Links

- About catalog tree
- About search
- About this site
- Subscribe to eNews
- Catalog & Datasheets
- Search
- BF245A; BF245B; BF245C
- BF245A; BF245B; BF245C

BF245A; BF245B; BF245C; N-channel silicon field-effect transistors

- [Description](#)
- [Features](#)
- [Applications](#)
- [Datasheet](#)
- [Products, packages, availability and ordering](#)
- [Find similar products](#)
- [Support & tools](#)
-
-

To be kept informed on B

Description

General purpose N-channel symmetrical junction field-effect transistors in a plastic 1 package.

Features

- Interchangeability of drain and source connections
- Frequencies up to 700 MHz.

Applications

- LF, HF and DC amplifiers.

Datasheet

Type nr.	Title	Publication release date	Datasheet status	Page count	File size (kB)
	BF245A; N-channel silicon field- BF245B; effect transistors BF245C	30-Jul-96	Product Specification	11	97

Products, packages, availability and ordering

<u>Partnumber</u>	<u>North American Partnumber</u>	<u>Order code (12nc)</u>	<u>marking/packing</u>	<u>package</u>	<u>device status</u>
BF245A	BF245A	9331 715 50112	Standard Marking *	Bulk Ammopack,	SOT54 Full productic Radial
		9331 715 50126	Standard Marking *	Ammopack, Radial	SOT54 Full productic
BF245B	BF245B	9331 143 30112	Standard Marking *	Bulk Ammopack,	SOT54 Full productic Radial
	BF245B AMO	9331 143 30126	Standard Marking *	Ammopack, Radial	SOT54 Full productic
BF245C	BF245C	9331 066 00112	Standard Marking *	Bulk Ammopack,	SOT54 Full productic Radial

Find similar products:

[BF245A; BF245B; BF245C](#) links to the similar products page containing an overview of products that are similar in function or related to the part number(s) as listed on this page. This page includes products from the same catalog tree(s), relevant selection guides and products from the same functional category.

Support & tools[Spice model of BF245A](#)[Spice model of BF245B](#)[Spice model of BF245C](#)