

## **Thick Film Chip Resistor Array**


**RA03 (0603SIZE / 4-ELEMENTS)**

**RA02 (0402SIZE / 4-ELEMENTS)**

### **FEATURES**

1. High density SMD packaging gives higher productivity and reduced assembly costs.
2. Suitable for flow and reflow soldering.
3. Suitable for automatic surface mount.

### **DIMENSIONS AND STRUCTURE**



Unit: mm

STYLE	TYPE	Terminal	L	W	H	Q1	a	b	p	Q2	D
RA 02	024R	Convex	2.0±0.1	1.0±0.1	0.45±0.1	0.3±0.1	0.2±0.1	0.3±0.1	0.5±0.1	0.2±0.1	0.2±0.1
RA 03	034R	Convex	3.2±0.15	1.6±0.2	0.6±0.1	0.65±0.15	0.3±0.15	0.3±0.15	0.8±0.1	0.45±0.1	0.38±0.1

### **RATINGS**

TYPE	Rated Power At 70°C (w)	Maximum Working Voltage (Vw)	Maximum Overload Voltage (Vo)	Temperature Coefficient of Resistance (ppm/°C)	Resistance Range	Resistance Tolerance	Operating Temperature Range (°C)
024R	1/16	50	100	±200	10Ω~1MΩ	J(± 5%) F(± 1%)	-55~+125
034R	1/16	50	100	±200	10Ω~1MΩ	J(± 5%) F(± 1%)	