


# NEW ENGLAND SEMICONDUCTOR

## SMALL SIGNAL PNP TRANSISTOR TO-18

PACKAGE	DEVICE TYPE	V <sub>CEO</sub> (sus) VOLTS	I <sub>C</sub> (max) AMPS	h <sub>FE</sub> @ I <sub>C</sub> /V <sub>CE</sub> min/max @ mA/V	V <sub>CE(sat)</sub> @ I <sub>C</sub> /I <sub>B</sub> V @ mA/mA	C <sub>Q<sub>F</sub></sub> p	f <sub>T</sub> (MHz)
TO-18 TO206AA  	2N2906	40	0.6	40/120@150/10	0.4@150/15	8	200
	2N2906A^	60	0.6	40/120@150/10	0.4@150/15	8	200
	2N2907	40	0.6	100/300@150/10	0.4@150/15	8	200
	2N2907A^	60	0.6	100/300@150/10	0.4@150/15	8	200
	2N3250A^	60	0.2	50/150@10/1	0.25@10/1	6	250
	2N3251A^	60	0.2	100/300@10/1	0.25@10/1	6	300
	2N3496	80	0.1	40@10/10	0.3@10/1	7	200
	2N3497	120	0.1	40@10/10	0.35@10/1	6	150
	2N3798	60	0.05	150@1/5	0.25@1/0.1	4	100
	2N3799	60	0.05	300@1/5	0.25@1/0.1	4	100
	2N3962	60	0.2	100/450@1/5	0.25@10/0.5	6	40
	2N3963	80	0.2	100/450@1/5	0.25@10/0.5	6	40
	2N3964	45	0.2	250/600@1/5	0.25@10/0.5	6	50
	2N3965	60	0.2	250/600@1/5	0.25@10/0.5	6	50
	2N4026	60	1.0	40/120@100/5	0.15@150/15	20	100
	2N4027	80	1.0	40/120@100/5	0.15@150/15	20	100
	2N4028	60	1.0	100/300@100/5	0.15@150/15	20	100
	2N4029	80	1.0	100/300@100/5	0.15@150/15	20	100
	2N6432	200	0.5	30/150@30/10	0.5@20/2	6	50
	2N6433	300	0.5	30/150@30/10	0.5@20/2	6	50
	BC107	45	0.2	110/450@2/5	0.25@10/0.5	4.5	150
	BC108	25	0.2	120/800@2/5	0.25@10/0.5	4.5	150
	BC109	25	0.2	200/800@2/5	0.25@10/0.5	4.5	150
	2N869A	18	0.2	40/120@10/5	0.15@10/1	6	400

^Available in JAN, JANTX, JANTXV