

Part Number : 1731120036 Product Description : FCT High Power Contact, Male, Straight, Crimp, 0.10μm Gold over

Male, Straight, Crimp, 0.10µm Gold over Nickel Phosphorus Mating Plating, 0.20µm Gold over Nickel Termination Plating, 40.0A,

10-8 AWG

Series Number: 173112 Status: Active

Product Category: D-Sub Contacts Engineering Number: FMP004P204

#### **Documents & Resources**

### **Drawings**

Drawing 1731120036\_sd.pdf

### **Specifications**

Application Specification 2195600660-000.pdf
Packaging Specification 1731120008-PK-000.pdf
Product Specification 2195600660-000.pdf

### **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<u> </u>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2022)4187-DC (10 June 2022)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# Part Details

## General

Status	Active
Category	D-Sub Contacts
Series	173112
Description	FCT High Power Contact, Male, Straight, Crimp, 0.10µm Gold over Nickel Phosphorus Mating Plating, 0.20µm Gold over Nickel Termination Plating, 40.0A, 10-8 AWG
Contact Type	High Power
Magnetic	Yes
Product Family	FCT D-Sub Connectors
Product Name	FCT Products
Туре	Mixed Layout
UPC	889056322775

## Electrical

Current - Maximum per Contact	40.0A
-------------------------------	-------

# Physical

Durability (mating cycles max)	200
Gender	Male
Material - Contact	Copper Alloy
Material - Plating Mating	Gold over Nickel Phosphorus
Material - Plating Termination	Gold over Nickel
Material - Retaining Clip	Copper Alloy
Net Weight	2.400/g
Orientation	Straight
Packaging Type	Bag
Plating min - Mating	0.100µm
Plating min - Termination	0.200µm
Temperature Range - Operating	-55° to +155°C
Termination Style	Crimp

Wire Size (AWG)	8, 10
	_ ,   -

## Use with Part(s)

Description	Part Number
Use With	FCT Mixed Layout Connectors

# **Application Tooling**

## Global

Description	Part Number
FCT Hand Crimp Tool, 8-Step Adjust	<u>1731121731</u>
FCT Locator for High Power Contacts	<u>1731121734</u>
FCT Removal Tool for Size 8 Contacts	<u>1731121747</u>

This document was generated on Sep 09, 2024