

LGH

TE Internal #: 5-830611-1 Circular Power Connectors, Lead Assembly, 10000 VDC, 16 AWG Wire Size, Wire-to-Wire, Wire & Cable, Socket, -55 – 125 °C [-67 – 257 °F]

View on TE.com >

Connectors > Power Connectors > Circular Power > Circular Power Connectors



Connector Product Type: Lead Assembly

Operating Voltage: 10000 VDC

Wire Size: 16 AWG

Connector System: Wire-to-Wire

Sealable: No

Features

Product Type Features

Connector Product Type	Lead Assembly
Connector System	Wire-to-Wire
Sealable	No



Connector & Contact Terminates To	Wire & Cable
Electrical Characteristics	
Operating Voltage	10000 VDC
Body Features	
Positive Stop Ferrule	Without
Contact Features	
Contact Type	Socket
Termination Features	
Termination Method to Wire & Cable	Pre-Terminated to Cable
Dimensions	
Wire Size	16 AWG
Assembly Length	3048 mm[120 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

5-830611-1

Circular Power Connectors, Lead Assembly, 10000 VDC, 16 AWG Wire Size, Wire-to-Wire, Wire & Cable, Socket, -55 – 125 °C [-67 – 257 °F]



Operation/Application

Shielded	No
Packaging Features	
Packaging Quantity	20
Packaging Method	Package
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (4% in Contact/Component)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Yet Reviewed for halogen content

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought

5-830611-1

Circular Power Connectors, Lead Assembly, 10000 VDC, 16 AWG Wire Size, Wire-to-Wire, Wire & Cable, Socket, -55 – 125 °C [-67 – 257 °F]





Documents

Product Drawings LGH 1/2 ELECT MLD END LEAD

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_5-830611-1_AH.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-830611-1_AH.3d_igs.zip

English

Customer View Model

```
ENG_CVM_CVM_5-830611-1_AH.3d_stp.zip
```

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English