# SGRS-2-221-6049 - ACTIVE

### RAYCHEM

TE Internal #: 383631-000 Splices, Parallel Splice, 12 – 14 AWG Wire Size, 4 – 2 mm<sup>2</sup> Wire Size, Sealable, 4000 – 8000 CMA Wire Size, Red, Length 1.485 in [37.7 mm], Bag

View on TE.com >

Terminals & Splices > Splices



Splice Type: Parallel Splice

Wire Size: 4–2mm<sup>2</sup>

Sealable: Yes

Compatible Insulation Diameter Range: 4.5 mm [.175 in]

## Features

## Product Type Features

Splice Type	Parallel Splice
Sealable	Yes
Compatible With Discrete Wire Type	Stranded



## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Primary Product Color	Red
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	4000 – 8000 CMA
Compatible Insulation Diameter Range	4.5 mm[.175 in]
Product Length	37.7 mm[1.485 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	

**C** For support call+1 800 522 6752

08/08/2024 11:55PM | Page 1

## SGRS-2-221-6049

Splices, Parallel Splice, 12 – 14 AWG Wire Size, 4 – 2 mm<sup>2</sup> Wire Size, Sealable, 4000 – 8000 CMA Wire Size, Red, Length 1.485 in [37.7 mm], Bag



Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Method	Bag
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Not Compliant
	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (40% in Solder) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900

ppm per homogenous material. Also BFR /CFR/PVC Free

## Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

## **Compatible Parts**

## SGRS-2-221-6049

Splices, Parallel Splice, 12 – 14 AWG Wire Size, 4 – 2 mm² Wire Size, Sealable, 4000 – 8000 CMA Wire Size, Red, Length 1.485 in [37.7 mm], Bag





TE Part # EG8162-000 HL1920E-230V-EURO

# Customers Also Bought



## Documents

**Product Drawings** SGRS-2-221-6049

English

## Datasheets & Catalog Pages

1654025\_Sec8\_SGRP\_SGRS-X-58\_SGRS

English