

Agastat

TE Internal #: 2-1423164-0

Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) 1.5 – 15 seconds, 10A Contact Current Rating, Off-Delay,

Chassis

View on TE.com >



Relays & Contactors > Relays > Time Delay Relays



Type of Control: **Knob**Input Voltage: **125 VDC**

Timing Range (Off-Time): 1.5 – 15 seconds

Contact Current Rating: 10 A

Mode of Operation: Off-Delay

Features

Configuration Features

Contact Arrangement	2 Form C, DPDT, 2 C/O
Electrical Characteristics	
Input Voltage	125 VDC
Contact Current Rating	10 A
Termination Features	
Relay Connection Type	Terminals

Mechanical Attachment

Terminal Configuration

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis

Screw Terminals

Dimensions

Product Width	82.55 mm[3.25 in]
Product Length	114.8 mm[4.52 in]
Product Height	78.4 mm[3.09 in]

Usage Conditions

Operating Temperature Range	-30 – 75 °C	

Operation/Application



Repeatability (Max)	±5%
Actuating System	DC
Type of Control	Knob
Timing Range (Off-Time)	1.5 – 15 seconds
Mode of Operation	Off-Delay

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





7022PK=RLY,STD,OFF,2P,125VDC,

TE Part #3-1423164-3













TE Part #4-1393159-8 20C318=SPRING,HOLD-DOWN,K10,.0

Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_2-1423164-0_P.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_2-1423164-0_P.3d_igs.zip

English

Time Delay Relays, Knob, 125VDC Input Voltage, Timing Range (Off-Time) 1.5 – 15 seconds, 10A Contact Current Rating, Off-Delay, Chassis



Customer View Model ENG_CVM_CVM_2-1423164-0_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.