

SCHOTTKY BARRIER RECTIFIERS

Reverse Voltage: 150---200V
Forward Current: 15A


FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop, low switching losses
- High surge capacity
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications
- The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- Case:** JEDEC TO-220AB, molded plastic body
- Terminals:** Solderable per MIL-STD-750, Method 2026
- Polarity:** As marked
- Mounting Position:** Any

TO-220AB



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS




Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbol	MBR15150CT	MBR15200CT	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	150	200	V
Maximum RMS voltage	V_{RWS}	135	140	V
Maximum DC blocking voltage	V_{DC}	150	200	V
Maximum average forward total device rectified current @ $T_C=100^\circ C$	$I_{(AV)}$	15		A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	150		A
Maximum instantaneous forward voltage @7.5A	V_F	0.95		V
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	0.2 50		mA
Maximum thermal resistance (Note1)	$R_{\theta JC}$	1.5		°C/W
Operating junction temperature range	T_J	-55 --- +150		°C
Storage temperature range	T_{STG}	-55 --- +150		°C

NOTES: 1. Thermal resistance from junction to case.

www.diode.kr

FIG.1 TYPICAL FORWARD CHARACTERISTICS**FIG.2 FORWARD DERATING CURVE****FIG.3 TYPICAL REVERSE CHARACTERISTICS****FIG.4 PEAK FORWARD SURGE CURRENT**