


# BC846...BC850-AH

## NPN Silicon Epitaxial Transistor

for switching and amplifier applications

### Features


- AEC-Q101 Qualified and PPAP Capable
- Halogen and Antimony Free(HAF), RoHS compliant



1.Base 2.Emitter 3.Collector  
SOT-23 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25\text{ }^\circ\text{C}$ )


Parameter	Symbol	Value	Unit	
Collector Base Voltage	BC846	$V_{CBO}$	80	V
	BC847, BC850	$V_{CBO}$	50	V
	BC848, BC849	$V_{CBO}$	30	V
Collector Emitter Voltage	BC846	$V_{CEO}$	65	V
	BC847, BC850	$V_{CEO}$	45	V
	BC848, BC849	$V_{CEO}$	30	V
Emitter Base Voltage	BC846, BC847	$V_{EBO}$	6	V
	BC848, BC849, BC850	$V_{EBO}$	5	V
Collector Current	$I_C$	100	mA	
Peak Collector Current	$I_{CM}$	200	mA	
Power Dissipation	$P_{tot}$	300	mW	
Junction Temperature	$T_j$	150	$^\circ\text{C}$	
Storage Temperature Range	$T_{stg}$	- 65 to + 150	$^\circ\text{C}$	



# BC846...BC850-AH

## Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit	
DC Current Gain at $V_{CE} = 5\text{ V}$ , $I_C = 2\text{ mA}$	Current Gain Group A					
	B	$h_{FE}$	110	-	220	-
	C	$h_{FE}$	200	-	450	-
Collector Base Cutoff Current at $V_{CB} = 30\text{ V}$	$I_{CBO}$	-	-	15	nA	
Collector Base Breakdown Voltage at $I_C = 100\text{ }\mu\text{A}$	BC846	$V_{(BR)CBO}$	80	-	-	V
	BC847, BC850	$V_{(BR)CBO}$	50	-	-	V
	BC848, BC849	$V_{(BR)CBO}$	30	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 2\text{ mA}$	BC846	$V_{(BR)CEO}$	65	-	-	V
	BC847, BC850	$V_{(BR)CEO}$	45	-	-	V
	BC848, BC849	$V_{(BR)CEO}$	30	-	-	V
Collector Emitter Breakdown Voltage at $I_C = 100\text{ }\mu\text{A}$	BC846, BC847	$V_{(BR)EBO}$	6	-	-	V
	BC848, BC849, BC850	$V_{(BR)EBO}$	5	-	-	V
Collector Emitter Saturation Voltage at $I_C = 10\text{ mA}$ , $I_B = 0.5\text{ mA}$ at $I_C = 100\text{ mA}$ , $I_B = 5\text{ mA}$	$V_{CEsat}$	-	-	250	mV	
	$V_{CEsat}$	-	-	600	mV	
Base Emitter On Voltage at $V_{CE} = 5\text{ V}$ , $I_C = 2\text{ mA}$ at $V_{CE} = 5\text{ V}$ , $I_C = 10\text{ mA}$	$V_{BE(on)}$	580	-	700	mV	
	$V_{BE(on)}$	-	-	720	mV	
Transition Frequency at $V_{CE} = 5\text{ V}$ , $I_C = 10\text{ mA}$ , $f = 100\text{ MHz}$	$f_T$	-	300	-	MHz	
Output Capacitance at $V_{CB} = 10\text{ V}$ , $f = 1\text{ MHz}$	$C_{ob}$	-	-	6	pF	
Input Capacitance at $V_{EB} = 0.5\text{ V}$ , $f = 1\text{ MHz}$	$C_{ib}$	-	9	-	pF	



# BC846...BC850-AH

