

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**


The **ASI TVU0.5A** is Designed for Television Band IV & V Applications up to 860 MHz.

**FEATURES:**

- Common Emitter
- $P_G = 9.5$  dB at 0.5 W/860 MHz
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

$I_C$	2.0 A
$V_{CBO}$	45 V
$V_{CEO}$	25 V
$V_{EBO}$	3.5 V
$P_{DISS}$	31.8 W @ $T_C = 25$ °C
$T_J$	-65 °C to +200 °C
$T_{STG}$	-65 °C to +150 °C
$\theta_{JC}$	33 °C/W

**PACKAGE STYLE .205 4L STUD**


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.976 / 24.800	1.000 / 25.4000
B	.976 / 24.800	1.000 / 25.4000
C	.028 / 0.700	.031 / 0.800
D	.138 / 3.500	
E	.161 / 4.100	.196 / 5.000
F	.098 / 2.500	.110 / 2.800
G	.200 / 5.100	.208 / 5.300
H	.004 / 0.100	.006 / 0.150
I	.425 / 10.800	.465 / 11.800
J	.200 / 5.100	2.05 / 5.200

**ORDER CODE: ASI10641**
**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
$BV_{CBO}$	$I_C = 1.0$ mA			45			V
$BV_{CEO}$	$I_C = 20$ mA			24			V
$BV_{EBO}$	$I_E = 0.25$ mA			3.5			V
$I_{CBO}$	$V_{CB} = 28$ V					0.45	mA
$h_{FE}$	$V_{CE} = 5.0$ V	$I_C = 100$ mA		15		120	---
$P_G$	$V_{CE} = 20$ V	$I_C = 150$ mA	$f = 860$ MHz	9.5			dB
$IMD_1$	$P_{OUT} = 0.5$ W			-58			dBc

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.