


# CP208-2N3767

## NPN - Power Transistor Die

### 4.0 Amp, 80 Volt

The CP208-2N3767 is a silicon NPN power transistor designed for power amplifier and medium speed switching applications.



#### MECHANICAL SPECIFICATIONS:

Die Size	66 x 66 MILS
Die Thickness	12.5 MILS
Base Bonding Pad Size	12 x 24 MILS
Emitter Bonding Pad Size	11 x 14 MILS
Top Side Metalization	Al - 50,000Å
Back Side Metalization	Cr/Ni/Ag - 17,000Å
Scribe Alley Width	3.4 MILS
Wafer Diameter	4 INCHES
Gross Die Per Wafer	2,645

#### MAXIMUM RATINGS: ( $T_A=25^\circ\text{C}$ )





	SYMBOL		UNITS
Collector-Base Voltage	$V_{CBO}$	100	V
Collector-Emitter Voltage	$V_{CEO}$	80	V
Emitter-Base Voltage	$V_{EBO}$	6.0	V
Continuous Collector Current	$I_C$	4.0	A
Continuous Base Current	$I_B$	2.0	A
Operating and Storage Junction Temperature	$T_J, T_{stg}$	-65 to +150	$^\circ\text{C}$

#### ELECTRICAL CHARACTERISTICS: ( $T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
$I_{CBO}$	$V_{CB}=100\text{V}$		10	$\mu\text{A}$
$I_{CEV}$	$V_{CE}=80\text{V}, V_{EB}=1.5\text{V}$		10	$\mu\text{A}$
$I_{CEO}$	$V_{CE}=80\text{V}$		500	$\mu\text{A}$
$I_{EBO}$	$V_{EB}=6.0\text{V}$		500	$\mu\text{A}$
$BV_{CEO}$	$I_C=100\text{mA}$	80		V
$V_{CE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		1.0	V
$V_{CE(SAT)}$	$I_C=1.0\text{A}, I_B=100\text{mA}$		2.5	V
$V_{BE(ON)}$	$V_{CE}=10\text{V}, I_C=1.0\text{A}$		1.5	V
$h_{FE}$	$V_{CE}=5.0\text{V}, I_C=50\text{mA}$	30		
$h_{FE}$	$V_{CE}=5.0\text{V}, I_C=500\text{mA}$	40	160	
$h_{FE}$	$V_{CE}=10\text{V}, I_C=1.0\text{A}$	20		
$C_{ob}$	$V_{CB}=10\text{V}, I_E=0, f=100\text{kHz}$		50	pF

# CP208-2N3767

## Typical Electrical Characteristics



## BARE DIE PACKING OPTIONS

---



### BARE DIE IN TRAY (WAFFLE) PACK

**CT:** Singulated die in tray (waffle) pack.  
(example: CP211-PART NUMBER-CT)

**CM:** Singulated die in tray (waffle) pack 100% visually inspected as per MIL-STD-750, (method 2072 transistors, method 2073 diodes).  
(example: CP211-PART NUMBER-CM)

---



### UNSAWN WAFER

**WN:** Full wafer, unsawn, 100% tested with reject die inked.  
(example: CP211-PART NUMBER-WN)


---



### SAWN WAFER ON PLASTIC RING

**WR:** Full wafer, sawn and mounted on plastic ring,  
100% tested with reject die inked.  
(example: CP211-PART NUMBER-WR)

Please note: Sawn Wafer on Metal Frame (WS) is possible as a special order. Please contact your Central Sales Representative at 631-435-1110.



Visit the Central website for a complete listing of specifications:  
[www.centrasemi.com/bdspecs](http://www.centrasemi.com/bdspecs)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)