



## SUPER FAST GLASS PASSIVATED RECTIFIER

**SF21G THRU SF28G**


**VOLTAGE RANGE** 50 to 1000 Volts  
**CURRENT** 2.0 Ampere

### FEATURES

- Super fast switching
- Glass passivated chip junction
- Low power loss, high efficiency
- Low leakage
- High Surge Capacity
- High temperature soldering guaranteed  
 260°C/10 seconds, 0.375" (9.5mm) lead length

### MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.014ounce, 0.39 gram



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	SF 21G	SF 22G	SF 23G	SF 24G	SF 25G	SF 26G	SF 27G	SF 28G	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	150	200	300	400	500	600	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	105	140	210	280	350	420	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	100	200	300	400	500	600	Volts
Maximum Average Forward Rectified Current 0.375"(9.5mm) lead length at $T_A=55^\circ\text{C}$	$I_{(AV)}$	2.0								Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	50								Amps
Maximum Instantaneous Forward Voltage at 2.0A	$V_F$	0.95			1.25		1.7			Volts
Maximum DC Reverse Current at rated DC blocking Voltage at	$I_R$	$T_A = 25^\circ\text{C}$								$\mu\text{A}$
		$T_A = 125^\circ\text{C}$								
Maximum Reverse Recovery Time Test conditions $I_F = 0.5\text{A}$ , $I_R = 1.0\text{A}$ , $I_{RR} = 0.25\text{A}$	$t_{rr}$	35								nS
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	$C_J$	30				20				pF
Typical Thermal Resistance (NOTE 1)	$R_{\theta JA}$	40								$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	$T_J$	(-55 to +150)								$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	(-55 to +150)								$^\circ\text{C}$

#### Notes:

1. Thermal Resistance from Junction to Ambient with 0.375" (9.5mm) lead length, PCB mounted.



# SUPER FAST GLASS PASSIVATED RECTIFIER

SF21G THRU SF28G

VOLTAGE RANGE 50 to 1000 Volts  
CURRENT 2.0 Ampere

## RATING AND CHARACTERISTIC CURVES SF21G THRU SF28G

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES : 1.Rise Time=7ns max. Input Impedance= 1 magohm. 22pF  
2.Rise time=10ns max. Source Impedance= 50 ohms

SET TIME BASE FO 50/100ns/cm