

BD136-6/10/16
BD138-6/10/16
BD140-6/10/16

Power Transistors
PNP Silicon
45,60,80 Volts

Features

- Halogen free available upon request by adding suffix "-HF"
- Complement with BD135,BD137,BD139
- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	BD136 BD138 BD140	-45 -60 -80	Vdc
Collector-Base Voltage	BD136 BD138 BD140	-45 -60 -80	Vdc
Emitter-Base Voltage	V_{EBO}	-5.0	Vdc
Collector Current	I_C	-1.5	Adc
Base Current	I_B	-0.5	Adc
Total Device Dissipation @ $T_A=25^\circ C$ Derate above $25^\circ C$	P_D	1.25 10	Watt mW/ $^\circ C$
Total Device Dissipation @ $T_C=25^\circ C$ Derate above $25^\circ C$	P_D	1.25 100	Watt mW/ $^\circ C$
Operating & Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ C$
Maximum Thermal Resistance Junction to Case	R_{thJC}	10	$^\circ C/W$
Maximum Thermal Resistance Junction to Ambient Air	R_{thJA}	100	$^\circ C/W$

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
--------	-----------	-----	-----	-------

OFF CHARACTERISTICS


BV_{CEO}	Collector-Emitter Sustaining Voltage $I_C=-30mA, I_B=0$	BD136 BD138 BD140	-45 -60 -80	Vdc
I_{CBO}	Collector Cutoff Current ($V_{CB}=-30Vdc, I_E=0$) ($V_{CB}=-30Vdc, I_E=0, T_C=125^\circ C$)		-0.1 -10	μAdc
I_{EBO}	Emitter Cutoff Current ($V_{BE}=-5.0Vdc, I_C=0$)		-10	μAdc
h_{FE}	DC Current Gain* ($I_C=-5mAdc, V_{CE}=-2Vdc$) ($I_C=-0.5Adc, V_{CE}=-2Vdc$) ($I_C=-150mAdc, V_{CE}=-2Vdc$)		25 25 40	250
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_B=-500mAdc, I_C=-50mAdc$)		-0.5	Vdc
$V_{BE(ON)}$	Base-Emitter ON Voltage ($V_{CE}=-2Vdc, I_C=-0.5Adc$)		-1	Vdc

*Pulse test: Pulse width 300 usec, Duty cycle 2%

Classification of $h_{FE(3)}$

Rank	6	10	16
Range	40-100	63-160	100-250

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7.



BD136-6/10/16
BD138-6/10/16
BD140-6/10/16




Figure 1. Active-Region Safe Operating Area



Ordering Information :

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.