


1. SPECIFICATION

AK-150810-PM-3C2

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 15 mm	
03	Rated Input Power	1.0 W	
04	Max. Input Power	1.5 W for 1 minute	
05	Impedance	$8\Omega \pm 15\%$ at 2KHz 1V	
06	Resonance Frequency (Fo)	1200Hz \pm 20% at Fo, 1V	
07	Sound pressure level	86 dB(0.1W/0.1M) \pm 3 dB	at AVE 1.0, 1.5, 2.0, 2.5 KHz.
		95 dB(1.0W/0.1M) \pm 3 dB	
08	Frequency Range	Fo – 20 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 1.0W(2.83v rms).	

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



WIRE: UL1571,AWG30#
CONNECTOR: Equivalent to MOLEX 51021-0200

TITLE:	DYNAMIC SPEAKER		DRAWN:	Sunny	2016-11-24	SCALE:	2:1	SHEET:	1 of 1
PART NO.	AK-150810-PM-3C2		DESIGNED:	R&D OF AAT		UNITS:	mm		
DWG NO.	CA-K16112401	1 REV	CHECKED:			TOLERANCE ± 0.5			
			APPROVAL:			UNLESS OTHERWISE SPECIFIED:			
			MATERIAL:	PBT		ONE PLACE DECIMAL ± ***			
						TWO PLACE DECIMAL ± ***			
						THREE PLACE DECIMAL ± ***			



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC