


**Reverse Voltage 50 to 1000V Forward Current 1.5A**

## FEATURES

- \* Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- \* High temperature metallurgically bonded construction
- \* Cavity-free glass passivated junction
- \* Capable of meeting environmental standards of MIL-S-19500
- \* Typical IR less than 1.0 $\mu$ A
- \* High temperature soldering guaranteed: 260°C/10 seconds



## Mechanical Data

**Case:** JEDEC SOD123-FL/MINI SMA, molded plastic over glass DIE

**Terminals:** Plated leads, solderable per MIL-STD-750, Method 2026

**Polarity:** Color band denotes cathode end

**Mounting Position:** Any

**Weight:** 0.0155 g

**Handling precaution:** None

We declare that the material of product is Halogen free (green epoxy compound)

## Electrical Characteristic

### 1. Maximum & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	SOD F151-SH	SOD F152-SH	SOD F153-SH	SOD F154-SH	SOD F155-SH	SOD F156-SH	SOD F157-SH	Unit				
Device marking code		G1	G2	G3	G4	G5	G6	G7					
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V				
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V				
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V				
Maximum average forward rectified current lead length at T <sub>C</sub> = 75°C (Note 2)	I <sub>F(AV)</sub>	1.5							A				
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	50							A				
Typical reverse recovery time (Note 1)	trr	150		250		500			ns				
Typical thermal resistance (Note 2)	R <sub>θJA</sub>	75							°C/W				
Operating junction temperature range	T <sub>J</sub>	−55 to +150							°C				
storage temperature range	T <sub>STG</sub>	−65 to +175							°C				

### Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	SOD F151-SH	SOD F152-SH	SOD F153-SH	SOD F154-SH	SOD F155-SH	SOD F156-SH	SOD F157-SH	Unit
Maximum instantaneous forward voltage at 1.5A	V <sub>F</sub>	1.3							V
Maximum DC reverse current T <sub>J</sub> = 25°C at rated DC blocking voltage T <sub>J</sub> = 125°C	I <sub>R</sub>	5.0 100							μA
Typical junction capacitance at 4.0V, 1MHz (Note 2)	C <sub>J</sub>	15.0							PF

#### NOTES:

1. IF = 0.5A, IR = 1.0A, IRR = 0.25A

2. 8.0mm<sup>2</sup> (.013mm thick) land areas

## 2. Characteristic Curves ( TA = 25°C unless otherwise noted )

Fig. 1 - Forward Current Derating Curve




Fig 3. - Typical Instantaneous Forward Characteristics




Fig 5. - typical transient thermal impedance




Fig. 2 - Maximum Non-repetitive Peak Forward Surge Current




Fig 4. - Typical Reverse Characteristics






Fig 6. - Typical Junction Capacitance




### 3. dimension:

SOD123-FL



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	3.5	3.9	0.138	0.159
B	0.75	0.95	0.029	0.037
C	2.6	3.0	0.103	0.119
D	1.6	2.0	0.063	0.079
E	0.45Typ		0.018Typ	
H	0.9	1.2	0.036	0.047
J	0.12	0.22	0.005	0.009
K	0.8Typ		0.032Typ	

Suggested solder pad layout



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD123-FL	0.044(1.10)	0.040(1.00)	0.079(2.00)