


**Major Ratings and Characteristics**

| Characteristics                                    | 200CNQ...  | Units            |
|--|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform                   | 200        | A                |
| $V_{RRM}$ range                                    | 35 to 45   | V                |
| $I_{FSM}$ @tp = 5 $\mu$ s sine                     | 26,000     | A                |
| $V_F$ @100Apk, $T_J = 125^\circ\text{C}$ (per leg) | 0.49       | V                |
| $T_J$ range  | -55 to 150 | $^\circ\text{C}$ |

**Description/Features**

The 200CNQ center tap Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 150  $^\circ\text{C}$  junction temperature. Typical applications are in high current switching power supplies, plating power supplies, UPS systems, converters, free-wheeling diodes, welding, and reverse battery protection.

- 150  $^\circ\text{C}$   $T_J$  operation
- Center tap module
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



## 200CNQ... Series

Bulletin PD-2.257 rev. D 07/01

International  
IR Rectifier

### Voltage Ratings

| Part number                                     | 200CNQ035 | 200CNQ040 | 200CNQ045 |
|---|-----------|-----------|-----------|
| $V_R$ Max. DC Reverse Voltage (V)               | 35        | 40        | 45        |
| $V_{RWM}$ Max. Working Peak Reverse Voltage (V) |           |           |           |

### Absolute Maximum Ratings

| Parameters  | 200CNQ | Units | Conditions   |
|---|--------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current (Per Leg) * See Fig. 5 (Per Device)      | 100    | A     | 50% duty cycle @ $T_C = 114^\circ\text{C}$ , rectangular wave form   |
|   | 200    |       |  |
| $I_{FSM}$ Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7 | 26,000 | A     | 5 $\mu\text{s}$ Sine or 3 $\mu\text{s}$ Rect. pulse<br>10ms Sine or 6ms Rect. pulse<br>Following any rated load condition and with rated $V_{RRM}$ applied |
|   | 1550   |       |  |
| $E_{AS}$ Non-Repetitive Avalanche Energy (Per Leg)                                | 135    | mJ    | $T_J = 25^\circ\text{C}$ , $I_{AS} = 20$ Amps, $L = 0.67$ mH   |
| $I_{AR}$ Repetitive Avalanche Current (Per Leg)                                   | 20     | A     | Current decaying linearly to zero in 1 $\mu\text{sec}$<br>Frequency limited by $T_J$ max. $V_A = 1.5 \times V_R$ typical                                   |

### Electrical Specifications

| Parameters   | 200CNQ | Units            | Conditions  |
|--|--------|------------------|---|
| $V_{FM}$ Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)    | 0.54   | V                | @ 100A<br>$T_J = 25^\circ\text{C}$                                      |
|  | 0.68   | V                | @ 200A  |
|  | 0.49   | V                | @ 100A<br>$T_J = 125^\circ\text{C}$                                     |
|  | 0.64   | V                | @ 200A  |
| $I_{RM}$ Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1) | 10     | mA               | $T_J = 25^\circ\text{C}$  |
|  | 500    | mA               | $T_J = 125^\circ\text{C}$<br>$V_R = \text{rated } V_R$                  |
| $V_{F(TO)}$ Threshold Voltage                                    | 0.32   | V                | $T_J = T_J \text{ max.}$  |
| $r_t$ Forward Slope Resistance                                   | 0.81   | m $\Omega$       |   |
| $C_T$ Max. Junction Capacitance (Per Leg)                        | 5200   | pF               | $V_R = 5V_{DC}$ , (test signal range 100Khz to 1Mhz) $25^\circ\text{C}$ |
| $L_S$ Typical Series Inductance (Per Leg)                        | 7.0    | nH               | From top of terminal hole to mounting plane                             |
| $dv/dt$ Max. Voltage Rate of Change (Rated $V_R$ )               | 10000  | V/ $\mu\text{s}$ |   |

### Thermal-Mechanical Specifications

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2%

| Parameters  | 200CNQ     | Units              | Conditions                           |
|---|------------|--------------------|--------------------------------------|
| $T_J$ Max. Junction Temperature Range                             | -55 to 150 | $^\circ\text{C}$   |                                      |
| $T_{stg}$ Max. Storage Temperature Range                          | -55 to 150 | $^\circ\text{C}$   |                                      |
| $R_{thJC}$ Max. Thermal Resistance Junction to Case (Per Leg)     | 0.40       | $^\circ\text{C/W}$ | DC operation * See Fig. 4            |
| $R_{thJC}$ Max. Thermal Resistance Junction to Case (Per Package) | 0.20       | $^\circ\text{C/W}$ | DC operation                         |
| $R_{thCS}$ Typical Thermal Resistance, Case to Heatsink           | 0.10       | $^\circ\text{C/W}$ | Mounting surface, smooth and greased |
| wt Approximate Weight   | 79 (2.80)  | g (oz.)            |                                      |
| T Mounting Torque   | Min.       | 24 (20)            | Kg-cm<br>(lbf-in)                    |
|   | Max.       | 35 (30)            |                                      |
|   | Typ.       | 13.5 (12)          |                                      |
|   | Max.       | 46 (40)            |                                      |
| Terminal Torque   | Min.       | 35 (30)            |                                      |
|   | Max.       | 46 (40)            |                                      |
| Case Style  | TO-244AB   |                    | Modified JEDEC                       |




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5- Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6- Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

(2) Formula used:  $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$ ;

$Pd$  = Forward Power Loss =  $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);

$Pd_{REV}$  = Inverse Power Loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R @ V_{R1} = 80\%$  rated  $V_R$

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 07/01

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.