


2SA1481/2SC2960**High-Speed Switching Applications****Features**

- Fast switching speed.
- High breakdown voltage.

Package Dimensions

unit:mm

2033



() : 2SA1481

Specifications**Absolute Maximum Ratings at Ta = 25°C**

| Parameter | Symbol | Conditions | Ratings | Unit |
|------------------------------|-----------|------------|-------------|------|
| Collector-to-Base Voltage | V_{CB0} | | (-)60 | V |
| Collector-to-Emitter Voltage | V_{CEO} | | (-)50 | V |
| Emitter-to-Base Voltage | V_{EBO} | | (-)5 | V |
| Collector Current | I_C | | (-)150 | mA |
| Peak Collector Current | I_{CP} | | (-)400 | mA |
| Collector Dissipation | P_C | | 250 | mW |
| Junction Temperature | T_J | | 150 | °C |
| Storage Temperature | T_{stg} | | -55 to +150 | °C |

Electrical Characteristic at Ta = 25°C

| Parameter | Symbol | Conditions | Ratings | | | Unit |
|---|---------------|---------------------------------|---------|---------|--------|---------|
| | | | min | typ | max | |
| Collector Cutoff Current | I_{CBO} | $V_{CB} = (-)400V, I_E = 0$ | | | (-)0.1 | μA |
| Emitter Cutoff Current | I_{EBO} | $V_{EB} = (-)4V, I_C = 0$ | | | (-)0.1 | μA |
| DC Current Gain | h_{FE} | $V_{CE} = (-)6V, I_C = (-)1mA$ | 100* | | 560* | |
| Gain-Bandwidth Product | f_T | $V_{CE} = (-)6V, I_C = (-)1mA$ | | 100 | | MHz |
| Output Capacitance | C_{ob} | $V_{CB} = (-)6V, f = 1MHz$ | | 2.7 | | pF |
| | | | | (4.0) | | pF |
| Collector-to-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C = (-)10mA, I_B = (-)1mA$ | | (-)0.1 | (-)0.4 | V |
| Base-to-Emitter Saturation Voltage | $V_{BE(sat)}$ | $I_C = (-)10mA, I_B = (-)1mA$ | | (-)0.75 | (-)1.1 | V |
| Collector-to-Base Breakdown Voltage | $V_{(BR)CBO}$ | $I_C = (-)10\mu A, I_E = 0$ | (-)60 | | | V |
| Collector-to-Emitter Breakdown Voltage | $V_{(BR)CEO}$ | $I_C = (-)1mA, R_{BE} = \infty$ | (-)50 | | | V |
| Emitter-to-Base Breakdown Voltage | $V_{(BR)EBO}$ | $I_E = (-)10\mu A, I_C = 0$ | (-)5 | | | V |
| Delay Time | t_d | See specified Test Circuit | | 40 | 60 | ns |
| Rise Time | t_r | See specified Test Circuit | | 80 | 130 | ns |
| | | | | (120) | (230) | ns |
| Storage Time | t_{stg} | See specified Test Circuit | | 230 | 450 | ns |
| | | | | (190) | (700) | ns |
| Fall Time | t_f | See specified Test Circuit | | 160 | 250 | ns |
| | | | | (240) | (390) | ns |

* ; The 2SA1481/2SC2960 are classified by 1mA h_{FE} as follows :


| | | | | | |
|-------|-----|-------|-----|-------|-----|
| 100 E | 200 | 160 F | 320 | 280 G | 560 |
|-------|-----|-------|-----|-------|-----|

SANYO Electric Co., Ltd. Semiconductor Business Headquarters







TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

Switching Time Test Circuit









(For PNP, the polarity is reversed.)








$10 I_{B1} = -10 I_{B2} = I_C = 10 \text{ mA}$
Unit (resistance : Ω , capacitance : F)



2SA1481/2SC2960



2SA1481/2SC2960



■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1998. Specifications and information herein are subject to change without notice.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.